

BOURNE1.TXT

UNIX Bourne Shell Programming

Developed by:

User Liaison Section, D-7131
Denver Office

[Name and number removed at author's
request]

Revision Date: February 7, 1991

Page 1

BOURNE1.TXT

- I. INTRODUCTION..... v
 - A. Audience..... v
 - B. Course Objectives..... v
 - C. Course Handout Conventions..... vi

- 1. BOURNESHELL OVERVIEW..... 1
 - 1.1 What is the BourneShell?..... 2
 - 1.2 Making a Bourne Shell Script Executable..... 3
 - 1.3 Tracing Mechanisms..... 6
 - Workshop 1..... 9

- 2. USER, SHELL, AND READ-ONLY SHELL VARIABLES..... 11
 - 2.1 User Variables..... 11
 - 2.2 Shell Variables..... 14
 - 2.2.1 HOME..... 14
 - 2.2.2 IFS..... 15
 - 2.2.3 MAIL..... 15
 - 2.2.4 MAILPATH..... 15
 - 2.2.5 MAILCHECK..... 16
 - 2.2.6 PATH..... 16
 - 2.2.7 PS1..... 17
 - 2.2.8 PS2..... 17
 - 2.3 Read-Only User Variables..... 18
 - 2.4 Read-Only Shell Variables..... 19
 - 2.4.1 Name of the Calling Program..... 19
 - 2.4.2 Arguments..... 19
 - 2.4.3 Shift..... 21
 - 2.4.4 Set..... 22
 - 2.4.5 expr..... 23
 - Workshop 2..... 27

- 3. POSITIONAL PARAMETERS..... 33
 - 3.1 Reading Input Into a Shell Variable..... 34
 - 3.2 Command Substitution..... 36
 - 3.3 Comments in BourneShell Scripts..... 38
 - 3.4 BourneShell Environment - Exporting Variables..... 39
 - Workshop 3..... 41

- 4. CONTROL CONSTRUCTS:..... 45
 - 4.1 Types of Tests Used with Control Constructs:..... 46
 - 4.2 Test on Numeric Values..... 47
 - 4.3 Test on Character Strings..... 47
 - 4.4 Test on File Types..... 49
 - 4.5 if then..... 50
 - 4.6 if then else..... 52
 - 4.7 if then elif..... 54

BOURNE1.TXT

- 4.8 for..... 55
- 4.9 while..... 57
- 4.10 until..... 58
- 4.11 case..... 60
- Workshop 4..... 63

- 5. COMPILING PROGRAMS IN UNIX..... 67
 - 5.1 "C": Sample Program with a Main and Two Functions
in One 67
 - 5.2 "C": Compiling a Program..... 69
 - 5.3 "C": Renaming the Executable Module..... 71
 - 5.4 "C": Giving a Name to the Output File..... 72
 - 5.5 "C": Producing an Assembly Listing..... 73
 - 5.6 "C": Main and Two Functions in Three Separate Source
Files..... 74
 - 5.7 "C": Compiling but Not Producing an Executable
Module..... 75
 - 5.8 FORTRAN: Sample Program a Main and Two Subroutine... 76
 - 5.9 FORTRAN: Compiling a Program..... 77
 - 5.10 FORTRAN: Renaming the Executable Module..... 79
 - 5.11 FORTRAN: Giving a Name to the Output File..... 80
 - 5.12 FORTRAN: Producing an Assembly Listing..... 81
 - 5.13 FORTRAN: Main and Two Subroutines in Three Separate
Source Files..... 82
 - 5.14 FORTRAN: Compiling But Not Producing an Executable
Module..... 83
 - 5.15 FORTRAN: Compiling Object Files to Produce an
Executable Module..... 84
 - 5.16 COBOL: Sample Program with a Main and Two
Subroutines..... 85
 - 5.17 COBOL: Compiling a Program..... 86
 - 5.18 COBOL: Running a Program..... 87
 - Workshop 5..... 89

- 6. UNIX TOOLS..... 95
 - 6.1 Processes..... 95
 - 6.2 Executing a Command..... 95
 - 6.3 Process Identification..... 95
 - 6.4 grep: A Pattern Matching Filter..... 98
 - 6.4.1 More on Regular Expressions..... 99
 - 6.4.2 Closure.....103
 - 6.4.3 Some Nice grep Options104
 - 6.4.4 Summary of Regular Expression Characters.....105
 - 6.5 sed: Edit a File to Standard Output.....106
 - 6.6 awk: A Pattern Matching Programming Language.....110
 - 6.7 sort: Sort a File.....114
 - 6.8 What Other Useful UNIX Tools are Available.....117
 - 6.9 Archiver and Library Maintainer.....118

BOURNE1.TXT

- 6.9.1 ar: Creating an Archive File with Object Modules.....119
- 6.9.2 ar: Verifying the Contents of the Archive File.....119
- 6.9.3 ar: Removing Duplicate Object Files.....120
- 6.9.4 ar: Compiling Main and Archive Files.....120
- Workshop 6.....121

- 7. VAX DCL TO UNIX SHELL SCRIPT CONVERSION.....125
 - 7.1 Processes.....127
 - 7.2 Pipes.....128
 - 7.3 Input, Output, and Error Redirection.....129
 - 7.4 Command Structure and File Naming Conventions.....131
 - 7.5 File Management Commands.....133
 - 7.6 Metacharacters.....135
 - 7.7 Wildcards: Are They Really Wild?.....136
 - 7.8 Summary.....137
 - Workshop 7.....139

- 8. ADVANCED FEATURES OF FTP.....143
 - 8.1 Initializing FTP on UMAX.....144
 - 8.2 Multiple File Transfers.....145
 - 8.3 Auto Login Feature.....146
 - 8.4 Macros.....148
 - 8.5 Filename Translation.....149
 - 8.6 Aborting Transfers.....150
 - 8.7 More Remote Computer Commands.....151
 - Workshop 8.....153

- 9. OPTIONAL CHAPTER - KORNSHELL PROGRAMMING.....155
 - 9.1 KornShell Variables.....155
 - 9.2 User Defined Variables.....157
 - 9.3 Values of Variables Between Child and Parent Processes.....158
 - 9.4 ksh: Aliases.....159
 - 9.5 ksh: Command Line Editing.....161
 - 9.6 ksh: Interactive Command Line Editing.....162
 - 9.7 ksh: Functions.....164
 - 9.8 ksh: The Select Construct.....166
 - 9.9 ksh: Tracing and Conditional Execution.....168
 - Workshop 9.....169

- APPENDIX A - sh.....173
- APPENDIX B - test.....189
- APPENDIX C - expr.....193

BOURNE1.TXT

APPENDIX D - ftp.....	195
APPENDIX E - cc.....	209
APPENDIX F - f77.....	219
APPENDIX G - lint.....	231
APPENDIX H - cb.....	235
APPENDIX I - ar.....	237
APPENDIX J - time.....	243
APPENDIX K - ksh.....	245
INDEX.....	279

I. INTRODUCTION

A. Audience

This course is for individuals who have completed "UNIX for Beginning Users" (or equivalent experience) and want to write UNIX BourneShell script files. A script file contains a sequence of UNIX commands which can be executed by entering one command. It is assumed that the student already has a good understanding of the UNIX operating system, be able to use a UNIX editor, and be familiar with a computer terminal or typewriter keyboard.

B. Course Objectives

Upon successful completion of this course the student will be able to:

1. Write moderately complex BourneShell scripts.
2. Make a BourneShell script executable.
3. Demonstrate how to use the following BourneShell commands: shift, exit, expr, test, if then, if then else, if then elif, for, while, until, and case.

BOURNE1.TXT

4. Use the following BourneShell constructs: tracing mechanisms (for debugging), user variables, BourneShell variables, read-only variables, positional parameters, reading input to a BourneShell script, command substitution, comments, and exporting variables. In addition, test on numeric values, test on file type, and test on character strings are covered.
6. Create a ".profile" script to customize the user environment.
7. Use advanced features of File Transfer Protocol (FTP)
8. Compile source code into object and executable modules.
9. Optional: KornShell programming. This is of primary interest to programmers.
10. Convert VMS DCL command files to UNIX Shell.

C. Course Handout Conventions

There are several conventions used in this handout for consistency and easier interpretation:

1. Samples of actual terminal sessions are single-lined boxed.
2. User entries are shown in bold print and are underlined.

exit

3. All keyboard functions in the text will be bold.

(Ret)	Backspace
Tab	Ctrl-F6
Print (Shift-F7)	Go to DOS (1)

NOTE: (Ret) indicates the Return or Enter key located above the right Shift key.

4. Examples of user entries not showing the computer's response are in dotted-lined boxes.

BOURNE1.TXT

```

3 PID      TTY      TIME      COMMAND      3
3 10443    rt02120  0:01      sh            3
3 10427    rt02120  0:04      ksh           3
3
3 sgavlick rt021e0   Sep 7    13:26        3
3 teacher  rt021b0   Sep 7    14:39        3
3
3 memo     3
3 class_notes 3
3 $        3

```

AAUU

1.2 Making a Bourne Shell Script Executable

A BourneShell script is an ordinary file that contains commands which can be executed in sequence by entering one command at the BourneShell prompt. In order for a script to be executed, it must first be executable. This is done with the chmod command.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat shell_ex 3
3 echo "This is a very simple shell procedure " 3
3 echo "created with the basic echo command " 3
3 echo "and three other very basic commands " 3
3 echo 3
3 ps 3
3 echo 3
3 who 3
3 echo 3
3 ls 3
3 $ 3

```

AAUU

If the ls -l shell_ex command were entered, we would see the protections assigned to this file.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $ls -l shell_ex 3
3 -rw-r--r-- 1 teacher class 66 Sep 7 10:24 shell_ex 3
3 $ 3

```

AAUU

The character in column one is the type of file.

- = ordinary (plain) disk file

BOURNE1.TXT

- d = directory
- b = block special file
- c = character special file
- p = fifo file ("named pipe") special file
- l = symbolic link

Notice that the script file in the previous sample session has the following file protections:

- User - Read and Write
- Group - Read
- Other - Read

No execute permissions have been granted for user, group, or other. If we try to execute this script by typing its name, the following would result.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $shell_ex 3
3 shell_ex: execute permission denied 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

This error message would indicate that execute permission was denied. The BourneShell script could not be executed. To change the permissions for the BourneShell script, use the chmod command.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $chmod 755 shell_ex 3
3 $ls -l shell_ex 3
3 -rwxr-xr-x 1 teacher class 66 Sep 7 10:26 shell_ex 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```


BOURNE1.TXT

```
3 echo "created with the basic echo command " 3
3 echo "and three other very basic commands " 3
3 echo 3
3 ps 3
3 echo 3
3 who 3
3 echo 3
3 ls 3
3 $ 3
```

AAUU

Execute the BourneShell script using the -x option on the call to the shell. The following sample session shows how to do this and it shows the results of the trace.

Sample session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $sh -x shell_ex 3
3 + echo This is a very simple shell procedure 3
3 This is a very simple shell procedure 3
3 + echo created with the basic echo command 3
3 created with the basic echo command 3
3 + echo and three other very basic commands 3
3 and three other very basic commands 3
3 + echo 3
3 3 3
3 + ps 3
3 PID TTY TIME COMMAND 3
3 10443 rt01120 0:01 sh 3
3 10427 rt02120 0:04 ksh 3
3 + echo 3
3 3 3
3 + who 3
3 sgavlick rt021e0 Sep 7 13:26 3
3 teacher rt02120 Sep 7 14:39 3
3 + echo 3
3 3 3
3 + ls 3
3 memo 3
3 class_notes 3
3 $ 3
```

AAUU

The commands as read from the BourneShell script are indicated by the plus sign (+). The next line or lines are the results of the execution of the command. Using this tracing option allows you to see the execution of each command in the script and see the results of that execution.

BOURNE1.TXT

Sample Sesssion:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo person 3
3 person 3
3 $echo $person 3
3 Richard 3
3 $ 3

```

AAÙ
If you want to have imbedded spaces in a variable, it is necessary to quote the string.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $person='Richard and Kathleen' 3
3 $echo $person 3
3 Richard and Kathleen 3
3 $ 3

```

AAÙ

The echo utility copies its arguments to the standard output. The command echo \$person displays the value of the variable person. It will not display \$person because the BourneShell doesn't pass \$person as an argument. The leading dollar sign (\$) causes the BourneShell to substitute the value of the variable and then passes that value to the utility. The echo utility then displays the value of the variable, not its name, never knowing that you called it with a variable. The BourneShell passed the same command line as if you had typed in echo Richard and Kathleen. The BourneShell can be prevented from doing this substitution by entering one of the following:

Sample Sessions:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo $person 3
3 Richard and Kathleen 3
3 $ 3

```

AAÙ

In this session the contents of the variable person are displayed. The BourneShell made the substitution because the variable name person is preceded by a dollar sign (\$).

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo \person 3

```

```

3 $person 3
3 \$ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

In the above example the variable person is preceded by a dollar sign (\$) but the dollar sign has a backslash (\) ahead of it. The backslash has the effect of cancelling the special meaning of the character following the backslash. In this case, the special meaning of the dollar sign is ignored and the substitution is not done.

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo '$person' 3
3 $person 3
3 \$ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

The single quote marks (') causes the characters between the marks to be taken as literal. The shell makes no attempt to interpret the meanings of these characters. The shell passes these characters on with no substitution.

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo "$person" 3
3 Richard and Kathleen 3
3 \$ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

The double quote marks do not prevent the shell from making substitution; and the value of the variable will be displayed by the utility.

2.2 Shell Variables

The BourneShell declares and initializes variables that determine such things as your home directory, what directories the shell will look in when you give commands, how often to look for mail, your prompt, and many other things. We will look at several of these BourneShell variables and their functions. You can assign new values to these variables from the command line or from the execution of the .profile file in your home directory.

2.2.1 HOME

BOURNE1.TXT

The first BourneShell variable that we will look at is the HOME variable. By default, the home directory is the current working directory after you login. The system administrator determines your home directory when you establish an account and places that information in the /etc/passwd file. When you login, the BourneShell gets that pathname and assigns it to the HOME variable.

When you enter a cd command with no argument, the utility takes the name of the directory from the HOME variable and makes it the current working directory. If you change the HOME variable to another directory pathname, the utility will make the new directory the current working directory.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo $HOME 3
3 /user0/rharding 3
3 $cd 3
3 $pwd 3
3 /user0/rharding 3
3 $HOME=/user0/rharding/eng 3
3 $cd 3
3 $pwd 3
3 /user0/rharding/eng 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

This example shows how the value of the HOME variable affects the cd utility. The cd command will use the value of the HOME variable as the pathname for the current working directory.

2.2.2 IFS

This is the internal-field separator BourneShell variable. You can always use a space or tab to separate characters on the command line. When you assign the IFS variable to another character, you can also use this character as the field separator.

Example:

```
.....
. $num_args a:b:c:d .
.....
```

This example shows only one argument, namely a:b:c:d.

```
.....
. $IFS=: .
. $num_args a:b:c:d .
.....
```

BOURNE1.TXT

This example now shows four different arguments; each being separated by the new IFS, (:).

2.2.3 MAIL

The MAIL variable contains the name of the file that the mail (and mailx) utilities use to store your mail. Usually, the absolute pathname of this file is /usr/mail/name, where name is your login name.

Example:

```
.....  
. $MAIL=/usr/mail/rharding .  
.....
```

2.2.4 MAILPATH

This variable contains a list of filenames separated by colons. If set, the BourneShell will inform you when any of these files are modified (i.e. when new mail arrives). Normally, this variable is not set.

2.2.5 MAILCHECK

This variable specifies how often, in seconds, the BourneShell will check for new mail. The default is 600 seconds. If set to 0, it will check for new mail each time before it gives you a prompt.

2.2.6 PATH

This BourneShell variable will describe the directories that will be searched looking for the program that you want to execute. The BourneShell looks in several directories for a file that has the same name as the command that you entered. The PATH variable controls this search path. Normally, the first directory searched is the current working directory. If the program is not found, the search continues in the /bin and then the /usr/bin directory. Generally, these directories contain executable programs. If the program is not found in one of these directories, the BourneShell reports that the program can't be found (or executed).

The PATH variable lists the pathnames in the order in which the search will proceed. The pathnames are separated by a colon (:). If nothing (null string) precedes the colon, that indicates to start the search at the current working directory.

Example:

```
.....
```

BOURNE1.TXT

```
. $PATH=./user0/rharding/bin:/bin:/usr/bin .
. $ .
.....
```

This PATH variable indicates to start the search for the program at the current working directory, then look in the directory /user0/rharding/bin, then /bin, and finally /usr/bin.

If each user has a unique path specified, each user can execute a different program by giving the same command. The search for the program stops when it is satisfied; thus, you can use the same name for your own programs as the standard UNIX utilities. To do this, simply put your program in one of the first directories that the BourneShell searches.

2.2.7 PS1

This is the BourneShell prompt which lets you know that the shell is waiting for you to give it a command. The default BourneShell prompt is a dollar sign (\$). The shell stores the prompt as a string variable in PS1. When you change the value of this variable, the appearance of the prompt will change. When you are working on several different machines, it might be useful to have the prompt be the name of the machine you are working on.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $pwd 3
3 /user0/rharding 3
3 $PS1='domax0: ' 3
3 domax0: 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

Notice that prompt is now domax0:

2.2.8 PS2

This variable is called the secondary prompt. If the command is not completed on one line and must be continued on the next line, the prompt for that continued line is PS2. The default is >. This prompt indicates that the BourneShell is expecting you to finish the previous command line.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo 'demonstration of prompt string' 3
3 >2' 3
```


BOURNE1.TXT

```
3 $readonly person 3
3 $example=Richard 3
3 $readonly example 3
3 $readonly 3
3 readonly person 3
3 readonly example 3
3 $ 3
```

AAUU

2.4 Read-Only Shell Variables

The read-only shell variables are similar to the read-only user variables; except the value of these variables is assigned by the shell, and the user CANNOT modify them.

2.4.1 Name of the Calling Program

The shell will store the name of the command you used to call a program in the variable named \$0.

It has the number zero because it appears before the first argument on the command line.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat name_ex 3
3 echo 'The name of the command used' 3
3 echo 'to execute this script was' $0 3
3 $name_ex 3
3 The name of the command used 3
3 to execute this script was name_ex 3
3 $ 3
```

AAUU

2.4.2 Arguments

The BourneShell will store the first nine command line arguments in the variables named \$1, \$2, ..., \$9. These variables appear in this section because you cannot change them using the equal sign. It is possible to modify them using the set command.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat arg_ex 3
3 echo 'The first five command line' 3
3 echo 'arguments are' $1 $2 $3 $4 $5 3
```

BOURNE1.TXT

```

3 $arg_ex Richard Kathleen Douglas 3
3 The first five command line 3
3 arguments are Richard Kathleen Douglas 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

The script arg_ex will display the first five command-line arguments. The variables representing \$4 and \$5 have a null value.

The BourneShell variable \$* represents all of the command-line arguments as shown in the following example.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAZ
3 $cat display_all 3
3 echo $* 3
3 $display_all Richard Kathleen Douglas 3
3 Richard Kathleen Douglas 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

The BourneShell variable \$# contains the number of arguments on the command line. This is a string variable that represents a decimal number. You can use the expr utility to perform calculations with that number and test to perform logical tests on it.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAZ
3 $cat num_args 3
3 echo 'This script was called with' 3
3 echo $# 'arguments' 3
3 $num_args Richard Kathleen Douglas 3
3 This script was called with 3
3 3 arguments 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

2.4.3 Shift

The shift command promotes each of the command-line arguments. The second argument, represented by \$2, is now the first argument, represented by \$1. The third becomes the second and so on until the last argument becomes the next to last. You can access only the first nine command-line arguments (as \$1 through \$9). The shift command gives you access to the tenth, and the first becomes unavailable. There is no "unshift" command that will return the

BOURNE1.TXT

arguments that are no longer available.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat demo_shift 3
3 echo 'arg1='$1 ' arg2='$2 ' arg3='$3 3
3 shift 3
3 echo 'arg1='$1 ' arg2='$2 ' arg3='$3 3
3 shift 3
3 echo 'arg1='$1 ' arg2='$2 ' arg3='$3 3
3 shift 3
3 echo 'arg1='$1 ' arg2='$2 ' arg3='$3 3
3 shift 3
3 $demo_shift Richard Kathleen Douglas 3
3 arg1=Richard arg2=Kathleen arg3=Douglas 3
3 arg1=Kathleen arg2=Douglas arg3= 3
3 arg1=Douglas arg2= arg3= 3
3 demo_shift: cannot shift 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

The BourneShell will display an error message when the script executes a shift command after it has run out of variables.

2.4.4 Set

The Set command will display a list of all the variables that are set when it has no arguments.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $set 3
3 HOME=/user0/teacher 3
3 IFS= 3
3 3 3
3 LOGNAME=richard 3
3 MAIL=/usr/mail/richard 3
3 MAILCHECK=600 3
3 PATH=./bin:/usr/bin 3
3 PS1=$ 3
3 PS2=> 3
3 SHELL=/bin/sh 3
3 TERM=vt100 3
3 TZ=MST7MDT 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

BOURNE1.TXT

When set is called with arguments, it sets the value of the command-line arguments (\$1-\$n) to the arguments. The example sets the first three arguments.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat set_ex 3
3 set who really cares 3
3 echo $#: $* 3
3 $set_ex 3
3 3: who really cares 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
2.4.5 expr

```

The expr command will perform arithmetic in the BourneShell.

```

EIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII»
o Command format: expr expression o
o
o See Appendix C for a complete list of expressions o
EIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII%

```

The arguments are taken as an expression. After the evaluation has taken place, the result is written to standard output. The terms of the expression must be separated by blanks. Special characters to the shell must be escaped. Strings containing blanks or other special characters must be quoted.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $expr 7 + 8 + 10 3
3 25 3
3 $expr 10 - 8 3
3 2 3
3 $expr 10 '*' 4 3
3 40 3
3 $expr 135 / 5 3
3 27 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

expr will also work with user defined variables as in the following example:

BOURNE1.TXT

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $cat data 3
3 8 3
3 15 3
3 25 3
3 $cat express 3
3 count=0 3
3 tot=0 3
3 for a in `cat data` 3
3 do 3
3 tot=`expr $tot + $a` 3
3 count=`expr $count + 1` 3
3 done 3
3 avg=`expr $tot / $count` 3
3 echo "The average is $avg" 3
3 $ 3

```

AAÙ
Let's execute the script "express" with tracing on so we can follow the execution.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $sh -x express 3
3 count=0 3
3 tot=0 3
3 + cat data 3
3 + expr 0 + 8 3
3 tot=8 3
3 + expr 0 + 1 3
3 count=1 3
3 + expr 8 + 15 3
3 tot=23 3
3 + expr 1 + 1 3
3 count=2 3
3 + expr 23 + 25 3
3 tot=48 3
3 + expr 2 + 1 3
3 count=3 3
3 + expr 48 / 3 3
3 avg=16 3
3 + echo The average is 16 3
3 The average is 16 3
3 $ 3

```

AAÙ

NOTES

BOURNE1.TXT

the substitution.

True/False

Continue on the next page

7. What do the following shell variables do?

HOME

IFS

MAIL

MAILPATH

MAILCHECK

PATH

PS1

BOURNE1.TXT

13. What is displayed when you enter set with no arguments?

Continue on the next page

COMPUTER EXERCISES

14. Login to the Multimax (domax1) using the username and password given to you by the instructor.

15. Create a subdirectory called sub_dir.

16. Modify your .profile to include the following:
 - a) Change the home directory to sub_dir
 - b) Set the internal-field separator to a comma
 - c) Have mail messages saved into mail1.
 - d) Set the PATH to look for programs in the following directories:

```
$HOME/bin  
/bin  
/usr/bin
```
 - e) Change the prompt to reflect the name of the system

BOURNE1.TXT

Insure that the BourneShell script is executable by issuing this command:

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $chmod a+x neat_shell                                     3
3   $                                                         3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

Now, if we type the name of the BourneShell script with no arguments, we get the following results.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $neat_shell                                              3
3                                                         3
3   neat_shell is the name of the shell script              3
3   There were 0 arguments.                                  3
3                                                         3
3   $                                                         3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

In this sample session, there were no arguments given so none were printed. \$0 is the positional parameter that refers to the name of the script. Since there were no arguments given with this invocation of neat_shell, there were zero arguments listed.

3.1 Reading Input Into a Shell Variable

The BourneShell script can read user input from standard input. The read command will read one line from standard input and assign the line to one or more variables. The following example shows how this works.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $cat read_script                                         3
3   echo "Please enter a string of your choice"              3
3   read a                                                    3
3   echo $a                                                  3
3   $                                                         3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

This simple script will read one line from standard input

BOURNE1.TXT

(keyboard) and assign it to the variable a.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $read_script 3
3 Please enter a string of your choice 3
3 Here it is 3
3 Here it is 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

The line read from standard input can also be assigned to several variables as shown in the following example.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat reads 3
3 echo "Please enter three strings" 3
3 read a b c 3
3 echo $a $b $c 3
3 echo $c 3
3 echo $b 3
3 echo $a 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

This time, we will turn on the trace mechanism and follow the execution of this BourneShell script.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $sh -x reads 3
3 + echo Please enter three strings 3
3 Please enter three strings 3
3 + read a b c 3
3 this is more than three strings 3
3 + echo this is more than three strings 3
3 this is more than three strings 3
3 + echo more than three strings 3
3 more than three strings 3
3 + echo is 3
3 is 3
3 + echo this 3
3 this 3

```

```
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA\U
```

It is interesting to note that the spaces separate the values for the variables a,b, and c. For example, the variable a was assigned the string this, the variable b was assigned the string is, and the remainder of the line was assigned to c (including the spaces).

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat read_ex 3
3 echo 'Enter line: \c' 3
3 read line 3
3 echo "The line was: $line" 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA\U
```

In this example, the \c option will suppress the carriage return. The single quote marks protect the backslash from being interpreted by the shell. Also notice that the double quote marks have no effect on the substitution of the variable line.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $read_ex 3
3 Enter line: All's well that ends well 3
3 The line was: All's well that ends well 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA\U
```

3.2 Command Substitution

You can execute a command by enclosing it within two grave accent marks [these are sometimes called backquotes (`)]. The BourneShell will replace the command and the grave marks with the output from the command.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat dir 3
3 dir=`pwd` 3
3 echo 'You are using the' $dir 'directory' 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA\U
```

NOTE: The grave marks lean to the left, and the apostrophes

BOURNE1.TXT

lean to the right. The grave marks enclose the pwd command.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $dir 3
3 You are using the /user0/rharding directory 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

The important thing to notice here is that the pwd command was executed; and the output, /user0/rharding, was then assigned to the variable dir.

It is not necessary to assign the output of a command to a variable as shown in the previous example. The command substitution can occur directly as shown in the next example.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat dir2 3
3 echo 'You are using the' `pwd` 'directory' 3
3 $dir2 3
3 You are using the /user0/rharding directory 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

One final example will show a practical use of command substitution. This BourneShell script will use the date command to provide the date in a useful format.

The normal output from the date command looks like the following.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $date 3
3 Wed Sep 12 18:02:05 MDT 1990 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

Here's a BourneShell script that rearranges the output into a more useable format.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;

```

BOURNE1.TXT

```

3 $cat dateset 3
3 set `date` 3
3 echo $* 3
3 echo 3
3 echo 'Argument 1:' $1 3
3 echo 'Argument 2:' $2 3
3 echo 'Argument 3:' $3 3
3 echo 'Argument 4:' $4 3
3 echo 3
3 echo $2 $3, $6 3
3 $dateset 3
3 Wed Sep 12 18:02:05 MDT 1990 3
3 3
3 Argument 1: Wed 3
3 Argument 2: Sep 3
3 Argument 3: 12 3
3 Argument 4: 18:02:05 3
3 3
3 Sep 12, 1990 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

The first command in the BourneShell script dateset uses the grave accent marks to set the command-line argument variables to the output of the date command. The next commands show the first four of these argument variables. The final command displays the arguments in a different order that could be useful in a report or a letter.

3.3 Comments in BourneShell Scripts

Comments can be inserted into the BourneShell script by beginning each comment line with the pound symbol (#) or a colon (:). All characters after the comment character will be ignored by the shell. The only exception to this rule is that the first character of the first line must not be a pound symbol; if the first character is a pound sign, the BourneShell tries to execute the script as if it was written in CShell syntax.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat com_sub 3
3 # The first line sets your present working directory 3
3 # to the variable 'directory' 3
3 directory=`pwd` 3
3 # The second line sets the date to the variable 'when' 3
3 when=`date` 3

```

BOURNE1.TXT

```
3 : The third line will echo on the screen 3
3 echo "You are in $directory on $when" 3
3 : You could have said echo : 3
3 : "You are in `pwd` on `date`" 3
3 : to have a one line program 3
3 $ 3
```

ÀAAÀ

3.4 BourneShell Environment - Exporting Variables

Within a process, you can declare, initialize, read, and modify variables. The variable is local to that process. When a process forks a child process, the parent process does not automatically pass the value of the variable to the child process.

Here is an example of the variables not being exported.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÀ;
3 $cat no_export 3
3 car=mercedes # set the variable 3
3 echo $0 $car $$ # $0 = name of file executed 3
3 # $car =value of variable car 3
3 # $$ = PID number (process id) 3
3 inner # execute another BourneShell script 3
3 echo $0 $car $$ # display same as above 3
3 $cat inner 3
3 echo $0 $car $$ # display variables for this process 3
3 $chmod a+x no_export 3
3 $chmod a+x inner 3
3 $no_export 3
3 no_export mercedes 4790 3
3 inner 4792 3
3 no_export mercedes 4790 3
3 $ 3
```

ÀAAÀ

When no_export was executed, it, of course, assigned a value of mercedes to the variable car and printed it out. The call to inner created a child process. Its PID is 4792, while the parent PID is 4790. Notice, when inner tried to print the value of car, it printed nothing. The reason is because the value of car was not passed by the parent.

Can the value be passed from parent to child process? Yes, by using the export command. Let's look at an example.

Sample Session:

BOURNE1.TXT

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat export_it 3
3 car=mercedes 3
3 export car 3
3 echo $0 $car $$ 3
3 inner1 3
3 echo $0 $car $$ 3
3 $cat inner1 3
3 echo $0 $car $$ 3
3 car=chevy 3
3 echo $0 $car $$ 3
3 $chmod a+x export_it 3
3 $chmod a+x inner1 3
3 $export_it 3
3 export_it mercedes 4798 3
3 inner1 mercedes 4800 3
3 inner1 chevy 4800 3
3 export_it mercedes 4798 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

In the `export_it` BourneShell script, the variable `car` was initialized to `mercedes`; and then it was exported. This means that the value of `car` is now available to a child process. When `inner1` prints out the value of `car` it has the value of `mercedes`. This is as we expect because the value of `car` was exported from the parent. The next line of `inner1` changes the value of `car` to `chevy`. This is shown in the next line of the sample session. The last line of the session shows the return to the parent process and the value is still `mercedes`. How is this possible?

Exporting variables is only valid from the parent to the child process. The child process cannot change the parent's variable.
Workshop 3

This workshop will reinforce your understanding of the ideas presented in Chapter 3. Login to the Multimax using the username and password given to you by the instructor. Each student is to complete the entire workshop.

DESK EXERCISES

1. What is the positional parameter that represents the name of the command?

BOURNE1.TXT

2. What positional parameter stands for the number of arguments on the command line?

3. What command will read one line from standard input and assign the value to a variable?

4. What character is used to indicate command substitution?

5. What are the two characters that indicate comments in BourneShell scripts?

Continue on the next page

6. Why is it bad practice to put a pound sign (#) in the first character position of the first line of a BourneShell script?

7. Variables set by the parent process are automatically

BOURNE1.TXT

known to the child process.

True/False

8. What command will allow the value of a variable to be passed to a child process?

9. Can a child process change the value of the parents' variable? Why?

COMPUTER EXERCISES

10. Write a BourneShell script called "reverse_it" that has three strings as parameters and then display the strings in opposite order. Be sure to include appropriate comments.

Hint: positional parameters

11. Write a BourneShell script called "read_it" that does the same as question 10 but prompts the user to enter each string separately. How would you trace the execution of this script. Do it!

Continue on the next page.

12. Write a BourneShell script that uses the output of the "date" command and changes it

from:

Wed Sep 12 18:02:05 MDT 1990

BOURNE1.TXT

```

ÛAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÛ
3 $cat test_string 3
3 number=1 3
3 numero=0001 3
3 if test $number = $numero 3
3 then echo "String values of $number and $numero are equal" 3
3 else echo "String values of $number and $numero not equal" 3
3 fi 3
3 if test $number -eq $numero 3
3 then echo "Numeric values of $number and $numero are equal" 3
3 else echo "Numeric values of $number and $numero not equal" 3
3 fi 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```

Let's follow the execution of this script with tracing.

Sample Session:

```

ÛAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÛ
3 $sh -x test_string 3
3 number=1 3
3 numero=0001 3
3 + test 1 = 0001 3
3 + echo String values of 1 and 0001 are not equal 3
3 String values of 1 and 0001 are not equal 3
3 + test 1 -eq 0001 3
3 + echo Numeric values of 1 and 0001 are equal 3
3 Numeric values of 1 and 0001 are equal 3
3 $chmod a+x test_string 3
3 $test_string 3
3 String values of 1 and 0001 are not equal 3
3 Numeric values of 1 and 0001 are equal 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

```

4.7 if then elif

The format for this construct is:

```

ÉIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII»
o Command Format: if expression o
o then commands o
o elif expression o
o then commands o
o else commands o
o fi o
ÈIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII%

```


BOURNE1.TXT

4. Write a BourneShell script using the "if then else" construct that will check for equality of two strings that are supplied as parameters to the script. Output a message stating if the strings are equal or not equal.

5. Write a BourneShell script using the "if then elif" construct that will check two numbers, input as parameters, and tell if the first parameter is greater than, equal to, or less than the second number. Output appropriate error messages.

6. Write a BourneShell script using the "for" construct that has a loop index called "fruit" and an argument list as follows: apples oranges bananas pears. Echo the name of each argument to the monitor screen and when the last argument is listed output an appropriate message.

Continue on the next page

7. Write a BourneShell script using the "while" construct that will add all the numbers between 0 and 9 and display the result. The sum of the digits 0 through 9 is 45.

AAU

5.2 "C": Compiling a Program

To compile the previous example program into an executable module, enter the following command at the command line.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cc hello.c                                     3
3 $                                               3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

Without any options, cc accepts C source code and assembly language programs that follow the conventions outlined above. It will compile, assemble, and load these programs to produce an executable called a.out. The cc utility puts the object code in files with the same base filename (everything before the period) as the source but with a filename extension of .o . The a.out stands for assembly output. This is the default.

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cc hello.c                                     3
3 $a.out                                           3
3 Hello from main!                               3
3                                                 3
3 Calling function1!                             3
3                                                 3
3             Hello from function1!              3
3                                                 3
3             Back from function1!                3
3                                                 3
3 Calling function2!                             3
3                                                 3
3             Hello from function2!              3
3                                                 3
3             Back from function2!                3
3                                                 3
3 That's all!                                    3
3 $                                               3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

NOTE: The a.out file that was created by the cc utility has the following permissions:

BOURNE1.TXT

user - read, write, and execute
group - read and execute
other - read and execute

It is not necessary for you to change the permissions using the chmod command because the cc utility set the execute permissions for you.

5.3 "C": Renaming the Executable Module

You can rename the executable module using the mv command. The file permissions will be the same as before the file is renamed.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $mv a.out hello 3
3 $hello 3
3 Hello from main! 3
3 3
3 Calling function1! 3
3 3
3 Hello from function1! 3
3 3
3 Back from function1! 3
3 3
3 Calling function2! 3
3 3
3 Hello from function2! 3
3 3
3 Back from function2! 3
3 3
3 That's all! 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

5.4 "C": Giving a Name to the Output File

It is possible to have the output sent to a file you specify instead of a.out by using the following command:

```
EIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII»
o Command Format: cc -o output source o
o o o
o output - the name of the executable file o
o o o
```


BOURNE1.TXT

The a.out stands for assembly output. This is the default.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $f77 hello.f 3
3 $a.out 3
3 Hello from main! 3
3 3
3 Calling function1! 3
3 3
3 Hello from function1! 3
3 3
3 Back from function1! 3
3 3
3 Calling function2! 3
3 3
3 Hello from function2! 3
3 3
3 Back from function2! 3
3 3
3 That's all! 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

NOTE: The a.out file that was created by the f77 utility has the following permissions:

- user - read, write, and execute
- group - read and execute
- other - read and execute

It is not necessary for you to change the permissions using the chmod command because the f77 utility set the execute permissions for you.

5.10 FORTRAN: Renaming the Executable Module

You can rename the executable module using the mv command. The file permissions will be the same as before the file is renamed.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $mv a.out hello 3
3 $hello 3

```


BOURNE1.TXT

4. "C": What command can be used to rename the executable file produced by the cc compiler? What are the file protections associated with the executable?

5. "C": What option will produce an assembly listing? What is the filename extension of this file?

Continue on the next page

6. "C": What command will compile the source code program but will not load object files but will keep the object files in files with extensions of .o?

7. FORTRAN: What is the command to invoke the compiler?

8. FORTRAN: What is the filename extension for source code programs?

9. FORTRAN: What is the name of the default executable file?

BOURNE1.TXT

10. FORTRAN: How can you change the permissions on the executable module so anyone can execute it?

11. FORTRAN: What option on the call to the compiler will allow you to specify the name of the executable file?

Continue on the next page

12. FORTRAN: What option on the call to the compiler will produce an assembly listing? What is the filename extension of this file?

13. FORTRAN: What option will produce object modules but not produce an executable module?

14. FORTRAN: What command will produce an executable module from several object modules?

15. COBOL: What is the command to call the compiler?

BOURNE1.TXT

The grep utility searches files for a pattern and displays all lines that contain the pattern. It uses limited-regular-expressions (these are expressions that have string values that use a subset of all the possible alphanumeric and special characters) like those used with ed to match the patterns.

Be careful using the characters \$, *, [, ^, |, (,), and \ in the regular expression because they will be evaluated by the shell. It is good practice to enclose the regular expression in single quotes. This will prevent the shell from evaluating these special characters.

The grep utility will assume standard input if no files are given. Normally, each line found in the file will be displayed to standard output.

Sample session:

```
.....  
. $grep 'disc' memo .  
.....
```

This command will search the file "memo" for the string "disc". It will include words like discover and indiscreet because they contain the characters "disc". The single quote marks are not necessary and for this example they wouldn't have made any difference. They do allow you to include spaces in the search pattern.

6.4.1 More on Regular Expressions

The grep command can be best understood by a discussion of regular expressions. Let's create a database of phone numbers called phone.lis and then use regular expressions to search through the database. Here is a listing of the contents of phone.lis

Sample session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÀ;  
3 $cat phone.lis 3  
3 Smith, Joan 7-7989 3  
3 Adams, Fran 2-3876 3  
3 StClair, Fred 4-6122 3  
3 Jones, Ted 1-3745 3  
3 Stair, Rich 5-5972 3  
3 Benson, Sam 4-5587 3  
3 $ 3  
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

BOURNE1.TXT

The format for the records in this database is:

Last name, First name <tab> #-####

Using the database (phone.lis) above. What grep command would we use to search through the database and get all the records that had a person whose name contains an "S".

An alphabetic character represents itself.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep S phone.lis                                     3
3   Smith, Joan           7-7989                          3
3   StClair, Fred        4-6122                          3
3   Stair, Rich          5-5972                          3
3   Benson, Sam          4-5587                          3
3   $                                                            3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

This grep command searched for the string "S" and then listed all the lines in phone.lis that matched. A single . (dot) is used to represent any single character.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep .S phone.lis                                    3
3   Benson, Sam         4-5587                            3
3   $                                                            3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

A \$ represents the end of the line.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep 5$ phone.lis                                    3
3   Jones, Ted           1-3745                          3
3   $                                                            3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

A ^ represents the beginning of the line

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;

```

BOURNE1.TXT

```

3   $grep ^S phone.lis           3
3   Smith, Joan      7-7989       3
3   StClair, Fred   4-6122       3
3   Stair, Rich     5-5972       3
3   $                3

```

ÀAAÀ

Regular expressions must get to grep in order for them to be evaluated properly. Let's say we want to get the records of employees that have a phone number that begins with a "4".

What does the following expression do?

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÀ;
3   $grep <tab>4 phone.lis       3
3   StClair, Fred      4-6122       3
3   Jones, Ted        1-3745       3
3   Benson, Sam       4-5587       3
3   $                3

```

ÀAAÀ

Why did we get the record of Ted Jones? The tab character was evaluated by the shell and so the search was actually made looking for a "4". This is the same as if we had entered \$grep 4 phone.lis. We must prevent the shell from evaluating these characters, this is done with the \ (backslash) character as shown in the next example.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÀ;
3   $grep \<<tab>4 phone.lis       3
3   StClair, Fred      4-6122       3
3   Benson, Sam       4-5587       3
3   $                3

```

ÀAAÀ

Now it worked properly. It searched for a <tab> character followed by the number 4. The [] (left and right brackets) are used to identify a range of characters.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÀ;
3   $grep \[AF] phone.lis       3
3   Adams, Fran       2-3876       3

```

BOURNE1.TXT

```

3   StClair, Fred           4-6122           3
3   $                       3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

Why do [] need to be quoted? In the previous example the search makes a match on "A" or "F" .

A - (dash) can indicate inclusion. For example, we want to make a match on a phone number that has a 1, 2, 3, or 4. How can this be done? Here's an example:

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep \[1-4] phone.lis           3
3   Adams, Fran           2-3876           3
3   StClair, Fred         4-6122           3
3   Jones, Ted            1-3745           3
3   Stair, Rich           5-5972           3
3   Benson, Sam           4-5587           3
3   $                       3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

A ^ character looks for all characters NOT inside the [] brackets.

For example,

[^0-9] matches all non-digits

[^a-zA-Z] matches all non-alphabetic characters

Note: \, *, and \$ lose their meta-character meanings inside the []. Also the ^ character is special only if it appears first.

What is the following command searching for?

Sample Session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep '[^789]$\ ' phone.lis           3
3   Adams, Fran           2-3876           3
3   StClair, Fred         4-6122           3
3   Jones, Ted            1-3745           3
3   Stair, Rich           5-5972           3
3   $                       3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

6.4.2 Closure

BOURNE1.TXT

The * (asterisk) represents zero or more of the characters preceding the asterisk.

A* represents 0 or more As.

AA* represents 1 or more As.

[0-9]*\$ 0 or more digits at the end of a line
(last four digits in a phone number)

.* represents 0 or more of any character.

How would you write a grep command using regular expressions to find the last name starting with an "S" and the first name with an "F"?

^S Begins with an "S"

.*,F Any number of characters before ,F

Sample session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep ^S.\*,F phone.lis 3
3   StClair, Fred 4-6122 3
3   $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

Note: The * (asterisk) was quoted so the shell didn't try to evaluate it.

It is very desirable to quote the entire string to keep the shell from doing an expansion or substitution. It also increases readability of the regular expression as in the following example:

Sample session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $grep '^S.\*, F' phone.lis 3
3   StClair, Fred 4-6122 3
3   $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

6.4.3 Some Nice grep Options

BOURNE1.TXT

The grep provides several options that modify how the search is performed.

- c Report count of matching lines only
- v Print those lines that don't match the pattern.

What will these lines print?

Sample session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3   $grep -c '[J-Z]' phone.lis                                     3
3   5                                                               3
3   $                                                               3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

Why did we get this result? Let's analyze the command. In English, this command could be interpreted to mean "Tell me how many records in the file "phone.lis" contain a letter from the set J through and including Z." Look at the phone.lis file and see that five records fit this restriction. So the answer is 5.

Now look at another example and see what this one does.

Sample session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3   $grep -v '[J-Z]' phone.lis                                     3
3   Adams,Fran           2-3876                                   3
3   $                                                               3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

Why is this the only record that was found? The -v option says to select records that don't match the pattern. This is the same pattern as the previous example and therefore it selects records that don't match the pattern. The "Adams" record is the only one that doesn't make a match. It doesn't have a character from the set J through and Z.

6.4.4 Summary of Regular Expression Characters

- ^ Beginning of the line
- \$ End of the line

textual address /regular-expression/

Note: Forward slashes enclose textual addresses

The sed instructions indicate what editing function to perform. Here some useful sed instructions:

- s substitute
- d delete

Note: Most sed command lines contain spaces or metacharacters and they should be quoted to protect them from the shell. There are many more editing commands provided by sed. Here is a sample sed command to edit the records in the database file that we are already familiar with, namely, phone.lis:

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $sed /s/Smith/Smythe/ phone.lis 3
3 Smythe, Joan 7-7989 3
3 Adams, Fran 2-3876 3
3 StClair, Fred 4-6122 3
3 Jones, Ted 1-3745 3
3 Stair, Rich 5-5972 3
3 Benson, Sam 4-5587 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

sed is an editor . It simply copies the standard input to the standard output, editing the lines that match the indicated address. The original file is not changed.

Here's another example of a sed command.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $sed '2,4 s/2$/3/' phone.lis 3
3 Smith, Joan 7-7989 3
3 Adams, Fran 2-3876 3
3 StClair, Fred 4-6123 3
3 Jones, Ted 1-3745 3
3 Stair, Rich 5-5972 3
3 Benson, Sam 4-5587 3

```

```
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU
```

What does this sed command do? If you read command in English it reads like this: On lines 2 through 4 substitute the 2 at the end of the line with a 3. Notice that the phone number for StClair,Fred changed from 4-6122 to 4-6123. The number for Stair,Rich didn't change because it was outside the range.

The sed utility can also be use to delete parts of a line of data. This is done by substituting nothing for the parts you want to delete. It looks like this:

Sample session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $sed 's/^.*, //' phone.lis 3
3 Joan 7-7989 3
3 Fran 2-3876 3
3 Fred 4-6122 3
3 Ted 1-3745 3
3 Rich 5-5972 3
3 Sam 4-5587 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU
```

Reading this command it means:

Substitute from the beginning of the line followed by any number of characters followed by a comma with the null string (nothing). This has the effect of removing the text.

Here's a delete command and how it's used.

Sample session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $sed d phone.lis 3
3 $ 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU
```

Why is there no output? Well, it read standard input and did the editing function on all the selected lines. Since no lines were specified all lines were selected to be edited. The editing was to delete the line.

Question: Has the original file been destroyed?

BOURNE1.TXT

Multiple commands are allowed in sed. Each instruction is applied to each input line.

Sample session:

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $sed '/Stair/d'                               3
3   >/Adams/d' phone.lis                          3
3   Smith, Joan           7-7989                  3
3   StClair, Fred        4-6122                   3
3   Jones, Ted           2-1136                   3
3   Benson, Sam          4-5587                   3
3   $                                                    3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

The records for Adams and Stair have both been removed from the database.

Note: The > character is the BourneShell secondary prompt.

6.6 awk: A Pattern Matching Programming Language

Suppose you wanted to change the format of the database phone.lis to be the first name followed by the last name. There is no easy way to do this with sed. Fortunately, UNIX not only provides a stream editor (sed) but it also has a formatting tool. The formatting tool in UNIX is called awk. This tool is named after authors who wrote it Alfred V. Aho, Peter J. Weinberger, and Brian W. Kerningham so it really doesn't have any meaning.

The awk utility is a pattern scanning and processing language. It will search one or more files for a specified pattern and then performs an action, such as writing to standard output or incrementing a counter when it finds a match. You can use awk to generate reports or filter text. It works equally well with numbers or text. The authors designed it to be easy to use and sacrificed execution speed toward this end.

While the sed utility allows us to change the text in a stream, awk allows us to rearrange, add, or delete text in a stream, easily.

The awk takes advantage of many constructs from the C programming language. It has the following features:

- flexible format
- conditional execution

BOURNE1.TXT

```
print [expression-list] [>expression]
printf format [,expression-list][>expression]
next # skip remaining pattern on this input line
exit # skip the rest of the input
```

Statements are terminated by semi-colons, new-lines (CR), or right braces.

Let's look at the syntax for awk in a little simpler manner.

```
awk 'commands' [filename]
```

An awk program (commands) consists of a optional pattern to match and an action to perform if a match is found on the current line. This syntax looks like this:

```
awk '/pattern/{action}' [filename]
```

The pattern used is a regular expression enclosed in forward slashes. If no pattern is listed, the action will be performed for every line. An action can contain several commands. There can be multiple patterns and actions.

```
awk '/pattern1/{action1}
/pattern2/{action2}' [filename]
```

One of awks commands is print. It puts the current line on standard output.

Sample session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3
3 $awk '{print}' phone.lis 3
3 Smith, Joan 7-7989 3
3 Adams, Fran 2-3876 3
3 StClair, Fred 4-6122 3
3 Jones, Ted 1-3745 3
3 Stair, Rich 5-5972 3
3 Benson, Sam 4-5587 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

The awk splits every input line at whitespace and keeps track of

BOURNE1.TXT

the number of fields on each line and counts the number of lines read. Each field is identified by its field number and a \$.

\$1 Identifies the first field

\$2 Identifies the second field

.

\$0 Identifies the entire line

NF Identifies the number of fields on the line

NR Identifies the number of lines that have been read

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3                                                                    3
3  $awk '{print NR,$1}' phone.lis                                     3
3  1 Smith,                                                           3
3  2 Adams,                                                            3
3  3 StClair,                                                           3
3  4 Jones,                                                             3
3  5 Stair,                                                             3
3  6 Benson,                                                            3
3  $                                                                      3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÛ

```

To change the order of the names in phone.lis use awk. The comma in the print command tells awk to separate each field with a space. Without the comma, the output would have no spacing.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3  $awk '{print $2, $1 "<tab>"$3}' phone.lis                           3
3  Joan Smith,                7-7989                                  3
3  Fran Adams,                2-3876                                  3
3  Fred StClair,              4-6122                                  3
3  Ted Jones,                 1-3745                                  3
3  Rich Stair,                5-5972                                  3
3  Sam Benson,                4-5587                                  3
3  $                                                                      3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÛ

```

6.7 sort: Sort a File

The sort utility sorts line of all the named files together and

BOURNE1.TXT

- b Ignore leading blank spaces
- d Dictionary sort - ignore non alphanumeric characters
- m Merge two sorted files together
- n Sort the list as numbers not digit characters

Notice the -f options folds lower case into upper case. This option will make the sort for our problem work correctly. Here's the sample.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÿ
3  $grep '<tab>[45]' phone.lis|sed 's/<tab>/<tab>73/'|sort -f 3
3  Benson, Sam          734-5587          3
3  Stair, Rich         735-5972          3
3  StClair, Fred       734-6122          3
3  $                   3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

The sort can also be directed to use only a portion of the line as a sorting key versus the entire line. The utility will automatically break each line into fields at whitespace delimiters. You can use a character other than whitespace by using the -t option. The fields are set up like this:

```

      0      1      2
    /----|/----|/-----|
Adams, Fran          2-3876

```

In order to sort by the second field here is the sort command to enter.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÿ
3  $sort +1 phone.lis 3
3  Adams, Fran        2-3876          3
3  StClair, Fred      4-6122          3
3  Smith, Joan        7-7989          3
3  Stair, Rich        5-5972          3
3  Benson, Sam        4-5587          3
3  Jones, Ted         1-3745          3
3  $                   3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

Here's a sample of a sort on the 3rd field.

BOURNE1.TXT

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $sort +2 phone.lis                                     3
3   Jones, Ted      1-3745                                 3
3   Adams, Fran    2-3876                                 3
3   Benson, Sam    4-5587                                 3
3   StClair, Fred  4-6122                                 3
3   Stair, Rich    5-5972                                 3
3   Smith, Joan    7-7989                                 3
3   $                                                       3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

A sort can also be performed by a character position within a field. Here's the sample.

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   $sort +2.4 phone.lis                                   3
3   StClair, Fred   4-6122                                 3
3   Benson, Sam     4-5587                                 3
3   Jones, Ted      1-3745                                 3
3   Adams, Fran    2-3876                                 3
3   Stair, Rich    5-5972                                 3
3   Smith, Joan    7-7989                                 3
3   $                                                       3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

Note: The first character of a field is the delimiter for that field

6.8 What Other Useful UNIX Tools are Available

As stated from the beginning, one of the maxims used to develop UNIX was that tools would continue to be developed. Here is a list of tools that might be of interest to you.

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3   UNIX Tool      Description                               3
3                                                         3
3   comm           Compares two sorted file and reports      3
3                 differences                               3
3                                                         3
3   cut            Select columns or fields from lines in a   3
3                 field (System V only)                   3
3                                                         3
3   diff           Report the differences between two files  3

```


BOURNE1.TXT

The key command to list the table of contents is t. The t command will print a table of contents of the archive file. When the v option is used with the t command it will give a long listing of all information about the files.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $ar tv functs.a 3
3 rw-r--r-- 115/ 200 448 Sep 27 09:56 1990 funct1.o 3
3 rw-r--r-- 115/ 200 448 Sep 27 09:56 1990 funct2.o 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

This output shows that there are two members in this archive file, namely, funct1.o and funct2.o.

The protections of these files is:

- owner - read and write
group - read
other - read

The fields are, left to right, the file protections, owner, group, size (in bytes), creation date and time, and finally the name of the constituent.

6.9.3 ar: Removing Duplicate Object Files

Once the archive has been created and verified, the object files in your directory can be deleted. This can be accomplished with the rm command.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $rm funct?.o 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

The question mark (?) is a wildcard that stands for any single character. The files funct1.o and funct2.o no longer exist in your subdirectory.

6.9.4 ar: Compiling Main and Archive Files

BOURNE1.TXT

5. What is the UNIX command to find the PIDs associated with the controlling terminal? What option is needed to get detailed information?

6. What does the UNIX command grep do?

Continue on the next page

7. What do the following regular expressions represent?

`^Ba`

`.*`

`BB*`

`J*`

`[0-9]*$`

8. What does the UNIX command sed do?

BOURNE1.TXT

15. Write a grep command that finds all the phone numbers that don't begin with a 4, 5, or 6.

16. Write a grep command that finds all entries beginning with J-Z and ending with a 2 or 5.

17. Put a 23 in front of every phone number. (Hint:sed)

18. Replace the first name with the person's first initial and a period.

Continue on the next page

19. Task: A new phone system has been installed and people with phone extensions beginning with 4 or 5 now have a new prefix: 73. Create a file of only the people with the new phone numbers.

20. Print out the phone list showing last name and first name in the following format and sorted by last name.

First name <tab> Last name

That's enough, don't you think?

7. VAX DCL TO UNIX SHELL SCRIPT CONVERSION

This chapter will describe the steps necessary to convert DCL command files into Shell scripts. It is not a one to one conversion and many features found in one operating system are not found in the other. This requires you to write shell scripts that emulate features of the other. This is especially true of VAX and UNIX. The best way to accomplish this is to know exactly what it is that the command file does in VMS and then write the equivalent function in a shell script. There are few features that are the similar and those will be examined.

There is really no "best" way to approach this subject. VMS and UNIX are both unique operating systems. Much of the material covered in this course up to this point will be used in the conversion process. We will start with a list of standard UNIX tools and their VMS equivalents. This will give a you a flavor of the kinds of tools each operating system has to offer.

```

UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
^Major Tool          VMS          UNIX          3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA `
3
3
3Editors            EDT          ed            3
3                  TECO          ex            3
3                  TPU          vi            3
3
3Communications     MAIL         mail          3
3                  REPLY        write         3
3                  PHONE        talk          3
3                  DECnet       ftp           3
3                  telnet       telnet        3
3
3Compilers          FORTRAN     f77           3
3                  cc            cc            3
3
3Text Processing   RUNOFF     troff         3
3                  nroff        nroff         3
3                  awk           awk            3
3                  lex           lex            3
3                  sed           sed            3
3
3                  SORT          sort           3
3                  MERGE        merge          3

```

BOURNE1.TXT

3			3
3	Program Development	LINK link	3
3	Tools	DEBUG adb/dbx	3
3		LIBRARIAN ar/ranlib	3
3		DEC MMS make	3
3		yacc	3
3		DEC CMS scs	3
3			3
3	Miscellaneous	DECalc bc/dc	3
3		DECspell spell	3
3			3

AAUU

As you can see from the above lists, both systems offer editors capable of screen or line editing capabilities. Both have interactive communications, electronic mail, networking, file transfer, remote command execution, and remote logins. These utilities and tools are standard to UNIX but require a license to run under VMS. The Digital Command Language (DCL) and the UNIX Shell (Bourne,C, or Korn) are command interpreters. That is, they are both programs that parse the command line and then pass control to other programs that are the kernel of the operating system.

7.1 Processes

When you login to either system the operating system will create a unique process. This process is given access to memory and CPU resources. The differences between the two operating systems with respect to multi-tasking needs explanation. Multi-tasking is concurrent processes initiated by a single user. When the user starts a terminal session the system initiates a single process called the PARENT process. It is possible to start multiple processes from the parent process. This is called spawning in VMS and forking in UNIX. The new process is called a sub-process in VMS and a child process in UNIX. This idea of "forking" a child process occurs frequently in UNIX.

When UNIX creates a child process or VMS creates a subprocess different things occur. First, let's look at VMS. When the subprocess is spawned the parent goes to "sleep" until the user logs off from the subprocess. When the logoff occurs control returns to the parent. The VMS ATTACH command gives control back to the parent process and the subprocess goes to sleep. The point is that only one process is active at a time. The exception is the VMS RUN/PROCESS=name which will run a user-defined process at the same time commands can be issued at the parent process.

In UNIX, you can run parent and children processes at the same time. A child process can fork another process and thus a process

BOURNE1.TXT

can be both a parent and child. Child processes are not restricted to user-defined images but can be any valid UNIX operation. UNIX processes that are running or stopped but not getting input from a terminal are said to be in background. When you begin a UNIX session the kernel gives you a copy of the shell. When you enter a command the Shell forks a child. That child then processes the command you entered.

Note: some commands are executed by the Shell itself and no child is forked.

This is a different concept from VMS, in which all commands are executed by the parent process. Once a subprocess is created the parent remains dormant until the subprocess completes.

All the above parent and child processes use the standard default for input and output devices, the terminal. Input and output streams in UNIX are called standard input (stdin) and standard output (stdout). Standard error (stderr) also uses the terminal as it's default output. In order to redirect these streams from a terminal in VMS it is requires the assignment of the logical names SYS\$OUTPUT, SYS\$INPUT, and SYS\$error to a file or device. UNIX has a much nicer means of redirecting the input or output.

7.2 Pipes

A vertical bar (|) is used to redirect the output of a command to the input of another command. This is the power of UNIX. For example, we want to get a list of all currently active users, sorted in alphabetical order, and sent to the printer, how could that be done in VMS? Here's one solution:

VMS Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
^$SHOW USERS/OUTPUT=A.TEMP 3
^$SORT/KEY=POSITION:40,SIZE:6)- 3
^ A.TEMP SYS$PRINT 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

Notice the need for an intermediate file called A.TEMP.

Now how would this same requirement be met using UNIX. There is a command that will list the users that are currently logged on to the system. The command is who. Pipes allow the output of one command to be the input into another command. The output of who can be put into another UNIX command sort by a pipe. In a similar manner, the output of sort can be redirected to another command

BOURNE1.TXT

called lp. Thus the same problem can be solved using UNIX Shell in this way:

UNIX Bourne Shell Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3$who | sort | lp -dmtlzlz 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

Notice that there is not a one-to-one command conversion that is taking place here. The idea is to convert the process more than individual commands from VMS DCL to UNIX Shell.

7.3 Input, Output, and Error Redirection

Just as the VMS logicals SYS\$INPUT, SYS\$OUTPUT, SYS\$COMMAND, and SYS\$ERROR point at the terminal by default, so do the UNIX equivalents stdin, stdout, and stderr. The equivalent of the SYS\$COMMAND in UNIX is the "Here is" document. UNIX uses a much more simplified method of redirecting input and output to or from a file. UNIX does not require the effect of an ASSIGN statement ahead of the redirection. UNIX uses a metacharacter that is included as part of the command line. Here is an example of both VMS and UNIX.

VMS Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3$ASSIGN/USER A.LIS SYS$OUTPUT 3
3$ASSIGN/USER INPUT.DAT FOR005 3
3$RUN MYPROG 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

The equivalent function can be written in UNIX Shell like this:

UNIX Bourne Shell Sample:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3$myprog < input.dat > a.lis 3
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU
```

The point here is to see that the metacharacters < and > act as the input and output redirection symbols. Please don't get the idea that UNIX is much simpler than VMS DCL. That is not the case. They each have strong points and weak points, they are not the same. This is comparing apples and oranges.

Here is a partial list of the metacharacters used by the UNIX Shells and their meanings. These can be useful when you try to

BOURNE1.TXT

redirect input and output.

```

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
^Character      Meaning
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA^
^>             Redirect standard output (stdout)
^
^>>           Redirect and append standard output (stdout)
^
^>&            Redirect standard output (stdout) and standard error
^              (stderr)
^
^>>&          Redirect and append standard output (stdout) and
^              standard error (stderr)
^
^<            Redirect standard input (stdin)
^
^|            Redirect standard output (stdout) to another
^              command
^
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAU

```

These are the most commonly used redirection metacharacters.

Notes:

UNIX redirection only affects the command line on which the redirection character occurs.

Error messages are not redirected and will appear on the terminal.

If a file already exists, VMS will create a new version of the file with a higher version number. By default, UNIX will overwrite the existing file.

7.4 Command Structure and File Naming Conventions

VMS is not case-sensitive in its interpretation of commands. It doesn't distinguish between upper and lower case characters. This is not true in UNIX, however. Commands must be entered in lower case characters only. The Shell will not understand characters that are in uppercase.

Filenames are also case sensitive in UNIX. The file named MYFILE.DAT and the file myfile.dat refer to different files. One advantage of this is that you can have a much larger variety of filenames with fewer characters. Especially good if you don't like to type.

BOURNE1.TXT

This also has advantage over the filename conventions used by VMS. Directories and subdirectories are pointer files in both operating systems. When a subdirectory is created in VMS it is given the extension name .DIR automatically. UNIX files on the other hand do not distinguish between ordinary files and directories. Many VMS users have adopted a practice of naming new subdirectories in UNIX with all capital letters or the first letter being capitalized. This is not, however, standard UNIX practice.

VMS Sample Session:

```
.....
. $CREATE/DIRECTORY [.TEST] .
. $DIRECTORY .
.....
```

UNIX Shell Sample Session:

```
.....
. $mkdir Test .
. $ls Test .
.....
```

It is possible in UNIX to maintain the same filename conventions that you used in VMS. The period (.) is a legal character in a UNIX filename. Some VMS users like to continue the practice of naming files using the same . extensions from VMS. Problems occur when default extensions are different between the two systems. For example, object files use the extension .OBJ in VMS but .o in UNIX. Another example is FORTRAN source code in UNIX the extension is .f and VMS uses .FOR. Note that .o and .f are UNIX conventions to facilitate file recognition and that UNIX commands do not assume file extensions as VMS does.

Here is a list of commonly used extensions for both operating systems.

VMS	UNIX	Definition
.OLB	.a	Library
.BAS	.bas	BASIC Source Code
.C	.c	C Source Code
.FOR	.f	FORTRAN Source Code

BOURNE1.TXT

3	.h	C header files	3
3	.l	lex program	3
3			3
3	.OBJ	.o Object Code	3
3			3
3	.PAS	.p PASCAL Source Code	3
3	.s	Symbolic Assembly Code	3
3	.y	yacc program	3
3			3
3	.EXE	a.out Executable Image	3
3			3
3	.ADA	ADA Source Code	3
3	.B32	BLISS-32 Source Code	3
3	.CLD	Command description file	3
3	.COB	Cobol Source Code	3
3	.COM	Commands for the language interpreter	3
3	.DAT	Data file	3
3	.DIS	Distribution list file for MAIL	3
3	.DIR	Directory file	3
3	.EDT	Startup command file for EDT editor	3
3	.DOC	Documentation	3
3	.HLP	Input source files for HELP Library	3
3	.JOU	Journal file created by EDT	3
3	.LIS	Listing of text	3
3	.LOG	Batch job output file	3
3	.MAI	MAIL message file	3
3	.MAR	VAX Macro source code	3
3	.SYS	System Image	3
3	.TMP	Temporary file	3

ÀAAÀ

7.5 File Management Commands

This is a table of the more commonly used file management commands. Some of these commands have been covered elsewhere in this manual. The on-line manual command (man) can be used to get detailed information about any UNIX command.

UNIX Command	VMS equivalent	Purpose
ar	LIBRARY	Archive files
awk	TPU	Pattern matching utility
cat	TYPE/APPEND	Catenates and prints to terminal
cd	SET DEFAULT	Change working directory

BOURNE1.TXT

chgrp	SET FILE	Change group ownership
chmod	SET PROTECTION	Changes protection
cmp	DIFFERENCE	Compares two files and reports first difference found
cp	COPY	Create a new copy
find	DIRECTORY	Locates within a directory structure
ftp	COPY	Transfer to/from remote node
grep	SEARCH	Finds a string
ln	ASSIGN	Create a symbolic link
ls	DIRECTORY	List contents of a directory
merge	MERGE	Merge files
mkdir	CREATE/DIR	Make a directory
mv	RENAME	Moves or renames files
od	DUMP	Octal, decimal, hex, ASCII dump
pr	PRINT/HEAD	Prints files
pwd	SHOW DEFAULT	Working directory name
rm	DELETE	Removes or deletes files
rmdir	DELETE	Removes a directory file
sort	SORT	Sorts by a key
tail	EDIT/READ	Outputs last part of file
tar	BACKUP	Tape archive
touch	CREATE	Updates file characteristics or creates null file
tr	EDIT	Translates characters

7.6 Metacharacters

Characters that have special meanings to the Shell are known as metacharacters. Users should avoid using these characters in filenames as results might be unpredictable. We have already seen several metacharacters, for example, vertical bar (|), or the greater than (>) or less than (<). The function of metacharacters can be different depending on whether the Shell or a UNIX tool interprets the character. The following is a list of UNIX special characters and their VMS equivalent.

UNIX Char	Function	VMS equivalent
&	Perform command in Background	
=	Assignment operator	=
;	Command separator	
\	Continuation of command line	-
\m	Literal translation of metacharacter m	"m
'	Turn off special meaning	"
`	Process immediately	@ & run
"	Group characters into a single argument	"
#	Comment follows	!
*	Wildcard filename substitution	*
?	Wildcard filename substitution single character	%
\$	Argument substitution follows	'
\$#	Argument count	
\$\$	Process id	F\$GETJPI("PID")
\$?	Exit status	\$STATUS
\$<	Read one line from standard input	INQUIRE, READ
.	Current directory	[]
[]	Selective filename substitution	

Note: Metacharacters unique to the C-Shell have not been included in this list to reduce confusion. Check C-Shell documentation for a complete list.

7.7 Wildcards: Are They Really Wild?

UNIX wildcards extend the features found with wildcards in VMS. The following table shows how UNIX expands wildcard definitions:

UNIX example	Meaning
*	# All files in the current directory and one

BOURNE1.TXT

```

3          level below          3
3
3 .          # Files in the current directory  3
3
3
3 *.*       # All files that contain a period in the  3
3          filename          3
3
3 *.com     # All files in the current directory that  3
3          end in .com      3
3
3 ?.com    # All files in the current directory that  3
3          end in .com and have one character  3
3          preceding the period  3
3
3 name[xyz] # All files in the current directory, namex,  3
3          namey, or namez  3
3
3 name[a-z] # All files in the current directory namea  3
3          through namez   3
3
3 name[a-z4] # All files in the current directory, namea  3
3          through namez and name4  3
3

```

AAUU

There are no absolute rules concerning the use of wildcards. The output produced by the wildcard expansion process is command dependent. For instance, the ls * command will list files in the current directory and the files in the directory in the next lower level as well. The wc * (word count) command will produce output for the files in the current directory only. Thus as you can see commands vary in how wildcards are expanded.

Users and programmers can use wildcards in a similar way to the method of using wildcards on the VAX. UNIX will interpret *.com to mean any file in the current directory that ends in .com even though the extension has no meaning in UNIX.

7.8 Summary

The VMS and UNIX operating systems are similar in some respects. The VMS user must recognize that there are some fundamental differences.

UNIX allows multiple processes and the user must learn to manage these processes. VMS usually manages a single process which processes commands in sequence.

BOURNE1.TXT

Continue on the next page

```
$ Today = F$cvtime("today",,"weekday")
$ if today .eqs. "Monday" then goto monday
$ if today .eqs. "Tuesday" then goto tuesday
$ if today .eqs. "Wednesday" then goto wednesday
$ if today .eqs. "Thursday" then goto thursday
$ if today .eqs. "Friday" then goto friday
$ go to weekend
$ Monday:
$   Write sys$output " "
$   Write sys$output "Today is ''today' and there are 5 days
until this weekend"
$   Write sys$output " "
$   exit
$ Tuesday:
$   Write sys$output " "
$   Write sys$output "Today is ''today' and there are 4 days
until this weekend"
$   Write sys$output " "
$   exit
$ Wednesday:
$   Write sys$output " "
$   Write sys$output "Today is ''today' and there are 3 days
until this weekend"
$   Write sys$output " "
$   exit
$ Thursday:
$   Write sys$output " "
$   Write sys$output "Today is ''today' and there are 2 days
until this weekend"
$   Write sys$output " "
$   exit
$ Friday:
$   Write sys$output " "
$   Write sys$output "Today is ''today' and there is 1 day
until this weekend"
$   Write sys$output " "
$   exit
$ Weekend:
$   Write sys$output " "
```

BOURNE1.TXT

```
$ Write sys$output "Today is ''today' and why are you working  
on a weekend"  
$ Write sys$output " "  
$ exit
```

Continue on the next page

2. Not all functions, especially calls to library functions, that exist in VMS have an equivalent call in UNIX Shell. An example of this is F\$ELEMENT in VMS. Write a BourneShell script that will do the same job as F\$ELEMENT and test it.

If time remains and you want a further challenge:

3. Write a user interface to add and delete records to the phone.lis database. Query the user in a user friendly manner and check to see if the name is already in the database prior to adding it.

That's all for this workshop. If you didn't finish because of time, that's OK, as long as you understand the process needed to do conversions.

NOTES


```
3 mget change_pass.dat;1?
```

3

```
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU
```

The default is 'yes', pressing (Ret) will cause the file to be sent to the local directory. If you don't want this file transferred, enter n(Ret); you will then be prompted for the next file, if one exists.

8.3 Auto Login Feature

It is possible to have the login procedure occur automatically. To do this requires a file in your home directory called .netrc. The .netrc file contains login and initialization information to be used by the auto-login process. The following variables are used and can be separated by spaces, tabs, or new lines.

machine name

This is the name of the remote computer. The auto-login process will search the .netrc file for a machine variable that matches the name of the remote computer on the ftp command or as an open command argument. Once a match is found, the next variables are also processed until the end of file or another machine variable is encountered.

login name

This is the username on the remote system. If this variable is present, the auto-login process will login to the remote computer with the given username.

password string

This is the password to be used when logging in to the remote system.

NOTE: If this variable is present in the .netrc file, ftp will abort the auto-login process if the .netrc file is readable by anyone but the user.

account string

This supplies an additional account password. If present, the

BOURNE1.TXT

auto-login process will supply the string as an additional password if required by the remote server.

macdef name

This defines a macro. This variable will function like the ftp macdef command. A macro is defined with the specified name, its contents begin with the next .netrc line and continue until a null line (2 new line characters). If a macro named init is defined, it will be executed as the last step of the auto-login process.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $cat .netrc 3
3 machine erc830 3
3 login teacher 3
3 password secret1 3
3 machine erc780 3
3 login rharding 3
3 password secret2 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

To invoke the auto-login feature, type the ftp command and enter the name of the remote computer as an argument.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $ftp erc830 3
3 Connected to erc830. 3
3 220 erc830 Wollongong FTP Server (Ver 5.0) at Tue Oct 23 3
3 331 Password required for rharding. 3
3 230 User logged in, default directory D_1131:[RHARDING] 3
3 ftp> 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

If the .netrc file is readable by anyone other than the user, the following error message will appear; and the connection will not be made to the remote computer.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÁ;
3 $ls -l .netrc 3
3 $ftp erc830 3
3 Connected to erc830. 3

```


BOURNE1.TXT

cdup

delete (tough question)

mdelete (ditto)

mkdir

rmdir

Continue on the next page

COMPUTER EXERCISES (30 minutes)

5. Transfer all the files from on the VAX (erc830) to the domax1. Use only one command and use wildcards. The username and password for the VAX will be given to you by the instructor.

6. Transfer the files from the VAX and this time translate the names of the files as they are transferred.

7. Create an auto-login file for the erc830 and then do an auto-login to the VAX.

8. Logout.

9. OPTIONAL CHAPTER - KORNSHELL PROGRAMMING

The KornShell is a command-programming language that executes

BOURNE1.TXT

from arguments, arguments from each other and commands from each other.

- EDITOR Command line edit mode.
- FCEDIT Editor entered when using fc
- TERM Defines terminal capabilities
- PS1 Primary shell prompt
- PS2 Secondary shell prompt
- PS3 Select command prompt
- HOME Home directory
- ENV File(s) to execute when entering this shell
- LOGNAME Login name of the user

The command line argument variables are also available: \$\$, \$?, \$*, \$#, and the positionals (\$0, \$1, \$2...etc)

9.2 User Defined Variables

These variables are similar to the BourneShell. The general form is VARIABLE=value.

No spaces are allowed around the =. You can enclose them in double quotes "=" or single quotes '=' for clarity. No spaces are allowed in "value". These can also be enclosed in double or single quotes. "value" can be a string or an expression. The value of a variable can be accessed by preceding the name of the variable with a dollar sign (\$).

Examples:

```
.....  
. $MyString=''"This is a string"'.  
. $MyStatic=47.  
. $readonly Mystatic.  
.....
```

The readonly command makes MyStatic read only (can't change the contents).

Example:

BOURNE1.TXT

```
.....  
. $typeset -i BIGINT=1492 .  
.....
```

This will make the variable integer for faster arithmetics:

```
.....  
. $typeset -i8 OCTINT=9 .  
.....
```

The output of OCTINT will be an octal integer; the assignment is decimal.

Sample Session:

```
ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $echo $OCTINT 3
3 8#11 3
3 $ 3
```

```
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ
```

9.3 Values of Variables Between Child and Parent Processes

Values in one shell are local only to that shell. If a child process or a subshell needs to have access to a value established in its parent, the value must be exported from the parent.

```
$typeset -i8 -x OCTINT=19
```

The -x option exports the variable OCTINT; subshells can read it, but can't change the value in the parent.

```
$MyString='Hi there'
```

At this point, the variable MyString is local to the current process. It is not available to a child process.

```
$export MyString
```

Now the variable MyString is available to subshells.

To allow a subshell to change the content of an exported variable and have that change be know to the parent, execute the child with

". program_name"

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $cat my.vars 3
3 echo Variable coming into script: $PARENT 3
3 PARENT='child value' 3
3 echo Variable coming out of the script: $PARENT 3
3 $PARENT='parent value' 3
3 $echo $PARENT 3
3 parent value 3
3 $my.vars 3
3 Variable coming into script: 3
3 Variable coming out of the script: child value 3
3 $echo $PARENT 3
3 parent value 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

Sample session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $PARENT='parent value' 3
3 $echo $PARENT 3
3 parent value 3
3 $. my.vars 3
3 Variable coming into the script: parent value 3
3 Variable coming out of the script: child value 3
3 $echo $PARENT 3
3 child value 3
3 $ 3
ÀAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAÙ

```

9.4 ksh: Aliases

The first word of each command can be replaced by the text of an alias if an alias for this word has been defined. The first character of an alias name can be any printable character, but the remaining characters must be the same as any valid identifier. Aliases can be created, listed, and exported with the alias command. They can be removed with the unalias command.

Aliasing is performed when scripts are read but not while they are executed. Therefore, for an alias to take effect the alias command has to be executed before the command which references the alias is read.

BOURNE1.TXT

.....
Now when you type in the command list, the alias will substitute the command ls -la for list; and the long listing will be displayed.

Sample Session:

```
UAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA;
3 $list 3
3 total 54 0 3
3 drwx----- 4 teacher class 2590 May 1 09:39 . 3
3 drwxr-xr-x 63 teacher class 1536 Sep 9 13:11 .. 3
3 -rw-r--r-- 1 teacher class 64 Jul 4 10:33 .assistrc 3
. .
. .
```

9.5 ksh: Command Line Editing

There are two forms of command-line editing in the KornShell. Both use the command history in the file indicated by the KornShell variable HISTFILE (default is HISTFILE=\$HOME/.history).

Editing commands in the history file is accomplished with fc (fix command). To get a list of commands in the .history file, you enter the fc -l command at the dollar (\$).

By default, the alias history may also be used.

Editing a command in the .history file with the fc command is controlled by the KornShell variable FCEDIT. FCEDIT determines the editor that the fc command will use.

Example:

```
.....
. $FCEDIT=/usr/bin/vi .
. $fc .
.....
```

The KornShell variable causes the fc command to use the vi editor. The fc command, by itself, will take you into the vi editor with the most recent command. In this example, upon exiting the vi editor, the edited command will be executed.

Example:

```
.....
. $ct .profile .
```

BOURNE1.TXT

```
. .profile: No such file or directory .
. $fc -e - ct=cat c .
.....
```

The first line is a deliberate mistake; notice the error message. The fc command executes the most recent command that starts with a "c" and changes the first occurrence of "ct" to "cat"; it doesn't enter the editor.

Example:

```
.....
. $ls / .
. $fc -e - ls=cd .
.....
```

The first command will list the contents of the root directory. The fc command changes that command from "ls" to "cd"; the "-" indicates that the line is to be edited instead of taken into the editor before execution.

9.6 ksh: Interactive Command Line Editing

In this method of command-line editing, the EDITOR KornShell variable controls the editing.

Example:

```
.....
. $EDITOR=/usr/bin/vi .
.....
```

This command will put the KornShell in the vi editing mode.

To enter the edit history press Esc.

NOTE: This example is for the vi edit mode only; emacs or gmacs edit modes use different key strokes.

To move though the .history file use following keys:

- <k> Select the previous command
- <j> Select the next command
- <h> Next letter to the left
- <l> Next letter to the right

BOURNE1.TXT

When the command line that you desire to change is displayed on the screen, you can use the following commands to make changes:

<i>	insert chars Esc	Insert characters before the cursor
<A>	append chars Esc	Append characters at the end of the line
<r>	replacement char Esc	Change single character
<cw>	replacement word Esc	Change single word
<x>		Delete single character
NOTE:	A number can precede the command as a count, for example, "3x" deletes 3 characters.	
<dw>		Delete single word
NOTE:	A number can precede the command as a count, for example, "2dw" deletes 2 words.	
(Ret)		Execute the altered command

When the (Ret) key is pressed, the edited command line will be executed. History is not changed, but the new command is entered into the .history file at the end.

These are not the only commands available with the interactive command line editing. You will find that the arrow keys will not work while editing the command line. Most of the editor features will be available for you to use, depending upon which editor was selected by the EDITOR shell variable.

9.7 ksh: Functions

Functions are similar to aliases, they run in the current KornShell process and define a set of actions. Positional parameters can be referenced; other previously defined functions can be referenced; nested function definitions are allowed with full visibility to all definitions.

The function keyword is used to define KornShell functions. The functions are read in and stored internally. Any alias names are

BOURNE1.TXT

```

3      ;;
3 pebbles)
3     echo Pebbles was the selection
3     ;;
3 barney)
3     echo Barney was the selection
3     ;;
3 betty)
3     echo Betty was the selection
3     ;;
3 esac
3 done
3 $chmod 755 select.ksh
3 $select.ksh
3 1) fred
3 2) wilma
3 3) pebbles
3 4) barney
3 5) betty
3 #? 3
3 Pebbles was the selection
3 #? 5
3 Betty was the selection
3 #? 6
3 #? 4
3 Barney was the selection
3 # Ctrl-C
3 $
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAUU

```

9.9 ksh: Tracing and Conditional Execution

A KornShell script that is not executable can be run implicitly with the ksh command. Tracing can be accomplished using the -v or the -x option.

Sample Session:

```

ÚAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA¿
3 $ls -l select.ksh
3 -rw-r--r-- 1 teacher class 390 Oct 16 09:21 select.ksh
3 $ksh -x select.ksh
3 + stty erase
3 1) fred
3 2) wilma
3 3) pebbles
3 4) barney
3 5) betty

```


BOURNE1.TXT

SHELL

PWD

IFS

EDITOR

FCEDIT

TERM

PS1

PS2

PS3

HOME

ENV

LOGNAME

Continue on the next page

4. What is an alias?

BOURNE1.TXT

5. Define a function k that will:

Display the present working directory, display a message that a listing will follow, sleep for three seconds, and then list the contents.

6. Set up an alias to do the `ls -C` function. Use a name of your own choice.

7. Write a KornShell script using the `select` command to display the following choices:

Apples
Bananas
Pears
Jack Daniels

After a choice has been made print the following:

"Thanks, your choice was" (display the choice)

8. Logout

Continue on the next page
Complete the Summary Workshop

and

BOURNE1.TXT

these four symbols, ; and & have equal precedence, which is lower than that of && and ||. The symbols && and || also have equal precedence. A semicolon (;) causes sequential execution of the preceding pipeline; an ampersand (&) causes asynchronous execution of the preceding pipeline (i.e., the shell does not wait for that pipeline to finish). The symbol && (||) causes the list following it to be executed only if the preceding pipeline returns a zero (non-zero) exit status. An arbitrary number of new-lines may appear in a list, instead of semicolons, to delimit commands.

A command is either a simple-command or one of the following. Unless otherwise stated, the value returned by a command is that of the last simple-command executed in the command.

for name [in word ...] do list done

Each time a for command is executed, name is set to the next word taken from the in word list. If in word ... is omitted, then the for command executes the do list once for each positional parameter that is set (see Parameter Substitution below). Execution ends when there are no more words in the list.

case word in [pattern [| pattern] ...) list ;;] ... esac

A case command executes the list associated with the first pattern that matches word. The form of the patterns is the same as that used for file-name generation (see File Name Generation) except that a slash, a leading dot, or a dot immediately following a slash need not be matched explicitly.

if list then list [elif list then list] ... [else list] fi

The list following if is executed and, if it returns a zero exit status, the list following the first then is executed. Otherwise, the list following elif is executed and, if its value is zero, the list following the next then is executed. Failing that, the else list is executed. If no else list or then list is executed then the if command returns a zero exit status.

while list do list done

A while command repeatedly executes the while list and if the exit status of the last command in the list is zero, executes the do list; otherwise the loop terminates. If no commands in the do list are executed, then the while command returns a zero exit status; until may be used in place of while to negate the loop termination test.

(list)

Execute list in a sub-shell.

BOURNE1.TXT

```
{ list; }
    list is executed in the current (that is, parent)
    shell.
name () { list; }
    Define a function which is referenced by name. The
    body of the function is the list of commands between {
    and }. Execution of functions is described below (see
    Execution).
```

The following words are only recognized as the first word of a command and when not quoted:

```
if then else elif fi case esac for while until
do done {}
```

Comments

A word beginning with # causes that word and all the following characters up to a new-line to be ignored.

Command Substitution

The shell reads commands from the string between two grave accents (`) and the standard output from these commands may be used as all or part of a word. Trailing new-lines from the standard output are removed.

No interpretation is done on the string before the string is read, except to remove backslashes (\) used to escape other characters. Backslashes may be used to escape a grave accent (`) or another backslash (\) and are removed before the command string is read. Escaping grave accents allows nested command substitution. If the command substitution lies within a pair of double quotes (" ...` ...` ... "), a backslash used to escape a double quote (\") will be removed; otherwise, it will be left intact.

If a backslash is used to escape a new-line character (\new-line), both the backslash and the new-line are removed (see the later section on Quoting). In addition, backslashes used to escape dollar signs (\\$) are removed. Since no interpretation is done on the command string before it is read, inserting a backslash to escape a dollar sign has no effect. Backslashes that precede characters other than \, `, ", new-line, and \$ are left intact when the command string is read.

Parameter Substitution

The character \$ is used to introduce substitutable parameters. There are two types of parameters, positional

BOURNE1.TXT

and keyword. If parameter is a digit, it is a positional parameter. Positional parameters may be assigned values by set. Keyword parameters (also known as variables) may be assigned values by writing:

```
name=value [ name=value ] ...
```

Pattern-matching is not performed on value. There cannot be a function and a variable with the same name.

`${parameter}`

The value, if any, of the parameter is substituted.

The braces are required only when parameter is followed by a letter, digit, or underscore that is not to be interpreted as part of its name. If parameter is * or @, all the positional parameters, starting with \$1, are substituted (separated by spaces). Parameter \$0 is set from argument zero when the shell is invoked.

`${parameter:-word}`

If parameter is set and is non-null, substitute its value; otherwise substitute word.

`${parameter:=word}`

If parameter is not set or is null set it to word; the value of the parameter is substituted. Positional parameters may not be assigned to in this way.

`${parameter:?word}`

If parameter is set and is non-null, substitute its value; otherwise, print word and exit from the shell. If word is omitted, the message "parameter null or not set" is printed.

`${parameter:+word}`

If parameter is set and is non-null, substitute word; otherwise substitute nothing.

In the above, word is not evaluated unless it is to be used as the substituted string, so that, in the following example, pwd is executed only if d is not set or is null:

```
echo ${d:-`pwd`}
```

If the colon (:) is omitted from the above expressions, the shell only checks whether parameter is set or not.

The following parameters are automatically set by the shell:

- # The number of positional parameters in decimal.
- Flags supplied to the shell on invocation or by the set command.
- ? The decimal value returned by the last

BOURNE1.TXT

- synchronously executed command.
- \$ The process number of this shell.
- ! The process number of the last background command invoked.

The following parameters are used by the shell:

HOME The default argument (home directory) for the cd command.

PATH The search path for commands (see Execution below). The user may not change PATH if executing under rsh.

CDPATH

The search path for the cd command.

MAIL If this parameter is set to the name of a mail file and the MAILPATH parameter is not set, the shell informs the user of the arrival of mail in the specified file.

MAILCHECK

This parameter specifies how often (in seconds) the shell will check for the arrival of mail in the files specified by the MAILPATH or MAIL parameters. The default value is 600 seconds (10 minutes). If set to 0, the shell will check before each prompt.

MAILPATH

A colon (:) separated list of file names. If this parameter is set, the shell informs the user of the arrival of mail in any of the specified files. Each file name can be followed by % and a message that will be printed when the modification time changes. The default message is you have mail.

PS1 Primary prompt string, by default "\$ ".

PS2 Secondary prompt string, by default "> ".

IFS Internal field separators, normally space, tab, and new-line.

SHACCT

If this parameter is set to the name of a file writable by the user, the shell will write an accounting record in the file for each shell procedure executed. Accounting routines such as acctcom(1) and acctcms(1M) can be used to analyze the data collected.

SHELL When the shell is invoked, it scans the environment (see Environment below) for this name. If it is found and 'rsh' is the file name part of its value, the shell becomes a restricted shell.

BOURNE1.TXT

The shell gives default values to PATH, PS1, PS2, MAILCHECK and IFS. HOME and MAIL are set by login(1).

Blank Interpretation

After parameter and command substitution, the results of substitution are scanned for internal field separator characters (those found in IFS) and split into distinct arguments where such characters are found. Explicit null arguments (" or ') are retained. Implicit null arguments (those resulting from parameters that have no values) are removed.

Input/Output

A command's input and output may be redirected using a special notation interpreted by the shell. The following may appear anywhere in a simple-command or may precede or follow a command and are not passed on to the invoked command; substitution occurs before word or digit is used:

<word	Use file word as standard input (file descriptor 0).
>word	Use file word as standard output (file descriptor 1). If the file does not exist it is created; otherwise, it is truncated to zero length.
>>word	Use file word as standard output. If the file exists output is appended to it (by first seeking to the end-of-file); otherwise, the file is created.
<<[-]word	After parameter and command substitution are done on word, the shell input is read up to the first line that literally matches the resulting word, or to an end-of-file. If, however, - is appended to <<: <ol style="list-style-type: none">1) leading tabs are stripped from word before the shell input is read (but after parameter and command substitution is done on word),2) leading tabs are stripped from the shell input as it is read and before each line is compared with word, and3) shell input is read up to the first line that literally matches the resulting word, or to an end-of-file. If any character of word is quoted (see Quoting, later), no additional processing is done to the shell input. If no characters of

BOURNE1.TXT

word are quoted:

- 1) parameter and command substitution occurs,
- 2) (escaped) \newline is ignored, and
- 3) \ must be used to quote the characters \, \$, and `.

The resulting document becomes the standard input.

<&digit Use the file associated with file descriptor digit as standard input. Similarly for the standard output using >&digit.

<&- The standard input is closed. Similarly for the standard output using >&--.

If any of the above is preceded by a digit, the file descriptor which will be associated with the file is that specified by the digit (instead of the default 0 or 1). For example:

```
... 2>&1
```

associates file descriptor 2 with the file currently associated with file descriptor 1.

The order in which redirections are specified is significant. The shell evaluates redirections left-to-right. For example:

```
... 1>xxx 2>&1
```

first associates file descriptor 1 with file xxx. It associates file descriptor 2 with the file associated with file descriptor 1 (i.e. xxx). It directs both standard output and standard error output (stdout, stderr) to xxx. If the order of redirections were reversed, file descriptor 2 would be associated with the terminal (assuming file descriptor 1 had been) and file descriptor 1 would be associated with file xxx.

Using the terminology introduced on the first page, under Commands, if a command is composed of several simple commands, redirection will be evaluated for the entire command before it is evaluated for each simple command. That is, the shell evaluates redirection for the entire list, then each pipeline within the list, then each command within each pipeline, then each list within each command.

If a command is followed by & the default standard input for the command is the empty file /dev/null. Otherwise, the

BOURNE1.TXT

environment for the execution of a command contains the file descriptors of the invoking shell as modified by input/output specifications.

Redirection of output is not allowed in the restricted shell.

File Name Generation

Before a command is executed, each command word is scanned for the characters *, ?, and [. If one of these characters appears, the word is regarded as a pattern. The word is replaced with alphabetically sorted file names that match the pattern. If no file name is found that matches the pattern, the word is left unchanged. The character . at the start of a file name or immediately following a /, as well as the character / itself, must be matched explicitly.

- * Matches any string, including the null string.
- ? Matches any single character.
- [...] Matches any one of the enclosed characters. A pair of characters separated by - matches any character lexically between the pair, inclusive. If the first character following the opening "[" is a "!" any character not enclosed is matched.

Quoting

The following characters have a special meaning to the shell and cause termination of a word unless quoted:

; & () | ^ < > new-line space tab

A character may be quoted (i.e., made to stand for itself) by preceding it with a backslash (\) or inserting it between a pair of quote marks ('' or ""). During processing, the shell may quote certain characters to prevent them from taking on a special meaning. Backslashes used to quote a single character are removed from the word before the command is executed. The pair \newline is removed from a word before command and parameter substitution.

All characters enclosed between a pair of single quote marks (''), except a single quote, are quoted by the shell. Backslash has no special meaning inside a pair of single quotes. A single quote may be quoted inside a pair of double quote marks (for example, "").

Inside a pair of double quote marks (""), parameter and

BOURNE1.TXT

command substitution occurs and the shell quotes the results to avoid blank interpretation and file name generation. If `$*` is within a pair of double quotes, the positional parameters are substituted and quoted, separated by quoted spaces ("`$1 $2 ...`"); however, if `$@` is within a pair of double quotes, the positional parameters are substituted and quoted, separated by unquoted spaces ("`$1" "$2" ...`). `\` quotes the characters `\`, ```, `"`, and `$`. The pair `\newline` is removed before parameter and command substitution. If a backslash precedes characters other than `\`, ```, `"`, `$`, and new-line, the backslash itself is quoted by the shell.

Prompting

When used interactively, the shell prompts with the value of `PS1` before reading a command. If at any time a new-line is typed and further input is needed to complete a command, the secondary prompt (i.e., the value of `PS2`) is issued.

Environment

The environment (see `environ(5)`) is a list of name-value pairs that is passed to an executed program in the same way as a normal argument list. The shell interacts with the environment in several ways. On invocation, the shell scans the environment and creates a parameter for each name found, giving it the corresponding value. If the user modifies the value of any of these parameters or creates new parameters, none of these affects the environment unless the `export` command is used to bind the shell's parameter to the environment (see also `set -a`). A parameter may be removed from the environment with the `unset` command. The environment seen by any executed command is thus composed of any unmodified name-value pairs originally inherited by the shell, minus any pairs removed by `unset`, plus any modifications or additions, all of which must be noted in `export` commands.

The environment for any simple-command may be augmented by prefixing it with one or more assignments to parameters. Thus:

```
    TERM=450 cmd
and
    (export TERM; TERM=450; cmd)
```

are equivalent (as far as the execution of `cmd` is concerned).

If the `-k` flag is set, all keyword arguments are placed in

BOURNE1.TXT

the environment, even if they occur after the command name.
The following first prints a=b c and c:

```
echo a=b c
set -k
echo a=b c
```

Signals

The INTERRUPT and QUIT signals for an invoked command are ignored if the command is followed by &; otherwise signals have the values inherited by the shell from its parent, with the exception of signal 11 (SIGSEGV) (but see also the trap command below). See nohup(1) for more signal handling.

Execution

Each time a command is executed, the above substitutions are carried out. If the command name matches one of the Special Commands listed below, it is executed in the shell process. If the command name does not match a Special Command, but matches the name of a defined function, the function is executed in the shell process (note how this differs from the execution of shell procedures). The positional parameters \$1, \$2, are set to the arguments of the function. If the command name matches neither a Special Command nor the name of a defined function, a new process is created and an attempt is made to execute the command via exec(2).

The shell parameter PATH defines the search path for the directory containing the command. Alternative directory names are separated by a colon (:). The default path is :/bin:/usr/bin (specifying the current directory, /bin, and /usr/bin, in that order). Note that the current directory is specified by a null path name, which can appear immediately after the equal sign or between the colon delimiters anywhere else in the path list. If the command name contains a / the search path is not used; such commands will not be executed by the restricted shell. Otherwise, each directory in the path is searched for an executable file. If the file has execute permission but is not an a.out file, it is assumed to be a file containing shell commands. A sub-shell is spawned to read it. A parenthesized command is also executed in a sub-shell.

The location in the search path where a command was found is remembered by the shell (to help avoid unnecessary execs later). If the command was found in a relative directory, its location must be re-determined whenever the current

BOURNE1.TXT

directory changes. The shell forgets all remembered locations whenever the PATH variable is changed or the hash -r command is executed (see below).

Special Commands

Input/output redirection is now permitted for these commands. File descriptor 1 is the default output location.

:

No effect; the command does nothing. A zero exit code is returned.

. file

Read and execute commands from file and return. The search path specified by PATH is used to find the directory containing file.

break [n]

Exit from the enclosing for or while loop, if any. If n is specified break n levels.

continue [n]

Resume the next iteration of the enclosing for or while loop. If n is specified resume at the nth enclosing loop.

cd [arg]

Change the current directory to arg. The shell parameter HOME is the default arg. The shell parameter CDPATH defines the search path for the directory containing arg. Alternative directory names are separated by a colon (:). The default path is <null> (specifying the current directory). Note that the current directory is specified by a null path name, which can appear immediately after the equal sign or between the colon delimiters anywhere else in the path list. If arg begins with a / the search path is not used. Otherwise, each directory in the path is searched for arg. The cd command may not be executed by rsh.

echo [arg ...]

Echo arguments. See echo(1) for usage and description.

eval [arg ...]

The arguments are read as input to the shell and the resulting command(s) executed.

exec [arg ...]

The command specified by the arguments is executed in place of this shell without creating a new process. Input/output arguments may appear and, if no other arguments are given, cause the shell input/output to be modified.

exit [n]

BOURNE1.TXT

Causes a shell to exit with the exit status specified by *n*. If *n* is omitted the exit status is that of the last command executed (an end-of-file will also cause the shell to exit.)

`export [name ...]`

The given names are marked for automatic export to the environment of subsequently-executed commands. If no arguments are given, a list of all names that are exported in this shell is printed. (Variable names exported from a parent shell are listed only if they have been exported again during the current shell's execution.) Function names may not be exported.

`getopts`

Use in shell script to support command syntax standards (see `intro(1)`); it parses positional parameters and checks for legal options. See `getopts(1)` for usage and description.

`hash [-r] [name ...]`

For each name, the location in the search path of the command specified by name is determined and remembered by the shell. The `-r` option causes the shell to forget all remembered locations. If no arguments are given, information about remembered commands is presented. `hits` is the number of times a command has been invoked by the shell process. `cost` is a measure of the work required to locate a command in the search path. If a command is found in a "relative" directory in the search path, after changing to that directory, the stored location of that command is recalculated. Commands for which this will be done are indicated by an asterisk (*) adjacent to the hits information. `cost` will be incremented when the recalculation is done.

`newgrp [arg ...]`

Equivalent to `exec newgrp arg` See `newgrp(1M)` for usage and description.

`pwd`

Print the current working directory. See `pwd(1)` for usage and description.

`read [name ...]`

One line is read from the standard input and, using the internal field separator, IFS (normally space or tab), to delimit word boundaries, the first word is assigned to the first name, the second word to the second name, etc., with leftover words assigned to the last name. Lines can be continued using `\new-line`. Characters other than new-line can be quoted by preceding them with a backslash. These backslashes are removed before words are assigned to names, and no interpretation is

BOURNE1.TXT

done on the character that follows the backslash. The return code is 0 unless an end-of-file is encountered.

`readonly [name ...]`

The given names are marked readonly and the values of these names may not be changed by subsequent assignment. If no arguments are given, a list of all readonly names is printed.

`return [n]`

Causes a function to exit with the return value specified by n. If n is omitted, the return status is that of the last command executed.

`set [--aefhkntuvx [arg ...]]`

-a

Mark variables which are modified or created for export.

-e Exit immediately if a command exits with a non-zero exit status.

-f Disable file name generation.

-h Locate and remember function commands as functions are defined (function commands are normally located when the function is executed).

-k All keyword arguments are placed in the environment for a command, not just those that precede the command name.

-n Read commands but do not execute them.

-t Exit after reading and executing one command.

-u Treat unset variables as an error when substituting.

-v Print shell input lines as they are read.

-x Print commands and their arguments as they are executed.

-- Do not change any of the flags; useful in setting \$1 to -.

Using + rather than - causes these flags to be turned off. These flags can also be used upon invocation of the shell. The current set of flags may be found in \$-. The remaining arguments are positional parameters and are assigned, in order, to \$1, \$2, If no arguments are given the values of all names are printed.

`shift [n]`

The positional parameters from \$n+1 ... are renamed \$1 If n is not given, it is assumed to be 1.

`test`

Evaluate conditional expressions. See test(1) for usage and description.

`times`

Print the accumulated user and system times for

BOURNE1.TXT

processes run from the shell.

trap [arg] [n] ...

The command arg is to be read and executed when the shell receives signal(s) n. (Note that arg is scanned once when the trap is set and once when the trap is taken.) Trap commands are executed in order of signal number. Any attempt to set a trap on a signal that was ignored on entry to the current shell is ineffective. An attempt to trap on signal 11 (memory fault) produces an error. If arg is absent all trap(s) n are reset to their original values. If arg is the null string this signal is ignored by the shell and by the commands it invokes. If n is 0 the command arg is executed on exit from the shell. The trap command with no arguments prints a list of commands associated with each signal number.

type [name ...]

For each name, indicate how it would be interpreted if used as a command name.

ulimit [n]

Impose a size limit of n blocks on files written by the shell and its child processes (files of any size may be read). If n is omitted, the current limit is printed. Each user may lower the ulimit, but only a super-user (see su(1M)) can raise a ulimit.

umask [nnn]

The user file-creation mask is set to nnn (see umask(1)). If nnn is omitted, the current value of the mask is printed.

unset [name ...]

For each name, remove the corresponding variable or function. The variables PATH, PS1, PS2, MAILCHECK and IFS cannot be unset.

wait [n]

Wait for a background process whose process ID is n and report its termination status. If n is omitted, all the shell's currently active background processes are waited for and the return code will be zero.

Invocation

If the shell is invoked through exec(2) and the first character of argument zero is -, commands are initially read from /etc/profile and from \$HOME/.profile, if such files exist. Thereafter, commands are read as described below, which is also the case when the shell is invoked as /bin/sh. The flags below are interpreted by the shell on invocation only. Note that unless the -c or -s flag is specified, the first argument is assumed to be the name of a file

BOURNE1.TXT

containing commands, and the remaining arguments are passed as positional parameters to that command file:

- c string If the -c flag is present commands are read from string.
- s If the -s flag is present or if no arguments remain commands are read from the standard input. Any remaining arguments specify the positional parameters. Shell output (except for Special Commands) is written to file descriptor 2.
- i If the -i flag is present or if the shell input and output are attached to a terminal, this shell is interactive. In this case TERMINATE is ignored (so that kill 0 does not kill an interactive shell) and INTERRUPT is caught and ignored (so that wait is interruptible). In all cases, QUIT is ignored by the shell.
- r If the -r flag is present the shell is a restricted shell.

The remaining flags and arguments are described under the set command above.

rsh Only

rsh is used to set up login names and execution environments whose capabilities are more controlled than those of the standard shell. The actions of rsh are identical to those of sh, except that the following are disallowed:

- changing directory (see cd(1)),
- setting the value of \$PATH,
- specifying path or command names containing /,
- redirecting output (> and >>).

The restrictions above are enforced after .profile is interpreted.

A restricted shell can be invoked in one of the following ways: (1) rsh is the file name part of the last entry in the /etc/passwd file (see passwd(4)); (2) the environment variable SHELL exists and rsh is the file name part of its value; (3) the shell is invoked and rsh is the file name part of argument 0; (4) the shell is invoked with the -r option.

When a command to be executed is found to be a shell procedure, rsh invokes sh to execute it. Thus, it is possible to provide to the end-user shell procedures that

BOURNE1.TXT

have access to the full power of the standard shell, while imposing a limited menu of commands; this scheme assumes that the end-user does not have write and execute permissions in the same directory.

The net effect of these rules is that the writer of the .profile has complete control over user actions, by performing guaranteed setup actions and leaving the user in an appropriate directory (probably not the login directory).

The system administrator often sets up a directory of commands (i.e., /usr/rbin) that can be safely invoked by rsh. Some systems also provide a restricted editor red.

EXIT STATUS

Errors detected by the shell, such as syntax errors, cause the shell to return a non-zero exit status. If the shell is being used non-interactively execution of the shell file is abandoned. Otherwise, the shell returns the exit status of the last command executed (see also the exit command above).

FILES

/etc/profile
\$HOME/profile
/tmp/sh*
/dev/null

SEE ALSO

acctcom(1), cd(1), echo(1), env(1), ksh(1), login(1),
pwd(1), test(1), umask(1).
acctcms(1M), newgrp(1M), su(1M) in the UMAX V
Administrator's Reference Manual.
dup(2), exec(2), fork(2), pipe(2), signal(2), ulimit(2),
wait(2), a.out(4), passwd(4), profile(4), environ(5) in the
UMAX V Programmer's Reference Manual.

CAVEATS

Words used for filenames in input/output redirection are not interpreted for filename generation (see File Name Generation, above). For example, cat file1 > a* will create a file named a*.

Because commands in pipelines are run as separate processes, variables set in a pipeline have no effect on the parent shell.

If the error message cannot fork, too many processes is displayed, try using the wait(1) command to clean up the

BOURNE1.TXT

spaces.

The following primitives are used to construct expr:

- r file true if file exists and is readable.
- w file true if file exists and is writable.
- x file true if file exists and is executable.
- f file true if file exists and is a regular file.
- d file true if file exists and is a directory.
- c file true if file exists and is a character special file.
- b file true if file exists and is a block special file.
- p file true if file exists and is a named pipe (fifo).
- u file true if file exists and its set-user-ID bit is set.
- g file true if file exists and its set-group-ID bit is set.
- k file true if file exists and its sticky bit is set.
- s file true if file exists and has a size greater than zero.

- t [fildes]
 true if the open file whose file descriptor number is fildes (1 by default) is associated with a terminal device.

- z s1 true if the length of string s1 is zero.
- n s1 true if the length of the string s1 is non-zero.

- s1 = s2 true if strings s1 and s2 are identical.
- s1 != s2 true if strings s1 and s2 are not identical.

- s1 true if s1 is not the null string.

- n1 -eq n2 true if the integers n1 and n2 are algebraically

BOURNE1.TXT

NAME

expr - evaluate arguments as an expression

SYNOPSIS

expr arguments

DESCRIPTION

The arguments are taken as an expression. After evaluation, the result is written on the standard output. Terms of the expression must be separated by blanks. Characters special to the shell must be escaped. Note that 0 is returned to indicate a zero value, rather than the null string. Strings containing blanks or other special characters should be quoted. Integer-valued arguments may be preceded by a unary minus sign. Internally, integers are treated as 32-bit, 2s complement numbers.

The operators and keywords are listed below. Characters that need to be escaped are preceded by \. The list is in order of increasing precedence, with equal precedence operators grouped within {} symbols.

expr \ | expr returns the first expr if it is neither null nor 0, otherwise returns the second expr.

expr \& expr returns the first expr if neither expr is null nor 0, otherwise returns 0.

expr { =, \>, \, \<, \, != } expr
returns the result of an integer comparison if both arguments are integers, otherwise returns the result of a lexical comparison.

expr { +, - } expr
addition or subtraction of integer-valued arguments.

expr { *, /, % } expr
multiplication, division, or remainder of the integer-valued arguments.

expr : expr The matching operator : compares the first argument with the second argument which must be a regular expression. Regular expression syntax is the same as that of ed(1), except matching operator returns the number of characters matched (0 on failure). Alternatively, the \(...\) pattern symbols

BOURNE1.TXT

can be used to return a portion of the first argument.

EXAMPLES

1. `a=`expr $a + 1``
adds 1 to the shell variable
2. `# For $a equal to either "/usr/abc/file" or just "file"`
`expr $a : '.*\/\(.*\)' \| $a`
3
returns the last segment of a path name (i.e., file).
Watch out for / alone as an argument: `expr` will take it as the division operator (see BUGS below).
3. `# A better representation of the previous example.`
`expr // $a : '.*\/\(.*\)'`
The addition of the // characters eliminates any ambiguity about the division operator and simplifies the whole expression.
4. `expr $VAR : '.*'`
returns the number of characters in \$VAR.

SEE ALSO

`ed(1)`, `sh(1)`.

DIAGNOSTICS

As a side effect of expression evaluation, `expr` returns the following exit values:

- 0 if the expression is neither null nor 0
- 1 if the expression is null or 0
- 2 for invalid expressions.

syntax error

for operator/operand errors

non-numeric argument

if arithmetic is attempted on such a string

BUGS

After argument processing by the shell, `expr` cannot tell the difference between an operator and an operand except by the value. If `$a` is an `=`, the command: `expr $a = '='` looks like: `expr = = =` as the arguments are passed to `expr` (and they will all be taken as the `=` operator). The following works: `expr X$a = X=`

APPENDIX D - ftp

BOURNE1.TXT

\$man ftp

NAME

ftp - Internet file transfer program

SYNOPSIS

ftp [-v] [-d] [-i] [-n] [-g] [host]

DESCRIPTION

ftp is the user interface to the DARPA File Transfer Protocol. The program transfers files to and from a remote network site.

The client host with which ftp is to communicate can be specified on the command line. In this case, ftp immediately attempts to establish a connection to an FTP server on that host; otherwise, ftp enters its command interpreter and waits for instruction, displaying the prompt ftp>.

ftp recognizes the following commands:

! [command [args]]

Invoke an interactive shell on the local machine. If there are arguments, the first is taken to be a command to execute directly, with the rest of the arguments as its arguments.

\$ macro-name [args]

Execute the macro-name that was defined with the macdef command. Arguments are passed to the macro unglobbed.

account [passwd]

Supply a supplemental password required by a remote system for access to resources once a login has been successfully completed. If no argument is included, the user will be prompted for an account password in a non-echoing input mode.

append local-file [remote-file]

Append a local file to a file on the remote machine. If remote-file is left unspecified, the local file name is used to name the remote file after being altered by any ntrans or nmap setting. File transfer uses the current settings for type, format, mode, and structure.

BOURNE1.TXT

- ascii Set the file transfer type to network ASCII. This is the default type.
- bell Sound a bell after each file transfer command is completed.
- binary Set the file transfer type to support binary image transfer.
- bye Terminate the FTP session with the remote server and exit ftp.
- case Toggle remote computer file name case mapping during mget commands. When case is on (default is off), remote computer file names with all letters in upper case are written in the local directory with the letters mapped to lower case.
- cd remote-directory
Change the working directory on the remote machine to remote-directory.
- cdup Change the remote machine working directory to the parent of the current remote machine working directory.
- close Terminate the FTP session with the remote server, and return to the command interpreter. Any defined macros are erased.
- cr Toggle carriage return stripping during ASCII type file retrieval. Records are denoted by a carriage return/linefeed sequence during ASCII type file transfer. When cr is on (the default), carriage returns are stripped from this sequence to conform with the UNIX single linefeed record delimiter. Records on non-UNIX remote systems may contain single linefeeds; when an ASCII type transfer is made, these linefeeds may be distinguished from a record delimiter only when cr is off.
- delete remote-file
Delete the file remote-file on the remote machine.
- debug [debug-value]
Toggle debugging mode. If an optional debug-value is specified, it is used to set the debugging level. When debugging is on, ftp prints each

BOURNE1.TXT

command sent to the remote machine, preceded by the string --> .

- `dir [remote-directory] [local-file]`
Print the contents of directory, remote-directory, and, optionally, place the output in local-file. If no directory is specified, the current working directory on the remote machine is used. If no local file is specified, or local-file is -, output comes to the terminal.
- `disconnect`
A synonym for close.
- `form format`
Set the file transfer form to format. The default format is file.
- `get remote-file [local-file]`
Retrieve the remote-file and store it on the local machine. If the local file name is not specified, it is given the same name it has on the remote machine, subject to alteration by the current case, ntrans, and nmap settings. The current settings for type, form, mode, and structure are used while transferring the file.
- `glob`
Toggle filename expansion for mdelete, mget and mput. If globbing is turned off with glob, the file name arguments are taken literally and not expanded. Globbing for mput is done as in csh(1). For mdelete and mget, each remote file name is expanded separately on the remote machine and the lists are not merged. Expansion of a directory name is likely to be different from expansion of the name of an ordinary file: the exact result depends on the foreign operating system and FTP server, and can be previewed by doing "mlls remote-files -". Note: mget and mput are not meant to transfer entire directory subtrees of files. That can be done by transferring a tar(1) archive of the subtree (in binary mode).
- `hash`
Toggle number-sign (#) printing for each data block transferred. The size of a data block is 1024 bytes.
- `help [command]`

BOURNE1.TXT

Print a description of command. With no argument, ftp prints a list of the known commands.

lcd [directory]

Change the working directory on the local machine. If no directory is specified, changes to the user's home directory.

ls [remote-directory] [local-file]

Print an abbreviated listing of the contents of a directory on the remote machine. If remote-directory is left unspecified, the current working directory is used. If no local file is specified, the output is sent to the terminal.

macdef macro-name

Define a macro. Subsequent lines are stored as the macro-name; a null line (consecutive newline characters in a file or carriage returns from the terminal) terminates macro input mode. There is a limit of 16 macros and 4096 total characters in all defined macros. Macros remain defined until a close command is executed. The macro processor interprets "\$" and "\" as special characters. A "\$" followed by a number (or numbers) is replaced by the corresponding argument on the macro invocation command line. A "\$" followed by an "i" signals that macro processor that the executing macro is to be looped. On the first pass "\$i" is replaced by the first argument on the macro invocation command line, on the second pass it is replaced by the second argument, and so on. A "\" followed by any character is replaced by that character. Use the "\" to prevent special treatment of the "\$".

mdelete [remote-files]

Delete the specified files on the remote machine.

mdir remote-files local-file

Like dir, except multiple remote files may be specified. If interactive prompting is on, ftp will prompt the user to verify that the last argument is indeed the target local file for receiving mdir output.

mget remote-files

Expand the remote-files on the remote machine and

BOURNE1.TXT

do a get for each file name thus produced. See glob for details on the filename expansion. Resulting file names will then be processed according to case, ntrans, and nmap settings. Files are transferred into the local working directory, which can be changed with "lcd directory"; new local directories can be created with "! mkdir directory".

mkdir directory-name

Make a directory on the remote machine.

mls remote-files local-file

Like ls, except multiple remote files may be specified. If interactive prompting is on, ftp will prompt the user to verify that the last argument is indeed the target local file for receiving mls output.

mode [mode-name]

Set the file transfer mode to mode-name. The default mode is stream.

mput local-files

Expand wild cards in the list of local files given as arguments and do a put for each file in the resulting list. See glob for details of filename expansion. Resulting file names will then be processed according to ntrans and nmap settings.

nmap [inpattern outpattern]

Set or unset the filename mapping mechanism. If no arguments are specified, the filename mapping mechanism is unset. If arguments are specified, remote filenames are mapped during mput commands and put commands issued without a specified remote target filename. If arguments are specified, local filenames are mapped during mget commands and get commands issued without a specified local target filename. This command is useful when connecting to a non-UNIX remote computer with different file naming conventions or practices. The mapping follows the pattern set by inpattern and outpattern. inpattern is a template for incoming filenames (which may have already been processed according to the ntrans and case settings). Variable templating is accomplished by including the sequences "\$1", "\$2", ..., "\$9" in

BOURNE1.TXT

inpattern. Use "\" to prevent this special treatment of the "\$" character. All other characters are treated literally, and are used to determine the nmap inpattern variable values. For example, given inpattern \$1.\$2 and the remote file name mydata.data, \$1 would have the value mydata, and \$2 would have the value data. The outpattern determines the resulting mapped filename. The sequences "\$1", "\$2", ..., "\$9" are replaced by any value resulting from the inpattern template. The sequence "\$0" is replaced by the original filename. Additionally, the sequence "[seq1,seq2]" is replaced by seq1 if seq1 is not a null string; otherwise it is replaced by seq2. For example, the command "nmap \$1.\$2.\$3 [\$1,\$2].[\$2,file]" would yield the output filename myfile.data for input filenames myfile.data and myfile.data.old, myfile.file for the input filename myfile, and myfile.myfile for the input filename .myfile. Spaces may be included in outpattern, as in the example:

```
nmap $1 | sed "s/ *$//" > $1
```

Use the "\" character to prevent special treatment of the "\$", "[", "]", and "," characters.

ntrans [inchars [outchars]]

Set or unset the filename character translation mechanism. If no arguments are specified, the filename character translation mechanism is unset. If arguments are specified, characters in remote filenames are translated during mput commands and put commands issued without a specified remote target filename. If arguments are specified, characters in local filenames are translated during mget commands and get commands issued without a specified local target filename. This command is useful when connecting to a non-UNIX remote computer with different file naming conventions or practices. Characters in a filename matching a character in inchars are replaced with the corresponding character in outchars. If the character's position in inchars is longer than the length of outchars, the character is deleted from the file name.

open host [port]

BOURNE1.TXT

Establish a connection to the specified host's FTP server. An optional port number can be supplied, in which case, ftp attempts to contact an FTP server at that port. If the auto-login option is on (default), ftp also attempts to automatically log the user in to the FTP server (see below).

prompt Toggle interactive prompting. Interactive prompting occurs during multiple file transfers to allow the user to selectively retrieve or store files. If prompting is turned off (default), any mget or mput transfers all files and mdelete will delete all files.

proxy ftp-command
Execute an ftp command on a secondary control connection. This command allows simultaneous connection to two remote FTP servers for transferring files between the two servers. The first proxy command should be an open, to establish the secondary control connection. Enter the command "proxy ?" to see other ftp commands executable on the secondary connection. The following commands behave differently when prefaced by proxy: open will not define new macros during the auto-login process, close will not erase existing macro definitions, get and mget transfer files from the host on the primary control connection to the host on the secondary control connection, and put, mput, and append transfer files from the host on the secondary control connection to the host on the primary control connection. Third party file transfers depend upon support of the FTP protocol PASV command by the server on the secondary control connection.

put local-file [remote-file]
Store a local file on the remote machine. If remote-file is left unspecified, the local file name is used in naming the remote file, after processing according to any ntrans or nmap settings. File transfer uses the current settings for type, format, mode, and structure.

pwd Print the name of the current working directory on the remote machine.

BOURNE1.TXT

- quit A synonym for bye.
- quote arg1 arg2 ...
 The arguments specified are sent, verbatim, to the remote FTP server.
- recv remote-file [local-file]
 A synonym for get.
- remotehelp [command-name]
 Request help from the remote FTP server. If a command-name is specified, it is supplied to the server as well.
- rename [from] [to]
 Rename, on the remote machine, the file from to the file to.
- reset Clear reply queue. This command re-synchronizes command/reply sequencing with the remote FTP server. Resynchronization may be necessary following a violation of the FTP protocol by the remote server.
- rmdir directory-name
 Delete a directory on the remote machine.
- runique Toggle storing of files on the local system with unique filenames. If a file already exists with a name equal to the target local filename for a get or mget command, a ".1" is appended to the name. If the resulting name matches another existing file, a ".2" is appended to the original name. If this process continues up to ".99", an error message is printed, and the transfer does not take place. The generated unique filename will be reported. Note that runique will not affect local files generated from a shell command (see below). The default value is off.
- send local-file [remote-file]
 A synonym for put.
- sendport Toggle the use of PORT commands. By default, ftp attempts to use a PORT command when establishing a connection for each data transfer. The use of PORT commands can prevent delays when performing multiple file transfers. If the PORT command

BOURNE1.TXT

fails, ftp uses the default data port. When the use of PORT commands is disabled, no attempt is made to use them for each data transfer. This is useful for certain FTP implementations that do ignore PORT commands but wrongly indicate they have been accepted.

- status Show the current status of ftp.
- struct [struct-name]
Set the file transfer structure to struct-name. The default structure is stream.
- sunique Toggle storing of files on remote machine under unique file names. Remote FTP server must support the FTP protocol STOU command for successful completion. The remote server will report a unique name. Default value is off.
- tenex Set the file transfer type to that needed to talk to TENEX machines.
- trace Toggle packet tracing.
- type [type-name]
Set the file transfer type to type-name. If no type-name is specified, the current type is printed. The default type is network ascii.
- user user-name [password] [account]
The user identifies him/herself to the remote FTP server. If the password is not specified and the server requires it, ftp prompts the user for it (after disabling local echo). If an account field is not specified, and the FTP server requires it, the user is prompted for it. If an account field is specified, an account command will be relayed to the remote server after the login sequence is completed if the remote server did not require it for logging in. Unless ftp is invoked with "auto-login" disabled, this process is done automatically on initial connection to the FTP server.
- verbose Toggle verbose mode. In verbose mode, all responses from the FTP server are displayed to the user. In addition, if verbose is on, when a file transfer completes, statistics regarding the

BOURNE1.TXT

efficiency of the transfer are reported. By default, verbose is on.

? [command]
A synonym for help.

Command arguments that have embedded spaces can be quoted with double quote (") marks.

ABORTING A FILE TRANSFER

To abort a file transfer, use the terminal interrupt key (usually <ctrl>C). Sending transfers will be immediately halted. Receiving transfers will be halted by sending a FTP protocol ABOR command to the remote server, and discarding any further data received. The speed at which this is accomplished depends upon the remote server's support for ABOR processing. If the remote server does not support the ABOR command, an ftp> prompt will not appear until the remote server has completed sending the requested file.

The terminal interrupt key sequence will be ignored when ftp has completed any local processing and is awaiting a reply from the remote server. A long delay in this mode may result from the ABOR processing described above, or from unexpected behavior by the remote server, including violations of the FTP protocol. If the delay results from unexpected remote server behavior, the local ftp program must be killed by hand.

FILE NAMING CONVENTIONS

Files specified as arguments to ftp commands are processed according to the following rules.

1. If the file name is -, the standard input (for reading) or the standard output (for writing) is used.
2. If the first character of the file name is a bar |, the remainder of the argument is interpreted as a shell command. ftp then forks a shell, using popen(3S) with the argument supplied, and reads (writes) from the stdout (stdin). If the shell command includes spaces, the argument must be quoted; for example, "| ls -lt". A particularly useful example of this mechanism is "dir | more".
3. Failing the above checks, if globbing is enabled, local file names are expanded according to the rules used in the csh(1); see the glob command. If the ftp command

BOURNE1.TXT

expects a single local file (e.g., put), only the first filename generated by the globbing operation is used.

4. For mget commands and get commands with unspecified local file names, the local filename is the remote filename, which may be altered by a case, ntrans, or nmap setting. The resulting filename may then be altered if runique is on.
5. For mput commands and put commands with unspecified remote file names, the remote filename is the local filename, which may be altered by a ntrans or nmap setting. The resulting filename may then be altered by the remote server if sunique is on.

FILE TRANSFER PARAMETERS

The FTP specification identifies many parameters that can affect a file transfer. The type can be one of ascii, image (binary), ebcdic, and local byte size (for PDP-10's and PDP-20's mostly). ftp supports the ascii and image types of file transfer, plus local byte size 8 for tenex mode transfers.

ftp supports only the default values for the remaining file transfer parameters: mode, form, and struct.

OPTIONS

Options can be specified at the command line, or to the command interpreter.

The -v (verbose on) option forces ftp to show all responses from the remote server, as well as report on data transfer statistics.

The -n option restrains ftp from attempting "auto-login" upon initial connection. If auto-login is enabled, ftp checks the netrc file in the user's home directory for an entry describing an account on the remote machine. If no entry exists, ftp will prompt for the remote machine login name (default is the user identity on the local machine), and, if necessary, prompt for a password and an account with which to login.

The -i option turns off interactive prompting during multiple file transfers.

The -d option enables debugging.

BOURNE1.TXT

The -g option disables file name globbing.

THE .netrc FILE

The .netrc file contains login and initialization information used by the "auto-login" process. It resides in the user's home directory. The following tokens are recognized; they may be separated by spaces, tabs, or new-lines:

machine name

Identify a remote machine name. The auto-login process searches the .netrc file for a machine token that matches the remote machine specified on the ftp command line or as an open command argument. Once a match is made, the subsequent .netrc tokens are processed, stopping when the end of file is reached or another machine token is encountered.

login name

Identify a user on the remote machine. If this token is present, the "auto-login" process will initiate a login using the specified name.

password string

Supply a password. If this token is present, the "auto-login" process will supply the specified string if the remote server requires a password as part of the login process. Note that if this token is present in the .netrc file, ftp will abort the "auto-login" process if the .netrc is readable by anyone besides the user.

account string

Supply an additional account password. If this token is present, the "auto-login" process will supply the specified string if the remote server requires an additional account password, or the "auto-login" process will initiate an ACCT command if it does not.

macrodef name

Define a macro. This token functions like the ftp macrodef command functions. A macro is defined with the specified name; its contents begin with the next .netrc line and continue until a null line (consecutive new-line characters) is encountered. If a macro named init is defined, it is automatically executed as the last step in the "auto-login" process.

BOURNE1.TXT

a.out.

If only one input file with a .c or .s suffix is supplied, the compiler automatically deletes the object file output produced from that input file after the executable program file a.out is created.

The cc options that modify the behavior described above are:

- A Cause ASCII assembler output to be generated and automatically piped to the assembler. The default is for direct generation of object code. The -A option is the same as the -q nodirect_code option.
- Bpath Run the compiler program contained in pathccom. If -B is specified with no path, then the default path is assumed to be /lib/o and the compiler program in /lib/ocom is run. If no -B option is specified, then the compiler program in /lib/ccom is run.
- c Compile only. Produce object file output, even if there was only one source file.
- C Retain comments during the macro preprocessor pass.
- Dname=def Define symbol name to be string def, as if by a #define statement. If =def is omitted, define name to be 1.
- E Run only the macro preprocessor, process only input files with the .c suffix; send the result of this pass to the standard output.
- g Generate special symbol table data for sdb(1) or cdb(1) and pass the -g flag to the link editor.
- G Cause object code to be directly generated by the compiler, bypassing the intermediate steps of producing assembly code and assembling it to produce object code. This is the default. The -G option is the same as the -q direct_code option.
- Idir dir is a directory name. Search for #include files whose names do not begin with / first in the directory containing the source file, then in dir, and then in a list of standard defaults. Multiple -I options can establish a hierarchy of #include

BOURNE1.TXT

file directories.

- o output
Name the final, executable output file output instead of a.out. Note the space between the -o and the file name.
- O Perform optimizations which speed up the generated code. Also, perform any space optimizations which do not impact code speed. See also the -q option.
- p Prepare to generate an execution profile using prof(1). Include special profiling code that counts how many times each routine is called. If linking occurs, use a special startup routine that calls monitor(3C) and produces a mon.out file upon termination. Uses special profiling versions of standard libraries found in /usr/lib/libp/lib*.a. NOTE: use of the MARK macro (see prof(5)) requires the -A option of cc.
- pg Prepare to generate an execution profile using gprof(1). Include special profiling code that counts how many times each function is called and how much time is spent in each. If linking occurs, use a special startup function that calls monstartup and produces a gmon.out file upon termination. Uses special profiling versions of standard libraries found in /usr/lib/libp/lib*.a. Note: Use of the MARK macro (see prof(5)) requires the -A option of cc.
- P Run all .c files through the preprocessing step, putting the result in the corresponding output file with a .i suffix.
- R Make initialized variables shared and read-only (by passing the -r option to the assembler).
- S Generate only assembly language output, putting it in one or more files that have the source file name and an .s suffix.
- Uname Undefine symbol name to remove its default definition.
- v Report the names of all subprocesses invoked in the compiled program, and their arguments. This option

BOURNE1.TXT

shows any files that are linked automatically and the current compiler, assembler, and link editor options.

- w Suppress warning diagnostics.
- Wc,arg
- Wa,arg
- Wl,arg Pass option arg to the compiler (see "C Compiler Internal Options" in the "Compiler and C Language" chapter in the UMAX V Programmer's Guide), assembler (see as(1)), or linker (see ld(1)), respectively.

The following options are intended to provide more detailed control over the generated code and action of the compiler. In general, they should only be used for special situations.

- q qualifier
- q qualifier=arg
Modify the generated code of the compiler to reflect various special requirements of a program. Qualifiers include the following:
 - align_text, noalign_text
Enable alignment of text segments on boundaries that allows the burst mode of systems equipped with APCs (Advanced Dual Processor Cards, utilizing the NS32332 CPU chip) to be most effectively used. The default option is -q noalign_text, unless the -q optimize=time option is specified.
 - xpc, apc, dpc
Generate code optimized for a system equipped with XPCs (Extended Performance Dual Processor Cards, utilizing the NS32532 CPU chip), APCs (Advanced Dual Processor Cards, utilizing the NS32332 CPU chip), or DPCs (Dual Processor Cards, utilizing the NS32032 CPU chip). If the -q xpc option is specified, then the preprocessor symbol ns32532 is defined and code optimal for the NS32532 is generated. If the -q apc option is specified, then the preprocessor symbol ns32332 is defined and the -q align_text option is enabled. If the -q dpc option is specified, then the preprocessor symbol ns32032 is defined and the

BOURNE1.TXT

-q noalign_text option is enabled. If neither -q xpc nor -q apc nor -q dpc is specified, then the default option is either -q xpc or -q apc or -q dpc, depending upon whether the system upon which the compiler is running is equipped with XPCs, APCs, or DPCs, respectively. Code generated with these options will work on all XPCs, APCs, and DPCs.

asmdir=prefix

crt0dir=prefix

lddir=prefix

Overrides the defaults for the locations of as(1) (the assembler), the relevant startup routine (either crt0.o, mcrt0.o, or gcrt0.o), and ld(1) (the link editor). The default values for these are asmdir=/bin/, crt0dir=/lib/ (if the startup routine is crt0.o or mcrt0.o), crt0dir=/usr/lib/ (if the startup routine is gcrt0.o), and lddir=/bin/.

compiler_registers, nocompiler_registers

Enable or disable compiler allocation of local variables to registers beyond those specified by register storage class specifications. The default option is -q compiler_registers. The -q nocompiler_registers option should only be used when code is written to depend on the existence of non-register class variables in memory.

direct_code, nodirect_code

Enable or disable the direct generation of code by the compiler. When enabled, the compiler will directly generate object code, bypassing the intermediate steps of producing assembly code and assembling it to produce the object code. The -q nodirect_code option (same as the -A option) should only be needed if the source file contains asm statements. The -q direct_code option (same as the -G option) is enabled by default. The -q nodirect_code option is enabled if the -R option is specified.

enter_exits, noenter_exits

Generate enter and exit instructions at subroutine start and end. Enter and exit

BOURNE1.TXT

instructions make stack tracing by debuggers possible. The `-q noenter_exits` option is enabled by default, unless the `-g` option is used.

`extensions, noextensions`

`extensions=parallel`

`extensions=microtasking`

Specifies which language extensions will be recognized. The `-q extensions=parallel` option specifies that extensions which support parallel programming are recognized. This includes shared memory declarations and in-line code generation for spin lock routines. Consult the section "C Parallel Programming Extensions" in Chapter 18, Compiler and C Language in the UMAX V Programmer's Guide. The `-q extension=microtasking` option specifies that extensions which support microtasking are recognized. This includes the `-q extension=parallel` extensions, and also specifies that the microtasking library and an alternate version of `crt0.o` are to be used by the load step. The `-q extensions` option is equivalent to `-q extension=microtasking`. The default option is `-q noextensions`.

`limitfregs, nolimitfregs`

Use or don't use the new NS32532 double precision floating point registers `f1`, `f3`, `f5`, `f7`. This flag is valid only in conjunction with the `-q xpc` flag. The default value for this flag is `-q limitfregs` (the new registers are not used). The double precision registers `f1`, `f3`, `f5`, `f7` do not exist on APCs and DPCs, and code that uses these registers will not work on APCs and DPCs.

`includes, noincludes`

Look or don't look for C language include files in the standard directory `/usr/include`. `-q noincludes` specifies there is no standard location for the include files. The default value is `-q includes`.

`long_case, nolong_case`

Enable or disable the generation of case statements using a full four byte displacement.

BOURNE1.TXT

The `-q nolong_case` option is the default, allowing case statements to span 8 Kilobytes. The `-q long_case` option allows case statements to span 16 Megabytes. This should only be needed in unusual circumstances.

long_jump, nolong_jump

Enable or disable the generation of jumps with four byte displacements when the assembler is unable to resolve them in 1 byte. This option only has effect when direct code generation is not enabled. The default option, `-q nolong_jump`, allows branches to span up to `_8` Kilobytes. The `-q long_jump` option will allow branches to span up to `_16` Megabytes.

loops, noloops

Enable or disable loop optimizations. These optimizations include loop-invariant hoisting and strength reduction. The default option is `-q noloops`.

optimize, nooptimize

`optimize=none, optimize=standard, optimize=time, optimize=space`
Specify the level of optimization. The `-q optimize` option is equivalent to the `-q optimize=standard`. The `-q nooptimize` option is equivalent to `-q optimize=none`. The `-O` option is equivalent to `-q optimize=standard`. The `-q optimize=standard` option enables a set of optimizations that do not take an excessive time to generate and do not overly favor space over time or vice versa. The `-q optimize=time` option enables optimizations which may take longer to recognize but should yield a program that takes minimal time. This option enables `-q align_text`, `-q loops`, and `-q novolatile`. If any of these options are inappropriate, they may be overridden by the appropriate `-q noxxx` option. The `-q optimize=space` option enables optimizations which may take longer to generate but should yield a program which takes minimal space. This option enables `-q preload_constants` and `-q tail_merge`. The default option is `-q optimize=none`.

preload_constants, nopreload_constants

Enable or disable the linking of constant

BOURNE1.TXT

values and addresses that are frequently referenced in the source code at the start of a program. This option saves space; it may save execution time if the constants and addresses are also referenced frequently during execution. The `-q nopreload_constants` option is the default; the `-q preload_constants` option is enabled by the `-O` option.

`reg_params, noreg_params`

Pass the first two parameters to a subroutine in registers rather than on the stack. The `-q noreg_params` option is the default. The standard libraries provided with the system assume `-q noreg_params` and will not work with object files built with the `-q reg_params` option.

`sbfixed, nosbfixed`

Enable or disable the use of the NS32000 `sb` register when generating immediate addresses. The `-q sbfixed` option is the default.

`signed_bit_fields, nosigned_bit_fields`

Enable or disable making bit fields in structures of type `int`, `short`, and `char` to be signed. The default option, `-q nosigned_bit_fields`, is to make all fields unsigned.

`small_enums, nosmall_enums`

Enable or disable the allocation of each enum type as the smallest predefined type that can represent all of the values that are listed (that is values of type `char`, `short`, `int`, `unsigned char`, `unsigned short`, or `unsigned int` that are used in the enum statement). The default option, `-q nosmall_enums`, allocates an enum type as an `int`.

`standard_library, nostandard_library`

Allows the compiler to replace calls to standard libc routines with equivalent in-line code. The default option is `-q nostandard_library`, unless the `-q optimize=time` option is specified.

`tail_merge, notail_merge`

BOURNE1.TXT

Enable or disable branch-tail merging, an optimization which reduces code size by sharing common portions of then and else clauses or of case switches. The `-q tail_merge` option is enabled by default, and disabled when `-O` is specified.

volatile, novolatile

Disable or enable additional optimization on the assumption that memory never changes except as the result of explicit store operations. The default option, `-q volatile`, disables these optimizations. The `-q novolatile` option should be used when all variables that can be modified asynchronously (e.g., by signal handlers) have type `volatile`. Asynchronous modification could happen, for example, with signals, device drivers, and parallel processes accessing shared memory. The current default is `-q novolatile`. In the future, the goal is to have `-q volatile` the default value.

FILES

<code>file.c</code>	input file
<code>file.o</code>	object file
<code>a.out</code>	linked output
<code>/lib/ccom</code>	compiler
<code>/lib/occom</code>	backup compiler
<code>/lib/crt0.o</code>	runtime startoff
<code>/lib/mcrt0.o</code>	startoff for profiling
<code>/lib/libc.a</code>	standard library, see <code>intro(3)</code>
<code>/usr/lib/lib*.a</code>	profiling libraries, see <code>intro(3)</code>
<code>/usr/include</code>	standard directory for <code>#include</code> files
<code>mon.out</code>	file produced for analysis by <code>prof(1)</code>

SEE ALSO

`adb(1)`, `as(1)`, `cdb(1)`, `gprof(1)`, `ld(1)`, `prof(1)`, `sdb(1)`, `a.out(4)`, `monitor(3C)`.
`cflow(1)` in the UMAX V User's Reference Manual.
"C Language" and "Compiler and C Language" in the UMAX V `cflow(1)` in the UMAX V User's Reference Manual.
"C Language" and "Compiler and C Language" in the UMAX V Programmer's Guide.
B. W. Kernighan and D. M. Ritchie, The C Programming Language. Prentice-Hall, 1978.

DIAGNOSTICS

The diagnostics produced by C itself are intended to be

BOURNE1.TXT

executable program file named aout.

If only one input file with an f, F, e, r, or s extension is supplied, the compiler automatically deletes the object file output produced from that input file after executable program file aout has been created.

All unrecognized options and all file names with extensions other than .f, .F, .e, .r, .c are passed to the loader. For assembler options, see as(1); for loader options, see ld(1). The f77 options are:

- Bprefix Run the compiler program contained in file prefixfcom. If prefix is not given, /usr/lib/ofcom is the default compiler used.
- c Compile only. Produce object file output (even if there was only one source file) and do not load the program after compiling it.
- Dname=def Define symbol name to be string def, when running the C language preprocessor, as if by a #define statement. If =def is omitted, defines name to be 1 while running the C preprocessor.
- Estring Pass option(s) string to the efl preprocessor when processing input files that have the e extension.
- F Generate only Fortran language output from the ratfor or efl preprocessor, placing it in a file that has the source file name and the f extension, but do not run the Fortran-77 compiler.
- g Generate special symbol table data for the sdb(1) debugger (or the optional debugger), and pass the -lg flag to the loader.
- Ipath Include source files from the directory named path when running the C language preprocessor. When compiling source files named with the F extension, search for #include files (whose names do not begin with /) first in the directory containing the source file, then in the directory path, and then in a list of standard defaults. Multiple -I options can establish a hierarchy of #include file directories.

BOURNE1.TXT

- i2 Make the default length of integer constants and variables, and all logical quantities, be short. Complementary option -i4 is the default, which calls for long integer variables and constants.
- m Apply the M4 macro preprocessor to each EFL or Ratfor source file before passing it through the efl or ratfor preprocessor.
- O Perform optimizations that speed up the generated code; also perform any space optimizations that do not impact code speed. See also the -q qualifier options.
- o output Name the final, executable output file output rather than aout.
- onetrip Generate object code that executes the range of every do loop at least once, even if the initial value of the loop index exceeds the limit value.
- p Prepare to generate an execution profile using prof(1). Include special profiling code that counts how many times each routine is called. If loading occurs, use a special startup routine that calls monitor(3) and produces a monout file upon termination. Use a special profiling library instead of the standard C library.
- pg Generate an execution profile using gprof. Include special profiling code that counts how many times each routine is called. If loading occurs, use a special startup routine that calls monitor(3) and produces one or more gmon.pid upon termination. A profiling version of the standard library is used.
- R Make initialized variables shared and read-only (by passing the -r option to the assembler).
- Rstring Pass option(s) string to the ratfor preprocessor when processing input files that have an r extension.
- S Generate assembly language output for each source file, but do not assemble it. Assembler output for a source file with the extension f, F, e, r, or c is put in a file with the same name and a s

BOURNE1.TXT

extension.

- U Do not convert uppercase letters to lowercase letters. By default Fortran programs are converted to lowercase letters except within character string constants.
- u Disable automatic data typing and, instead, make the default type of a variable the undefined type.
- v Report the names of all subprocesses invoked by the compiler and their arguments.
- w Suppress warning diagnostics.
- w66 Recognized only for compatibility with the Portable Fortran-77 Compiler, which used this option to suppress warnings about Fortran-66 features encountered during compilation. The Fortran-77 compiler does not flag language elements that are unique to Fortran-66.
- W[a c l], arg
Pass option arg to the assembler, compiler, or linker, as specified respectively by -Wa, arg, -Wc, arg, or -Wl, arg. The internal options for the f77 compiler include implementation options used to reconfigure the compiler for alien operating environments, and debugging options used for testing compiler software. These options should never be used in normal operation; they are described in the Fortran-77 Manual.
- q qualifier[=arg]
The qualifier options provide more detailed control over the generated code and action of the compiler. They modify the generated code of the compiler to reflect various special requirements of a program, and in general should only be used for special situations. The qualifier options deal with architecture, optimization selections, file configuration, and Fortran language extensions. In this listing they are grouped by category. Both the qualifiers and any arguments, which have compiler-defined values, can be abbreviated to their minimum number of unique characters. The qualifiers are:

BOURNE1.TXT

portable

apc, apc01, apc02, dpc, xpc[,2arg], host_is_target,
These qualifiers select generation of code that is compatible with Multimax systems having APC DPC or XPC (National Semiconductor NS32xxx-based) processor boards. The default is to generate code appropriate for the machine on which the compiler is running. (Differences between generated APC and DPC code are primarily in alignment optimization.)

apc The apc qualifier selects APC01 code and the libm_apc.a math library.

apc01 The apc01 qualifier is the same as the apc qualifier. It is equivalent to the obsoleted switch combination, -q apc -q nofpa.

apc02 The apc02 qualifier selects APC02 code (with Cone instructions) and uses the libm_fpa.a math library. This is equivalent to the obsoleted switch combination, -q apc -q fpa.

dpc The dpc qualifier selects code optimized for a DPC system, and uses the libm_apc.a library.

xpc[,arg]

The xpc qualifier generates code optimized for XPC systems, using the libm_xpc.a math library. Since xpc permits access of 4 additional floating point (fp) registers and uses floating point instructions that do not exist for APC and DPC boards, code compiled using this option may not be portable to APC and DPC systems. xpc accepts the arguments limitfregs and nolimitfregs. -q xpc,limitfregs assures code compatibility with APC and DPC systems, selecting the libm_apc.a math library rather than libm_xpc.a and suppressing the usage of some double-precision floating point registers that are available to

BOURNE1.TXT

XPC systems; only 4 double-precision float registers are used.
-q xpc,nolimitfregs permits all floating point registers to be used, and uses the libm_xpc.a math library.

host_is_target

The host_is_target qualifier optimizes code for the system performing the compilation. No attempt is made to preserve portability. This is default behavior.

portable

The portable qualifier generates code that is portable across all Multimax APC, DPC, and XPC systems. A universal math library, libm_apc.a, is used. Only optimizations that are explicitly portable are used. Produced code is portable to APC and DPC systems even if compiled on an XPC system, since only 4 double-precision float registers are used.

align_text, noalign_text

Enable or disable alignment of text segments on boundaries to optimize burst mode on Multimax systems having APC s. The default is noalign_text, unless optimize=time is enabled.

asmdir=prefix

Use the assembler located in the prefixas file instead of the default assembler, /bin/as.

compiler_registers, nocompiler_registers

Enable or disable compiler allocation of local variables to registers beyond those specified by register storage class specifications. The default is compiler_registers. nocompiler_registers should only be used when code is written to depend on the existence of non-register class variables in memory.

crt0dir=prefix

BOURNE1.TXT

Use the prefixcrt0.o startup file instead of the default startup file, /lib/crt0.o.

d_lines, nod_lines

Enable or disable the recognition of any comment line, beginning with a D, as a code line. The default is nod_lines.

direct_code, nodirect_code

Enable or disable the direct generation of code by the compiler. When enabled, the compiler directly generates object code, bypassing the intermediate steps of producing assembly code and assembling it to produce the object code. The nodirect_code qualifier should only be needed if the source file contains asm statements. direct_code is enabled by default. nodirect_code is enabled if the -R option is specified.

extensions[=arg], noextensions

Enable or disable the specification of Fortran extensions. The default qualifier is noextensions. The available arguments are:

- berkeley_f77 Supports the standard UNIX f77. This is equivalent to noextensions.
- extended_f77 Supports an extension to f77 that allows Fortran programs written for VAX/VMS to be compiled on Multimax systems. This is the default when the -q extensions qualifier is given without an argument.
- parallel Recognizes the extensions that support parallel programming, including shared memory declarations and spinlocks in-line. This does not change the value of an earlier specified berkeley_f77 or extended_f77 selection.

BOURNE1.TXT

lddir=prefix

Use the link editor in prefixld instead of the default, /bin/ld.

long_case, nolong_case

Enable or disable the generation of case statements using a full four-byte displacement. nolong_case is the default, allowing case statements to span 4 Kilobytes. long_case allows case statements to span 2 Megabytes. This should only be needed in unusual circumstances.

long_jump, nolong_jump

Enable or disable the generation of jumps with four-byte displacements when the assembler is unable to resolve them in one byte. The default, nolong_jump, allows branches to span up to 8 Kilobytes. long_jump allows branches to span up to 16 Megabytes. Direct code generation selects one-, two-, or four-byte displacement as appropriate, regardless of the setting of this option.

loops, noloops

Enable or disable loop optimizations. These optimizations include loop-invariant hoisting and strength reduction. The default is noloops.

optimize[=arg], nooptimize

Enable or disable different levels of optimization. The default is optimize=none. The available arguments are:

- | | |
|----------|---|
| none | Enable no special optimizations. none is equivalent to nooptimize. |
| space | Enable optimizations which may take longer to generate but which should produce a program that requires minimal space. This argument also enables preload_constants and tail_merge. |
| standard | Enable a set of optimizations |

BOURNE1.TXT

that do not take an excessive amount of time to generate and which do not favor space over time (or vice versa).

`time` Enable optimizations which may take longer to recognize but which should produce a program that requires minimal execution time. This argument also enables `align_text`, `loops`, and `novolatile`.

`preload_constants`, `nopreload_constants`

Enable or disable the loading of constant values and addresses that are frequently referenced in the source code at the start of a program. This option saves space; it may save execution time if the constants and addresses are also referenced frequently during execution. `no_preload_constants` is the default; `preload_constants` is enabled by the `-O` option.

`single_lib`, `nosingle_lib`

Enable or disable the use of single precision math routines for certain built-in functions when the functions are called with single precision arguments. The single precision versions offer significantly increased speed with almost no reduction in accuracy. `single_lib` is enabled by default.

`tail_merge`, `notail_merge`

Enable or disable branch-tail merging, an optimization that reduces code size by sharing common portions of then and else clauses or of case switches. `tail_merge` is disabled by default.

`volatile`, `novolatile`

Enable or disable additional optimization on the assumption that memory never changes except as the result of explicit store operations. The default is `volatile`, unless `optimize=time` is selected. `novolatile`, which enables the optimizations, is available only when `optimize=time` is selected. `novolatile` should only be used

BOURNE1.TXT

when it is clear that no variables can be modified asynchronously. Asynchronous modification could happen, for example, with signals, device drivers, or parallel processes accessing shared memory.

RESTRICTIONS

The -q flag and its qualifier options replace the following options, which are no longer supported:

- A Replaced by -q nodirect_code.
- G Replaced by -q direct_code.
- H Replaced by -q notail_merge.
- J Replaced by -q long_jump.
- T Replaced by -q loops.
- V Replaced by -q novolatile.

FILES

./fort[pid].?	temporary fortran process files
a.out	loaded output file
file.[fFresc]	input file
file.o	object file
gmon.[pid]	file produced for analysis by monitor(3)
mon.out	file produced for analysis by prof(1)
/lib/cpp	C preprocessor
/lib/libc.a	C library
/lib/cpp	C preprocessor
/lib/libc.a	C library
/usr/lib/fcom	Fortran compiler
/usr/lib/libFBERK.a	combined libF77.a, libI77.a, and libU77.a library
/usr/lib/libFBERK_p.a	profiling combined Berkeley function library
/usr/lib/libFORT.a	combined libFBERK.a and libX77.a library
/usr/lib/libFORT_p.a	profiling combined extended Berkeley function
/usr/lib/libm_apc.a	standard NS32081 code math library
/usr/lib/libm_fpa.a	math library for APC02 systems with Cone processor
/usr/lib/libm_xpc.a	XPC system math library (8 float-register, NS32381)

BOURNE1.TXT

is appended instead. When the `-c` option is not used, the second pass of lint checks this list of files for mutual compatibility. When the `-c` option is used, the `.ln` and the `llib-lx.ln` files are ignored.

Any number of lint options may be used, in any order, intermixed with file-name arguments. The following options are used to suppress certain kinds of complaints:

- a Suppress complaints about assignments of long values to variables that are not long.
- b Suppress complaints about break statements that cannot be reached. (Programs produced by `lex(1)` or `yacc(1)` will often result in many such complaints.)
- h Do not apply heuristic tests that attempt to intuit bugs, improve style, and reduce waste.
- u Suppress complaints about functions and external variables used and not defined, or defined and not used. (This option is suitable for running lint on a subset of files of a larger program).
- v Suppress complaints about unused arguments in functions.
- x Do not report variables referred to by external declarations but never used.

The following arguments alter lint's behavior:

- lx Include additional lint library `llib-lx.ln`. For example, a lint version of the Math Library `llib-lm.ln` can be included by inserting `-lm` on the command line. This argument does not suppress the default use of `llib-lc.ln`. These lint libraries must be in the assumed directory. This option can be used to reference local lint libraries and is useful in the development of multi-file projects.
- n Do not check compatibility against either the standard or the portable lint library.
- p Attempt to check portability to other dialects (IBM and GCOS) of C. Along with stricter checking, this option causes all non-external names to be truncated to eight characters and all external names to be truncated to

BOURNE1.TXT

six characters and one case.

-c Cause lint to produce a .ln file for every .c file on the command line. These .ln files are the product of lint's first pass only, and are not checked for inter-function compatibility.

-o lib

Cause lint to create a lint library with the name llib-llib.ln. The -c option nullifies any use of the -o option. The lint library produced is the input that is given to lint's second pass. The -o option simply causes this file to be saved in the named lint library. To produce a llib-llib.ln without extraneous messages, use of the -x option is suggested. The -v option is useful if the source file(s) for the lint library are just external interfaces (for example, the way the file llib-1c is written). These option settings are also available through the use of "lint comments" (see below).

The -D, -U, and -I options of cc(1) and cpp(1) and the -g and -O options of cc are also recognized as separate arguments. The -g and -O options are ignored, but, by recognizing these options, lint's behavior is closer to that of the cc command. Other options are warned about and ignored. The pre-processor symbol "lint" is defined to allow certain questionable code to be altered or removed for lint. Therefore, the symbol "lint" should be thought of as a reserved word for all code that is planned to be checked by lint.

Certain conventional comments in the C source will change the behavior of lint:

```
/*NOTREACHED*/
```

at appropriate points stops comments about unreachable code. (This comment is typically placed just after calls to functions like exit(2).)

```
/*VARARGSn*/
```

suppresses the usual checking for variable numbers of arguments in the following function declaration. The data types of the first n arguments are checked; a missing n is taken to be 0.

```
/*ARGSUSED*/
```

turns on the -v option for the next function.

BOURNE1.TXT

/*LINTLIBRARY*/

at the beginning of a file shuts off complaints about unused functions and function arguments in this file. This is equivalent to using the -v and -x options.

lint produces its first output on a per-source-file basis. Complaints regarding included files are collected and printed after all source files have been processed. Finally, if the -c option is not used, information gathered from all input files is collected and checked for consistency. At this point, if it is not clear whether a complaint stems from a given source file or from one of its included files, the source file name will be printed followed by a question mark.

The behavior of the -c and the -o options allows for incremental use of lint on a set of C source files. Generally, one invokes lint once for each source file with the -c option. Each of these invocations produces a .ln file which corresponds to the .c file, and prints all messages that are about just that source file. After all the source files have been separately run through lint, it is invoked once more (without the -c option), listing all the .ln files with the needed -lx options. This will print all the inter-file inconsistencies. This scheme works well with make(1); it allows make to be used to lint only the source files that have been modified since the last time the set of source files were linted.

FILES

/usr/lib/lint[12]	first and second passes
/usr/lib/l1ib-lc.ln	declarations for C Library functions (binary format; source is in /usr/lib/l1ib-lc)
/usr/lib/l1ib-port.ln	declarations for portable functions (binary format; source is in /usr/lib/l1ib-port)
/usr/lib/l1ib-lm.ln	declarations for Math Library functions (binary format; source is in /usr/lib/l1ib-lm.ln)
/usr/tmp/*lint*	temporaries

SEE ALSO

cc(1), cpp(1), lex(1), make(1), yacc(1), tmpnam(3S).

BUGS

exit(2), longjmp(3C), and other functions that do not return

BOURNE1.TXT

The `ar` command maintains groups of files combined into a single archive file. Its main use is to create and update library files as used by the link editor. It can be used, though, for any similar purpose. The magic string and the file headers used by `ar` consist of printable ASCII characters. If an archive is composed of printable files, the entire archive is printable.

When `ar` creates an archive, it creates headers in a format that is portable across all machines. The portable archive format and structure is described in detail in `ar(4)`. The archive symbol table (described in `ar(4)`) is used by the link editor (`ld(1)`) to effect multiple passes over libraries of object files in an efficient manner. An archive symbol table is only created and maintained by `ar` when there is at least one object file in the archive. The archive symbol table is in a specially named file which is always the first file in the archive. This file is never mentioned or accessible to the user. Whenever the `ar` command is used to create or update the contents of such an archive, the symbol table is rebuilt. The `s` option described below will force the symbol table to be rebuilt. The symbol table holds a maximum of 20,000 symbols.

Unlike command options, the command key is a required part of `ar`'s command line. The key (which may begin with a `-`) is formed with one of the following letters: `drqtpmx`. Arguments to the key, alternatively, are made with one of more of the following set: `vuaibcls`. `posname` is an archive member name used as a reference point in positioning other files in the archive. `afile` is the archive file. The names are constituent files in the archive file. The meanings of the key characters are as follows:

- `d` Delete the named files from the archive file.
- `r` Replace the named files in the archive file. If the optional character `u` is used with `r`, then only those files with dates of modification later than the archive files are replaced. If an optional positioning character from the set `aib` is used, then the `posname` argument must be present and specifies that new files are to be placed after (`a`) or before (`b` or `i`) `posname`. Otherwise new files are placed at the end.
- `q` Quickly append the named files to the end of the archive file. Optional positioning characters are invalid. The command does not check whether the added

BOURNE1.TXT

members are already in the archive. This option is useful to avoid quadratic behavior when creating a large archive piece-by-piece. Unchecked, the file may grow exponentially up to the second degree.

- t Print a table of contents of the archive file. If no names are given, all files in the archive are tabled. If names are given, only those files are tabled.
- p Print the named files in the archive.
- m Move the named files to the end of the archive. If a positioning character is present, then the posname argument must be present and, as in r, specifies where the files are to be moved.
- x Extract the named files. If no names are given, all files in the archive are extracted. In neither case does x alter the archive file.

The meanings of the key arguments are as follows:

- v Give a verbose file-by-file description of the making of a new archive file from the old archive and the constituent files. When used with t, give a long listing of all information about the files. When used with x, precede each file with a name.
- c Suppress the message that is produced by default when afile is created.
- l Place temporary files in the local (current working) directory, rather than in the default temporary directory, /tmp.
- s Force the regeneration of the archive symbol table even if ar is not invoked with a command which will modify the archive contents. This command is useful to restore the archive symbol table after the strip(1) command has been used on the archive.

SEE ALSO

ld(1), lorder(1), strip(1), tmpnam(3S), a.out(4), ar(4).
"The Common Object File Format" in the UMAX V Programmer's Guide.

BUGS

BOURNE1.TXT

If the same file is mentioned twice in an argument list, it may be put in the archive twice.

NAME

ar - common archive file format

DESCRIPTION

The archive command ar(1) combines several files into one. Archives are used mainly as libraries to be searched by the link editor ld(1).

Each archive begins with the archive magic string:

```
#define ARMAG      "!<arch>\n" /* magic string */
#define SARMAG     8          /* length of magic string */
```

Each archive that contains common object files (see a.out(4)) includes an archive symbol table. The link editor ld uses the symbol table to determine which archive members must be loaded during the link edit process. The archive symbol table (if it exists) is always the first file in the archive (but is never listed) and is automatically created and updated by ar.

Following the archive magic string are the archive file members. Each file member is preceded by a file member header in the following format:

```
#define ARFMAG      "\n" /* header trailer string */
struct ar_hdr {      /* file member header */
    char ar_date[12]; /* file member date */
                    /* member name */
    char ar_gid[6];   /* file member group
                    identification */
    char ar_mode[8];  /* file member mode
                    (octal) */
    char ar_size[10]; /* file member size */
    char ar_fmags[2]; /* header trailer string */
};
```

All information in the file member headers is in printable ASCII . The numeric information in the headers is stored as decimal numbers (except for ar_mode, which is in octal).

BOURNE1.TXT

Ctime converts a system time to a 24-character ASCII string. The format is described under ctime(3). No newline or NULL is included.

Ltime and gmtime both dissect a time field into month, day, etc., either for the local time zone or for GMT. The order and meaning of each element returned in tarray is described under ctime(3).

FILES

/usr/lib/libU77.a

SEE ALSO

ctime(3), itime(3F), idate(3F), fdate(3F)

NAME

time - time a command

SYNOPSIS

time command

DESCRIPTION

The command is executed; after it is complete, time prints the elapsed time during the command, the time spent in the system, and the time spent in execution of the command. Times are reported in seconds.

The times are printed on standard error.

SEE ALSO

timex(1).

times(2) in the UMAX V Programmer's Reference Manual.

APPENDIX K - ksh

\$man ksh

NAME

ksh, rksh - korn shell, a command programming language

SYNOPSIS

ksh [-acefhikmnorstuvx] [-o option] ... [arg ...]

rksh [-acefhikmnorstuvx] [-o option] ... [arg ...]

DESCRIPTION

ksh is a command programming language that executes commands read from a terminal or a file. rksh is a restricted version of the standard command interpreter ksh; it is used

BOURNE1.TXT

to set up login names and execution environments whose capabilities are more controlled than those of the standard shell. See Invocation below for the meaning of arguments to the shell.

ksh is close to being upwards compatible with the standard Bourne shell (sh(1)). Its major enhancements include command re-entry, in-line command editing, and aliasing.

Definitions.

A metacharacter is one of the following characters:

`; & () | < >` new-line space tab

A blank is a tab or a space. An identifier is a sequence of letters, digits, or underscores starting with a letter or underscore. Identifiers are used as names for aliases, functions, and named parameters. A word is a sequence of characters separated by one or more non-quoted metacharacters.

Commands.

A simple-command is a sequence of blank separated words which may be preceded by a parameter assignment list. (See Environment below). The first word specifies the name of the command to be executed. Except as specified below, the remaining words are passed as arguments to the invoked command. The command name is passed as argument 0 (see exec(2)). The value of a simple-command is its exit status if it terminates normally, or (octal) 200+status if it terminates abnormally (see signal(2) for a list of status values).

A pipeline is a sequence of one or more commands separated `|`. The standard output of each command but the last is connected by a pipe(2) to the standard input of the next command. Each command is run as a separate process; the shell waits for the last command to terminate. The exit status of a pipeline is the exit status of the last command. A list is a sequence of one or more pipelines separated by `;`, `&`, `&&`, or `||`, and optionally terminated by `;`, `&`, or `|&`. Of these five symbols, `;`, `&`, and `|&` have equal precedence, which is lower than that of `&&` and `||`. The symbols `&&` and `||` also have equal precedence. A semicolon (`;`) causes sequential execution of the preceding pipeline; an ampersand (`&`) causes asynchronous execution of the preceding pipeline (i.e., the shell does not wait for that pipeline to finish). The symbol `|&` causes asynchronous execution of the preceding

BOURNE1.TXT

command or pipeline with a two-way pipe established to the parent shell. The standard input and output of the spawned command can be written to and read from by the parent shell using the `-p` option of the special commands `read` and `print` described later. Only one such command can be active at any given time. The symbol `&&` (`||`) causes the list following it to be executed only if the preceding pipeline returns a zero (non-zero) value. An arbitrary number of new-lines may appear in a list, instead of semicolons, to delimit commands.

A command is either a simple-command or one of the following. Unless otherwise stated, the value returned by a command is that of the last simple-command executed in the command.

`for identifier [in word ...] do list done`

Each time a `for` command is executed, `identifier` is set to the next word taken from the `in word list`. If `in word ...` is omitted, then the `for` command executes the `do list` once for each positional parameter that is set (see Parameter Substitution below). Execution ends when there are no more words in the list.

`select identifier [in word ...] do list done`

A `select` command prints on standard error (file descriptor 2), the set of words, each preceded by a number. If `in word ...` is omitted, then the positional parameters are used instead (see Parameter Substitution below). The `PS3` prompt is printed and a line is read from the standard input. If this line consists of the number of one of the listed words, then the value of the parameter `identifier` is set to the word corresponding to this number. If this line is empty, the selection list is printed again. Otherwise the value of the parameter `identifier` is set to null. The contents of the line read from standard input is saved in the parameter `REPLY`. The list is executed for each selection until a break or end-of-file is encountered.

`case word in [pattern [| pattern] ...) list ;;] ... esac`

A `case` command executes the list associated with the first pattern that matches `word`. The form of the patterns is the same as that used for file-name generation (see File Name Generation below).

`if list then list [elif list then list] ... [else list] fi`

BOURNE1.TXT

The list following if is executed and, if it returns a zero exit status, the list following the first then is executed. Otherwise, the list following elif is executed and, if its value is zero, the list following the next then is executed. Failing that, the else list is executed. If no else list or then list is executed, then the if command returns a zero exit status.

while list do list done
until list do list done

A while command repeatedly executes the while list and, if the exit status of the last command in the list is zero, executes the do list; otherwise the loop terminates. If no commands in the do list are executed, then the while command returns a zero exit status; until may be used in place of while to negate the loop termination test.

(list)

Execute list in a separate environment. Note, that if two adjacent open parentheses are needed for nesting, a space must be inserted to avoid arithmetic evaluation as described below.

{list;}

list is simply executed. Note that { is a keyword and requires a blank in order to be recognized.

function identifier { list ;}
identifier () { list ;}

Define a function which is referenced by identifier. The body of the function is the list of commands between { and }. (See Functions below).

time pipeline

The pipeline is executed and the elapsed time as well as the user and system time are printed on standard error.

The following keywords are only recognized as the first word of a command and when not quoted:

if then else elif fi case esac for while until do done { }
function select time

Comments.

A word beginning with # causes that word and all the following characters up to a new-line to be ignored.

BOURNE1.TXT

Aliasing.

The first word of each command is replaced by the text of an alias if an alias for this word has been defined. The first character of an alias name can be any printable character, but the rest of the characters must be the same as for a valid identifier. The replacement string can contain any valid shell script including the metacharacters listed above. The first word of each command of the replaced text will not be tested for additional aliases. If the last character of the alias value is a blank then the word following the alias will also be checked for alias substitution. Aliases can be used to redefine special built-in commands but cannot be used to redefine the keywords listed above. Aliases can be created, listed, and exported with the alias command and can be removed with the unalias command. Exported aliases remain in effect for sub-shells but must be reinitialized for separate invocations of the shell (See Invocation below).

Aliasing is performed when scripts are read, not while they are executed. Therefore, for an alias to take effect the alias command has to be executed before the command which references the alias is read.

Aliases are frequently used as a short hand for full path names. An option to the aliasing facility allows the value of the alias to be automatically set to the full path name of the corresponding command. These aliases are called tracked aliases. The value of a tracked alias is defined the first time the identifier is read and undefined each time the PATH variable is reset. These aliases remain tracked so that the next subsequent reference will redefine the value. Several tracked aliases are compiled into the shell. The -h option of the set command makes each command name which is an identifier into a tracked alias.

The following exported aliases are compiled into the shell but can be unset or redefined:

```
echo='print -'  
false='let 0'  
functions='typeset -f'  
history='fc -l'  
integer='typeset -i'  
nohup='nohup '  
pwd='print - $PWD'  
r='fc -e -'
```

BOURNE1.TXT

```
true=':'  
type='whence -v'  
hash='alias -t'
```

Tilde Substitution.

After alias substitution is performed, each word is checked to see if it begins with an unquoted ~. If it does, then the word up to a / is checked to see if it matches a user name in the /etc/passwd file. If a match is found, the ~ and the matched login name is replaced by the login directory of the matched user. This is called a tilde substitution. If no match is found, the original text is left unchanged. A ~ by itself, or in front of a /, is replaced by the value of the HOME parameter. A ~ followed by a + or - is replaced by the value of the parameter PWD and OLDPWD respectively.

In addition, the value of each keyword parameter is checked to see if it begins with a ~ or if a ~ appears after a :. In either of these cases a tilde substitution is attempted.

Command Substitution.

The standard output from a command enclosed in a pair of grave accents (` `) may be used as part or all of a word; trailing new-lines are removed. The command substitution `cat file` can be replaced by the equivalent but faster ``. Command substitution of most special commands that do not perform input/output redirection are carried out without creating a separate process.

Parameter Substitution.

A parameter is an identifier, a digit, or any of the characters *, @, #, ?, -, \$, and !. A named parameter (a parameter denoted by an identifier) has a value and zero or more attributes. Named parameters can be assigned values and attributes by using the typeset special command. The attributes supported by the shell are described later with the typeset special command. Exported parameters pass values and attributes to sub-shells but only values to the environment.

The shell supports a limited one-dimensional array facility. An element of an array parameter is referenced by a subscript. A subscript is denoted by a [, followed by an arithmetic expression (see Arithmetic Evaluation below) followed by a]. The value of all subscripts must be in the range of 0 through 511. Arrays need not be declared. Any

BOURNE1.TXT

reference to a named parameter with a valid subscript is legal and an array will be created if necessary. Referencing an array without a subscript is equivalent to referencing the first element.

The value of a named parameter may also be assigned by writing:

```
name=value [ name=value ] ...
```

If the integer attribute, `-i`, is set for name the value is subject to arithmetic evaluation as described below. Positional parameters, parameters denoted by a number, may be assigned values with the set special command. Parameter `$0` is set from argument zero when the shell is invoked. The character `$` is used to introduce substitutable parameters.

`${parameter}`

The value, if any, of the parameter is substituted. The braces are required when parameter is followed by a letter, digit, or underscore that is not to be interpreted as part of its name or when a named parameter is subscripted. If parameter is a digit then it is a positional parameter. If parameter is `*` or `@`, then all the positional parameters, starting with `$1`, are substituted (separated by spaces). If an array identifier with subscript `*` or `@` is used, then the value for each of the elements is substituted (separated by spaces).

`${#parameter}`

If parameter is not `*`, the length of the value of the parameter is substituted. Otherwise, the number of positional parameters is substituted.

`${#identifier[*]}`

The number of elements in the array identifier is substituted.

`${parameter:-word}`

If parameter is set and is non-null then substitute its value; otherwise substitute word.

`${parameter:=word}`

If parameter is not set or is null then set it to word; the value of the parameter is then substituted. Positional parameters may not be assigned to in this way.

`${parameter:?word}`

If parameter is set and is non-null then substitute its value; otherwise, print word and exit from the shell. If word is omitted then a standard message is printed.

BOURNE1.TXT

`${parameter:+word}`

If parameter is set and is non-null then substitute word; otherwise substitute nothing.

`${parameter#pattern}`

`${parameter##pattern}`

If the shell pattern matches the beginning of the value of parameter, then the value of this substitution is the value of the parameter with the matched portion deleted; otherwise, the value of this parameter is substituted. In the first form the smallest matching pattern is deleted and in the latter form the largest matching pattern is deleted.

`${parameter%pattern}`

`${parameter%%pattern}`

If the shell pattern matches the end of the value of parameter, then the value of parameter with the matched part is deleted; otherwise substitute the value of parameter. In the first form the smallest matching pattern is deleted and in the latter form the largest matching pattern is deleted.

In the above, word is not evaluated unless it is to be used as the substituted string, so that, in the following example, pwd is executed only if d is not set or is null:

```
echo ${d:-`pwd`}
```

If the colon (:) is omitted from the above expressions, then the shell only checks whether parameter is set or not. If the shell pattern matches the end of the value of parameter, then the value of parameter with the matched part is deleted; otherwise substitute the value of parameter. In the first form the smallest matching pattern is deleted and in the latter form the largest matching pattern is deleted.

In the above, word is not evaluated unless it is to be used as the substituted string, so that, in the following example, pwd is executed only if d is not set or is null:

```
echo ${d:-`pwd`}
```

If the colon (:) is omitted from the above expressions, then the shell only checks whether parameter is set or not.

The following parameters are automatically set by the shell:

The number of positional parameters in decimal.

BOURNE1.TXT

- Flags supplied to the shell on invocation or by the set command.
- ? The decimal value returned by the last executed command.
- \$ The process number of this shell.
- _ The last argument of the previous command. This parameter is not set for commands which are asynchronous.
- ! The process number of the last background command invoked.
- PPID The process number of the parent of the shell.
- PWD The present working directory set by the cd command.
- OLDPWD
The previous working directory set by the cd command.
- RANDOM
Each time this parameter is referenced, a random integer is generated. The sequence of random numbers can be initialized by assigning a numeric value to RANDOM.
- RANDOM.
Each time this parameter is referenced, a random integer is generated. The sequence of random numbers can be initialized by assigning a numeric value to RANDOM.
- REPLY
This parameter is set by the select statement and by the read special command when no arguments are supplied.

The following parameters are used by the shell:

- CDPATH
The search path for the cd command.
- COLUMNS
If this variable is set, the value is used to define the width of the edit window for the shell edit modes and for printing select lists.
- EDITOR
If the value of this variable ends in emacs, gmacs, or vi and the VISUAL variable is not set, then the corresponding option (see Special Commands set below) will be turned on.
- ENV
If this parameter is set, then parameter substitution is performed on the value to generate the path name of the script that will be executed when the shell is invoked. (See Invocation below.) This file is typically used for alias and

BOURNE1.TXT

function definitions.

FCEDIT

The default editor name for the fc command.

IFS Internal field separators, normally space, tab, and new-line that is used to separate command words which result from command or parameter substitution and for separating words with the special command read.

HISTFILE

If this parameter is set when the shell is invoked, then the value is the path name of the file that will be used to store the command history. (See Command Re-entry below.)

HISTSIZE

If this parameter is set when the shell is invoked, then the number of previously entered commands that are accessible by this shell will be greater than or equal to this number. The default is 128.

HOME The default argument (home directory) for the cd command.

MAIL If this parameter is set to the name of a mail file and the MAILPATH parameter is not set, then the shell informs the user of arrival of mail in the specified file.

MAILCHECK

This variable specifies how often (in seconds) the shell will check for changes in the modification time of any of the files specified by the MAILPATH or MAIL parameters. The default value is 600 seconds. If set to 0, the shell will check before each prompt.

MAILPATH

A colon (:) separated list of file names. If this parameter is set then the shell informs the user of any modifications to the specified files that have occurred within the last MAILCHECK seconds. Each file name can be followed by a ? and a message that will be printed. The message will undergo parameter and command substitution with the parameter, \$_ defined as the name of the file that has changed. The default message is you have mail in \$_.

PATH The search path for commands (see Execution below). The user may not change PATH if executing under rksh (except in .profile).

PS1 The value of this parameter is expanded for parameter substitution to define the primary

BOURNE1.TXT

prompt string which by default is "\$ ". The character ! in the primary prompt string is replaced by the command number (see Command Re-entry below).

PS2 Secondary prompt string, by default "> ".

PS3 Selection prompt string used within a select loop, by default "#? ".

SHELL

The path name of the shell is kept in the environment. At invocation, if the value of this variable contains an r in the basename, then the shell becomes restricted.

TMOUT

If set to a value greater than zero, the shell will terminate if a command is not entered within the prescribed number of seconds. When the timer expires, a warning is printed and a 60 second grace period is provided.

VISUAL

If the value of this variable ends in emacs, gmacs, or vi then the corresponding option (see Special Commands set below) will be turned on.

The shell gives default values to PS1, PS2, MAILCHECK, TMOUT, and IFS. HOME, MAIL, SHELL, PATH, and TZ are set by login(1). The remaining parameters are typically set in /etc/profile, .profile, or \$(ENV) files.

After parameter and command substitution, the results of substitutions are scanned for the field separator characters (those found in IFS) and split into distinct arguments where such characters are found. Explicit null arguments "" or ' ' are retained. Implicit null arguments (those resulting from parameters that have no values) are removed.

Following substitution, each command word is scanned for the characters *, ?, and [unless the -f option has been set. If one of these characters appears then the word is regarded as a pattern. The word is replaced with alphabetically sorted file names that match the pattern. If no file name is found that matches the pattern, then the word is left unchanged. When a pattern is used for file name generation, the character . at the start of a file name or immediately following a /, as well as the character / itself, must be matched explicitly. In other instances of pattern matching the / and . are not treated specially.

* Matches any string, including the null string.

BOURNE1.TXT

? Matches any single character.

[...]

Matches any one of the enclosed characters. A

pair of characters separated by - matches any character lexically between the pair, inclusive. If the first character following the opening [is a !, then any character not enclosed is matched. A - can be included in the character set by putting it as the first or last character.

Each of the metacharacters listed above (See Definitions above) has a special meaning to the shell and causes termination of a word unless quoted. A character may be quoted (i.e., made to stand for itself) by preceding it with a \. The pair \new-line is ignored. All characters enclosed between a pair of single quote marks ('), except a single quote, are quoted. Inside double quote marks (""), parameter and command substitution occurs and \ quotes the characters \, ', ", and \$. \$* is equivalent to "\$1 \$2 ...", whereas @\$ is equivalent to \$1 \$2

The special meaning of keywords can be removed by quoting any character of the keyword. The recognition of special command names listed below cannot be altered by quoting them.

An ability to perform integer arithmetic is provided with the special command let. Evaluations are performed using long arithmetic. Constants are of the form [base#]n where base is a decimal number between two and thirty-six representing the arithmetic base and n is a number in that base. If the base is omitted then base 10 is used.

An internal integer representation of a named parameter can be specified with the -i option of the typeset special command. When this attribute is selected the first assignment to the parameter determines the arithmetic base to be used when parameter substitution occurs.

Since many of the arithmetic operators require quoting, an alternative form of the let command is provided. For any command which begins with a (, all the characters until a matching) are treated as a quoted expression. More precisely, ((...)) is equivalent to let " ...".

When used interactively, the shell prompts with the value of PS1 before reading a command. If at any time a new-line is

BOURNE1.TXT

typed and further input is needed to complete a command, then the secondary prompt (i.e., the value of PS2) is issued.

Before a command is executed, its input and output may be redirected using a special notation interpreted by the shell. The following may appear anywhere in a simple-command or may precede or follow a command and are not passed on to the invoked command. Command and parameter substitution occurs before word or digit is used except as noted below. File name generation occurs only if the pattern matches a single file and blank interpretation is not performed.

- <word Use file word as standard input (file descriptor 0).
- >word Use file word as standard output (file descriptor 1). If the file does not exist then it is created; otherwise, it is truncated to zero length.
- >>word Use file word as standard output. If the file exists then output is appended to it (by first seeking to the end-of-file); otherwise, the file is created.
- <<[-]word The shell input is read up to a line that is the same as word, or to an end-of-file. No parameter substitution, command substitution or file name generation is performed on word. The resulting document, called a here-document, becomes the standard input. If any character of word is quoted, no interpretation is placed upon the characters of the document; otherwise, parameter and command substitution occurs, \new-line is ignored, and \ must be used to quote the characters \, \$, `, and the first character of word. If - is appended to <<, all leading tabs are stripped from word and from the document.
- <&digit The standard input is duplicated from file descriptor digit (see dup(2)). Similarly for the standard output using >& digit.
- <&- The standard input is closed. Similarly for the standard output using >&-.

BOURNE1.TXT

If one of the above is preceded by a digit, then the file descriptor number referred to is that specified by the digit (instead of the default 0 or 1). For example:

```
... 2>&1
```

means file descriptor 2 is to be opened for writing as a duplicate of file descriptor 1.

The order in which redirections are specified is significant. The shell evaluates each redirection in terms of the (file descriptor, file) association at the time of evaluation. For example:

```
... 1>fname 2>&1
```

first associates file descriptor 1 with file fname. It then associates file descriptor 2 with the file associated with file descriptor 1 (i.e. fname). If the order of redirections were reversed, file descriptor 2 would be associated with the terminal (assuming file descriptor 1 had been) and then file descriptor 1 would be associated with file fname.

If a command is followed by & and job control is not active, then the default standard input for the command is the empty file /dev/null. Otherwise, the environment for the execution of a command contains the file descriptors of the invoking shell as modified by input/output specifications.

The environment (see environ(5)) is a list of name-value pairs that is passed to an executed program in the same way as a normal argument list. The names must be identifiers and the values are character strings. The shell interacts with the environment in several ways. On invocation, the shell scans the environment and creates a parameter for each name found, giving it the corresponding value and marking it export. Executed commands inherit the environment. If the user modifies the values of these parameters or creates new ones, using the export or typeset -x commands they become part of the environment. The environment seen by any executed command is thus composed of any name-value pairs originally inherited by the shell, whose values may be modified by the current shell, plus any additions which must be noted in export or typeset -x commands.

The environment for any simple-command or function may be

BOURNE1.TXT

augmented by prefixing it with one or more parameter assignments. A parameter assignment argument is a word of the form identifier=value. Thus:

```
TERM=450 cmd args          and
```

```
(export TERM; TERM=450; cmd args)
```

are equivalent (as far as the above execution of cmd is concerned).

If the -k flag is set, all parameter assignment arguments are placed in the environment, even if they occur after the command name. The following first prints a=b c and then c:

```
echo a=b c
set -k
echo a=b c
```

Functions.

The function keyword, described in the Commands section above, is used to define shell functions. Shell functions are read in and stored internally. Alias names are resolved when the function is read. Functions are executed like commands with the arguments passed as positional parameters. (See Execution below).

Functions execute in the same process as the caller and share all files, traps (other than EXIT and ERR) and present working directory with the caller. A trap set on EXIT inside a function is executed after the function completes. Ordinarily, variables are shared between the calling program and the function. However, the typeset special command used within a function defines local variables whose scope includes the current function and all functions it calls.

The special command return is used to return from function calls. Errors within functions return control to the caller.

Function identifiers can be listed with the -f option of the typeset special command. The text of functions will also be listed. Function can be undefined with the -f option of the unset special command.

Ordinarily, functions are unset when the shell executes a shell script. The -xf option of the typeset command allows a function to be exported to scripts that are executed

BOURNE1.TXT

without a separate invocation of the shell. Functions that need to be defined across separate invocations of the shell should be placed in the ENV file.

Jobs.

If the monitor option of the set command is turned on, a terminating background job is so noted whenever ksh is writing a prompt. When a job is started asynchronously with &, the shell prints a line which looks like:

```
[1] 1234
```

indicating that the job started asynchronously was job number 1 and had one (top-level) process, whose process id was 1234. It keeps a table of current jobs, printed by the jobs command, and assigns them small integer numbers.

There are several ways to refer to jobs in the shell. The character % introduces a job name. When referring to job number 1, name it as %1. Jobs can also be named by prefixes of the string typed in to invoke them. Thus, 'kill %cc' would kill a background job whose name began with the string "cc" (if there were such a job).

The shell maintains a notion of the current and previous jobs. In output pertaining to jobs, the current job is marked with a + and the previous job with a -. The abbreviation %+ refers to the current job and %- refers to the previous job. %% is also a synonym for the current job.

This shell learns immediately whenever a process changes state. It normally informs the user whenever a job is finished executing, but only just before it prints a prompt. This is done so that it does not otherwise disturb other work.

When attempting to leave a login shell while jobs are running, a warning will be printed that 'You have running jobs'. Use the jobs command to see what they are. If immediately trying exit again, the shell will give a second warning, and the jobs will be terminated.

Job Control.

If a job is running, a ^Z <ctrl>Z can be typed which sends a STOP signal to the current job. The shell will then normally indicate that the job has been 'Stopped', and print another prompt. The state of this job can then be manipulated using the bg command, or running some other

BOURNE1.TXT

commands and then eventually bring the job back into the foreground with the foreground command `fg`. A `^Z` takes effect immediately and is like an interrupt in that pending output and unread input are discarded when it is typed.

A job being run in the background will stop if it tries to read from the terminal. Background jobs are normally allowed to produce output, but this can be disabled by giving the command `stty tostop`. If this `tty` option is set, background jobs will stop when they try to produce output like they do when they try to read input.

Signals.

The `INT` and `QUIT` signals for an invoked command are ignored if the command is followed by `&` and job monitor option is not active. Otherwise, signals have the values inherited by the shell from its parent, with the exception of signal 11 (but see also the `trap` command below).

Execution.

Each time a command is executed, the above substitutions are carried out. If the command name matches one of the Special Commands listed below, it is executed within the current shell process. Next, the command name is checked to see if it matches one of the user defined functions. If it does, the positional parameters are saved and then reset to the arguments of the function call. When the function completes or issues a `return`, the positional parameter list is restored and any trap set on `EXIT` within the function is executed. The value of a function is the value of the last command executed. A function is also executed in the current shell process. If a command name is not a special command or a user defined function, a process is created and an attempt is made to execute the command via `exec(2)`.

The shell parameter `PATH` defines the search path for the directory containing the command. Alternative directory names are separated by a colon (`:`). The default path is `:/bin:/usr/bin` (specifying the current directory, `/bin`, and `/usr/bin`, in that order). Note that the current directory is specified by a null path name, which can appear immediately after the equal sign, between colon delimiters, or at the end of the path list. If the command name contains a `/` then the search path is not used. Otherwise, each directory in the path is searched for an executable file. If the file has execute permission but is not a directory or an `a.out` file, it is assumed to be a file containing shell commands. A sub-shell is spawned to read it. All non-exported aliases, functions, and named

BOURNE1.TXT

parameters are removed in this case. A parenthesized command is also executed in a sub-shell.

Command Re-entry.

The text of the last HISTSIZE (default 128) commands entered from a terminal device is saved in a history file. The file `$HOME/.history` is used if the HISTFILE variable is not set or is not writable. A shell can access the commands of all interactive shells which use the same named HISTFILE. The special command `fc` is used to list or edit a portion this file. The portion of the file to be edited or listed can be selected by number or by giving the first character or characters of the command. A single command or range of commands can be specified. If an editor program is not specified as an argument to `fc`, the value of the parameter FCEDIT is used. If FCEDIT is not defined, `/bin/ed` is used. The edited command(s) is printed and re-executed upon leaving the editor. The editor name `-` is used to skip the editing phase and to re-execute the command. In this case a substitution parameter of the form `old=new` can be used to modify the command before execution. For example, if `r` is aliased to `'fc -e -'` typing `'r bad=good c'` will re-execute the most recent command which starts with the letter `c`, replacing the string `bad` with the string `good`.

In-line Editing Options

Normally, each command line entered from a terminal device is simply typed followed by a new-line ('RETURN' or 'LINE FEED'). If either the `emacs`, or `vi` option is active, the user can edit the command line. To be in either of these edit modes set the corresponding option. An editing option is automatically selected each time the VISUAL or EDITOR variable is assigned a value ending in either of these option names.

The editing features require that the user's terminal accept 'RETURN' as carriage return without line feed and that a space ' ' must overwrite the current character on the screen. ADM terminal users should set the "space - advance" switch to 'space'. Hewlett-Packard series 2621 terminal users should set the straps to 'bcGHxZ etX'.

The editing modes implement a concept where the user is looking through a window at the current line. The window width is the value of COLUMNS if it is defined, otherwise 80. If the line is longer than the window width minus two, a mark is displayed at the end of the window to notify the user. As the cursor moves and reaches the window boundaries

BOURNE1.TXT

the window will be centered about the cursor. The mark is a > (<, *) if the line extends on the right (left, both) side(s) of the window.

Emacs Editing Mode

This mode is entered by enabling either the emacs or gmacs option. The only difference between these two modes is the way they handle ^T. To edit, the user moves the cursor to the point needing correction and then inserts or deletes characters or words as needed. All the editing commands are control characters or escape sequences. The notation for control characters is caret (^) followed by the character. For example, ^F is the notation for control F. This is entered by depressing 'f' while holding down the 'CTRL' (control) key. The 'SHIFT' key is not depressed. (The notation ^? indicates the DEL (delete) key.)

The notation for escape sequences is M- followed by a character. For example, M-f (pronounced Meta f) is entered by depressing ESC (ascii 033) followed by 'f'. (M-F would be the notation for ESC followed by 'SHIFT' (capital) 'F'.) All edit commands operate from any place on the line (not just at the beginning). Neither the "RETURN" nor the "LINE FEED" key is entered after edit commands except when noted.

^F	Move cursor forward (right) one character.
M-f	Move cursor forward one word. (The editor's idea of a word is a string of characters consisting of only letters, digits and underscores.)
^B	Move cursor backward (left) one character.
M-b	Move cursor backward one word.
^A	Move cursor to start of line.
^E	Move cursor to end of line.
^]char	Move cursor to character char on current line.
^X^X	Interchange the cursor and mark.
erase	(User defined erase character as defined by the stty command, usually ^H or #.) Delete previous character.
^D	Delete current character.
M-d	Delete current word.
M-^H	(Meta-backspace) Delete previous word.
M-h	Delete previous word.
M-^?	(Meta-DEL) Delete previous word (if the interrupt character is ^? (DEL, the default) then this command will not work).
^T	Transpose current character with next character in emacs mode. Transpose two previous characters in gmacs mode.

BOURNE1.TXT

^C Capitalize current character.
M-C Capitalize current word.
^K Kill from the cursor to the end of the line. If given a parameter of zero then kill from the start of line to the cursor.
^W Kill from the cursor to the mark.
M-p Push the region from the cursor to the mark on the stack.
kill (User defined kill character as defined by the stty command, usually ^G or @.) Kill the entire current line. If two kill characters are entered in succession, all kill characters from then on cause a line feed (useful when using paper terminals).
^Y Restore last item removed from line. (Yank item back to the line.)
^L Line feed and print current line.
^@ (Null character) Set mark.
M- (Meta space) Set mark.
^J (New line) Execute the current line.
^M (Return) Execute the current line.
eof End-of-file character, normally ^D, will terminate the shell if the current line is null.
^P Fetch previous command. Each time ^P is entered the previous command back in time is accessed.
M-< Fetch the least recent (oldest) history line.
M-> Fetch the most recent (youngest) history line.
^N Fetch next command. Each time ^N is entered the next command forward in time is accessed.
^Rstring Reverse search history for a previous command line containing string. If a parameter of zero is given the search is forward. String is terminated by a "RETURN" or "NEW LINE".
^O Operate - Execute the current line and fetch the next line relative to current line from the history file.
M-digits (Escape) Define numeric parameter, the digits are taken as a parameter to the next command. The commands that accept a parameter are ^F, ^B, erase, ^D, ^K, ^R, ^P and ^N.
M-letter Soft-key - The alias list is searched for an alias by the name _letter and if an alias of this name is defined, its value will be inserted on the line. The letter must not be one of the above meta-functions.
M-_ The last parameter of the previous command is inserted on the line.
M-. The last parameter of the previous command is

BOURNE1.TXT

inserted on the line.

M-* Attempt file name generation on the current word.

^U Multiply parameter of next command by 4.

\ Escape next character. Editing characters, the user's erase, kill and interrupt (normally ^?) characters may be entered in a command line or in a search string if preceded by a \. The \ removes the next character's editing features (if any).

^V Display version of the shell.

vi Editing Mode

There are two typing modes. Initially, when entering a command the user is in the input mode. To edit, the user enters control mode by typing ESC (033) and moves the cursor to the point needing correction and then inserts or deletes characters or words as needed. Most control commands accept an optional repeat count prior to the command.

When in vi mode on most systems, canonical processing is initially enabled and the command will be echoed again if the speed is 1200 baud or greater and it contains any control characters or less than one second has elapsed since the prompt was printed. The ESC character terminates canonical processing for the remainder of the command and the user can then modify the command line. This scheme has the advantages of canonical processing with the type-ahead echoing of raw mode.

If the option viraw is also set, the terminal will always have canonical processing disabled. This mode may be helpful for certain terminals.

Input Edit Commands

By default the editor is in input mode.

erase (User defined erase character as defined by the stty command, usually ^H or #.) Delete previous character.

^W Delete the previous blank separated word.

^D Terminate the shell.

^V Escape next character. Editing characters, the user's erase or kill characters may be entered in a command line or in a search string if preceded by a ^V. The ^V removes the next character's editing features (if any).

\ Escape the next erase or kill character.

BOURNE1.TXT

Motion Edit Commands

These commands will move the cursor.

[count]l Cursor forward (right) one character.
[count]w Cursor forward one alpha-numeric word.
[count]W Cursor to the beginning of the next word that follows a blank.
[count]e Cursor to end of word.
[count]E Cursor to end of the current blank delimited word.
[count]h Cursor backward (left) one character.
[count]b Cursor backward one word.
[count]B Cursor to preceding blank separated word.
[count]fc Find the next character c in the current line.
[count]Fc Find the previous character c in the current line.
[count]tc Equivalent to f followed by h.
[count]Tc Equivalent to F followed by l.
; Repeats the last single character find command, f, F, t, or T.
, Reverses the last single character find command.
0 Cursor to start of line.
^ Cursor to first non-blank character in line.
\$ Cursor to end of line.

Search Edit Commands

These commands access the command history.

[count]k Fetch previous command. Each time k is entered the previous command back in time is accessed.
[count]- Equivalent to k.
[count]j Fetch next command. Each time j is entered the next command forward in time is accessed.
[count]+ Equivalent to j.
[count]G The command number count is fetched. The default is the least recent history command.
/string Search backward through history for a previous command containing string. String is terminated by a "RETURN" or "NEW LINE". If string is null the previous string will be used.
?string Same as / except that search will be in the forward direction.
n Search for next match of the last pattern to / or ? commands.
N Search for next match of the last pattern to / or ?, but in reverse direction. Search history for the string entered by the previous / command.

Text Modification Edit Commands

BOURNE1.TXT

These commands will modify the line.

- a Enter input mode and enter text after the current character.
- A Append text to the end of the line. Equivalent to \$a.
- [count]cmotion
c[count]motion Delete current character through the character motion moves the cursor to and enter input mode. If motion is c, the entire line will be deleted and input mode entered.
- C Delete the current character through the end of line and enter input mode. Equivalent to c\$.
- S Equivalent to cc.
- D Delete the current character through the end of line.
[count]dmotion
d[count]motion Delete current character through the character motion moves the cursor to. Equivalent to d\$. If motion is d, the entire line will be deleted.
- i Enter input mode and insert text before the current character.
- I Insert text before the beginning of the line. Equivalent to the two character sequence ^i.
- [count]P Place the previous text modification before the cursor.
- [count]p Place the previous text modification after the cursor.
- R Enter input mode and replace characters on the screen with characters typed in overlay fashion.
- rc Replace the current character with c.
- [count]x Delete current character.
- [count]X Delete preceding character.
- [count]. Repeat the previous text modification command.
- ~ Invert the case of the current character and advance the cursor.
- [count]_ Causes the count word of the previous command to be appended and input mode entered. The last word is used if count is omitted.
- * Causes an * to be appended to the current word and file name generation attempted. If no match is found, it rings the bell. Otherwise, the word is replaced by the matching pattern and input mode is entered.

Other Edit Commands

BOURNE1.TXT

Miscellaneous commands.

- u Undo the last text modifying command.
- U Undo all the text modifying commands performed on the line.
- [count]v Returns the command `fc -e ${VISUAL:-${EDITOR:-vi}}` count in the input buffer. If count is omitted, then the current line is used.
- ^L Line feed and print current line. Has effect only in control mode.
- ^J (New line) Execute the current line, regardless of mode.
- ^M (Return) Execute the current line, regardless of mode.
- # Equivalent to `I#<cr>`. Useful for causing the current line to be inserted in the history without being executed.

Special Commands.

The following simple-commands are executed in the shell process. Input/Output redirection is permitted. File descriptor 1 is the default output location. Parameter assignment lists preceding the command do not remain in effect when the command completes unless noted.

`: [arg ...]`

Parameter assignments remain in effect after the command completes. The command only expands parameters. A zero exit code is returned.

`. file [arg ...]`

Parameter assignments remain in effect after the command completes. Read and execute commands from file and return. The commands are executed in the current shell environment. The search path specified by PATH is used to find the directory containing file. If any arguments arg are given, they become the positional parameters. Otherwise the positional parameters are unchanged.

`alias [-tx] [name[=value] ...]`

Alias with no arguments prints the list of aliases in the form `name=value` on standard output. An alias is defined for each name whose value is given. A trailing space in value causes the next word to be checked for list tracked aliases. The value of a tracked alias is the full path name corresponding to the given name.

BOURNE1.TXT

The value becomes undefined when the value of PATH is reset but the aliases remained tracked. Without the -t flag, for each name in the argument list for which no value is given, the name and value of the alias is printed. The -x flag is used to set or print exported aliases. An exported alias is defined across sub-shell environments. Alias returns true unless a name is given for which no alias has been defined.

`bg [%job]`

This command is only built-in on systems that support job control. Puts the specified job into the background. The current job is put in the background if job is not specified.

`break [n]`

Exit from the enclosing for while until or select loop, if any. If n is specified then break n levels.

`continue [n]`

Resume the next iteration of the enclosing for while until or select loop. If n is specified then resume at the n-th enclosing loop.

`cd [arg]`

`cd old new`

This command can be in either of two forms. In the first form it changes the current directory to arg. If arg is - the directory is changed to the previous directory. The shell parameter HOME is the default arg. The parameter PWD is set to the current directory. The shell parameter CDPATH defines the search path for the directory containing arg. Alternatedirectorynamesare a colon (:). The default path is <null> (specifying the current directory). Note that the current directory is specified by a null path name, which can appear immediately after the equal sign or between the colon delimiters anywhere else in the path list. If arg begins with a / then the search path is not used. Otherwise, each directory in the path is searched for arg.

The second form of cd substitutes the string new for the string old in the current directory name, PWD and tries to change to this new directory.

The cd command may not be executed by rksh.

BOURNE1.TXT

`eval [arg ...]`

The arguments are read as input to the shell and the resulting command(s) executed.

`exec [arg ...]`

Parameter assignments remain in effect after the command completes. If `arg` is given, the command specified by the arguments is executed in place of this shell without creating a new process. Input/output arguments may appear and affect the current process. If no arguments are given, the effect of this command is to modify file descriptors as prescribed by the input/output redirection list. In this case, any file descriptor numbers greater than 2 that are opened with this mechanism are closed when invoking another program.

`exit [n]`

Causes the shell to exit with the exit status specified by `n`. If `n` is omitted then the exit status is that of the last command executed. An end-of-file will also cause the shell to exit except for a shell which has the `ignoreeof` option (see `set` below) turned on.

`exit [name]`

The given names are marked for automatic export to the environment of subsequently-executed commands.

`fc [-e ename] [-nlr] [first] [last]`

`fc -e - [old=new] [command]`

In the first form, a range of commands from `first` to `last` is selected from the last `HISTSIZE` commands that were typed at the terminal. The arguments `first` and `last` may be specified as a number or as a string. A string is used to locate the most recent command starting with the given string. A negative number is used as an offset to the current command number. If the flag `-l`, is selected, the commands are listed on standard output. Otherwise, the editor program `ename` is invoked on a file containing these keyboard commands. If `ename` is not supplied, then the value of the parameter `FCEDIT` (default `/bin/ed`) is used as the editor. When editing is complete, the edited command(s) is executed. If `last` is not specified, it will be set to `first`. If `first` is not specified the default is the previous command for editing and `-16` for listing. The flag `-r` reverses the order of the commands and the flag `-n` suppresses command numbers

BOURNE1.TXT

when listing. In the second form the most recent command in the history whose first letters match command is re-executed after the substitution old=new is performed.

`fg [%job]`

This command is only built-in on systems that support job control. If job is specified, it brings it to the foreground. Otherwise, the current job is brought into the foreground.

`jobs [-l]`

Lists the active jobs; given the -l option lists process id's in addition to the normal information.

`kill [-sig] process ...`

Sends either the TERM (terminate) signal or the specified signal to the specified jobs or processes. Signals are either given by number or by names (as given in <signal.h>, stripped of the prefix "SIG"). The signal names are listed by 'kill -l'. There is no default, saying just 'kill' does not send a signal to the current job. If the signal being sent is TERM (terminate) or HUP (hangup), then the job or process will be sent a CONT (continue) signal if it is stopped. The argument process can be either a process id or a job.

`let arg ...`

Each arg is an arithmetic expression to be evaluated. All calculations are done as long integers and no check for overflow is performed. Expressions consist of constants, named parameters, and operators. The following set of operators, listed in order of decreasing precedence, are implemented:

-	unary minus
!	logical negation
* / %	multiplication, division, remainder
+ -	addition, subtraction
< >	comparison
== !=	equality inequality
=	arithmetic replacement

Sub-expressions in parentheses () are evaluated first and can be used to override the above precedence rules. The evaluation within a precedence group is from right to left for the = operator and from left to right for the others.

BOURNE1.TXT

A parameter name must be a valid identifier. When a parameter is encountered, the value associated with the parameter name is substituted and expression evaluation resumes. Up to nine levels of recursion are permitted. The return code is 0 if the value of the last expression is non-zero, and 1 otherwise.

`newgrp [arg ...]`

Equivalent to `exec newgrp arg`

`print [-Rnprsu[n]] [arg ...]`

The shell output mechanism. With no flags or with flag `-`, the arguments are printed on standard output as described by `echo(1)`. In raw mode, `-R` or `-r`, the escape conventions of `echo` are ignored. The `-R` option will print all subsequent arguments and options other than `-n`. The `-p` option causes the arguments to be written onto the pipe of the process spawned with `|&` instead of standard output. The `-s` option causes the arguments to be written onto the history file instead of standard output. The `-u` flag can be used to specify a one digit file descriptor unit number `n` on which the output will be placed. The default is 1. If the flag `-n` is used, no new-line is added to the output.

`read [-prsu[n]] [name?prompt] [name ...]`

The shell input mechanism. One line is read and is broken up into words using the characters in `IFS` as separators. In raw mode, `-r`, a `\` at the end of a line does not signify line continuation. The first word is assigned to the first name, the second word to the second name, etc., with leftover words assigned to the last name. The `-p` option causes the input line to be taken from the input pipe of a process spawned by the shell using `|&`. If the `-s` flag is present, the input will be saved as a command in the history file. The flag `-u` can be used to specify a one digit file descriptor unit to read from. The file descriptor can be opened with the `exec` special command. The default value of `n` is 0. If `name` is omitted then `REPLY` is used as the default name. The return code is 0 unless an end-of-file is encountered. An end-of-file with the `-p` option causes cleanup for this process so that another can be spawned. If the first argument contains a `?`, the remainder of this word is used as a prompt when the shell is interactive. If the given file descriptor is

BOURNE1.TXT

open for writing and is a terminal device then the prompt is placed on this unit. Otherwise the prompt is issued on file descriptor 2. The return code is 0 unless an end-of-file is encountered.

`readonly [name ...]`

The given names are marked `readonly` and these names cannot be changed by subsequent assignment.

`return [n]`

Causes a shell function to return to the invoking script with the return status specified by `n`. If `n` is omitted then the return status is that of the last command executed. If `return` is invoked while not in a function then it is the same as an `exit`.

`set [-aefhkmnostuvx] [-o option ...] [arg ...]`

The flags for this command have meaning as follows:

- a All subsequent parameters that are defined are automatically exported.
- e If the shell is non-interactive and if a command fails, execute the `ERR` trap, if set, and exit immediately. This mode is disabled while reading profiles.
- f Disables file name generation.
- h Each command whose name is an identifier becomes a tracked alias when first encountered.
- k All parameter assignment arguments are placed in the environment for a command, not just those that precede the command name.
- m Background jobs will run in a separate process group and a line will print upon completion. The exit status of background jobs is reported in a completion message. On systems with job control, this flag is turned on automatically for interactive shells.
- n Read commands but do not execute them.
- o The following argument can be one of the following option names:
 - `allexport` Same as `-a`.
 - `errexit` Same as `-e`.
 - `emacs` Puts the user in an `emacs` style inline editor for command entry.
 - `gmacs` Puts the user in a `gmacs` style inline editor for command entry.
 - `ignoreeof` The shell will not exit on end-of-file. The command `exit` must be used.

BOURNE1.TXT

keyword	Same as -k.
markdirs	All directory names resulting from file name generation have a trailing / appended.
monitor	Same as -m.
noexec	Same as -n.
noglob	Same as -f.
nounset	Same as -u.
verbose	Same as -v.
trackall	Same as -h.
vi	Puts the user in insert mode of a vi style in-line editor until hitting the escape character 033. This puts the user in move mode. A return sends the line.
viraw	Each character is processed as it is typed in vi mode.
xtrace	Same as -x. If no option name is supplied then the current option settings are printed.
-s	Sort the positional parameters.
-t	Exit after reading and executing one command.
-u	Treat unset parameters as an error when substituting.
-v	Print shell input lines as they are read.
-x	Print commands and their arguments as they are executed.
-	Turns off -x and -v flags and stops examining arguments for flags.
--	Do not change any of the flags; useful in setting \$1 to a value beginning with -. If no arguments follow this flag then the positional parameters are unset.

Using + rather than - causes these flags to be turned off. These flags can also be used upon invocation of the shell. The current set of flags may be found in \$-. The remaining arguments are positional parameters and are assigned, in order, to \$1, \$2, If no arguments are given then the values of all names are printed on the standard output.

shift [n]

The positional parameters from \$n+1 ... are renamed \$1 ..., default n is 1. The parameter n can be any arithmetic expression that evaluates to a non-negative number less than or equal to \$#.

BOURNE1.TXT

test [expr]

Evaluate conditional expression expr. See test(1) for usage and description. The arithmetic comparison operators are not restricted to integers. They allow any arithmetic expression. Four additional primitive expressions are allowed:

-L file

True if file is a symbolic link.

file1 -nt file2

True if file1 is newer than file2.

file1 -ot file2

True if file1 is older than file2.

file1 -ef file2

True if file1 has the same device and i-node number as file2.

times

Print the accumulated user and system times for the shell and for processes run from the shell.

trap [arg] [sig] ...

arg is a command to be read and executed when the shell receives signal(s) sig. (Note that arg is scanned once when the trap is set and once when the trap is taken.) Each sig can be given as a number or as the name of the signal. Trap commands are executed in order of signal number. Any attempt to set a trap on a signal that was ignored on entry to the current shell is ineffective. An attempt to trap on signal 11 (memory fault) produces an error. If arg is omitted or is -, then all trap(s) sig are reset to their original values. If arg is the null string then this signal is ignored by the shell and by the commands it invokes. If sig is ERR then arg will be executed whenever a command has a non-zero exit code. This trap is not inherited by functions. If sig is 0 or EXIT and the trap statement is executed inside the body of a function, then the command arg is executed after the function completes. If sig is 0 or EXIT for a trap set outside any function then the command arg is executed on exit from the shell. The trap command with no arguments prints a list of commands associated with each signal number.

typeset [-FLRZefilprtux[n] [name[=value]] ...]

Parameter assignments remain in effect after the command completes. When invoked inside a function, a new instance of the parameter name is created. The parameter value and type are restored when the function

BOURNE1.TXT

completes. The following list of attributes may be specified:

- F This flag provides UNIX to host-name file mapping on non-UNIX machines.
- L Left justify and remove leading blanks from value. If n is non-zero, it defines the width of the field, otherwise it is determined by the width of the value of first assignment. When the parameter is assigned, it is filled on the right with blanks or truncated, if necessary, to fit into the field. Leading zeros are removed if the -Z flag is also set. The -R flag is turned off.
- R Right justify and fill with leading blanks. If n is non-zero, it defines the width of the field, otherwise it is determined by the width of the value of first assignment. The field is left filled with blanks or truncated from the end if the parameter is reassigned. The L flag is turned off.
- Z Right justify and fill with leading zeros if the first non-blank character is a digit and the -L flag has not been set. If n is non-zero, it defines the width of the field, otherwise it is determined by the width of the value of first assignment.
- e Tag the parameter as having an error. This tag is currently unused by the shell and can be set or cleared by the user.
- f The names refer to function names rather than parameter names. No assignments can be made and the only other valid flag is -x.
- i Parameter is an integer. This makes arithmetic faster. If n is non-zero, it defines the output arithmetic base, otherwise the first assignment determines the output base.
- l All upper-case characters converted to lower-case. The upper-case flag, -u is turned off.
- p The output of this command, if any, is written onto the two-way pipe.
- r The given names are marked readonly and these names cannot be changed by subsequent assignment.
- t Tags the named parameters. Tags are user definable and have no special meaning to the shell.
- u All lower-case characters are converted to upper-case characters. The lower-case flag, -l is turned off.
- x The given names are marked for automatic export to

BOURNE1.TXT

the environment of subsequently-executed commands.

Using + rather than - causes these flags to be turned off. If no name arguments are given but flags are specified, a list of names (and optionally the values) of the parameters which have these flags set is printed. (Using + rather than - keeps the values to be printed.) If no names and flags are given, the names and attributes of all parameters are printed.

`ulimit [-cdfmpt] [n]`

- c Imposes a size limit of n blocks on the size of core dumps (not on UMAX V).
- d Imposes a size limit of n blocks on the size of the data area (not on UMAX V).
- f Imposes a size limit of n blocks on files written by child processes (files of any size may be read).
- m Imposes a soft limit of n blocks on the size of physical memory (not on UMAX V).
- p Changes the pipe size to n (not on UMAX V).
- t Imposes a time limit of n seconds to be used by each process (not on UMAX V).

If no option is given, -f is assumed. If n is not given, the current limit is printed.

`umask [nnn]`

The user file-creation mask is set to nnn (see `umask(2)`). If nnn is omitted, the current value of the mask is printed.

`unalias name ...`

The parameters given by the list of names are removed from the alias list.

`unset [-f] name ...`

The parameters given by the list of names are unassigned, i.e., their values and attributes are erased. Readonly variables cannot be unset. If the flag, -f, is set, then the names refer to function names.

`wait [n]`

Wait for the specified process and report its termination status. If n is not given then all currently active child processes are waited for. The return code from this command is that of the process

BOURNE1.TXT

waited for.

whence [-v] name ...

For each name, indicate how it would be interpreted if used as a command name.

The flag, -v, produces a more verbose report.

Invocation.

If the shell is invoked by `exec(2)`, and the first character of argument zero (`$0`) is `-`, then the shell is assumed to be a login shell and commands are read from `/etc/profile` and then from either `.profile` in the current directory or `$HOME/.profile`, if either file exists. Next, commands are read from the file named by performing parameter substitution on the value of the environment parameter `ENV` (for instance, `$HOME/.kshrc` set in `$HOME/.profile`) if the file exists. Commands are then read as described below; the following flags are interpreted by the shell when it is invoked:

- c string If the `-c` flag is present then commands are read from string.
- s If the `-s` flag is present or if no arguments remain then commands are read from the standard input. shell output, except for the output of some of the Special Commands listed above, is written to file descriptor 2.
- i If the `-i` flag is present or if the shell input and output are attached to a terminal, this shell is interactive. In this case `TERMINATE` is ignored (so that `kill 0` does not kill an interactive shell) and `INTERRUPT` is caught and ignored (so that `wait` is interruptible). In all cases, `QUIT` is ignored by the shell.
- r If the `-r` flag is present the shell is a restricted shell.

The remaining flags and arguments are described under the `set` command above.

rksh Only.

`rksh` is used to set up login names and execution environments whose capabilities are more controlled than those of the standard shell. The actions of `rksh` are identical to those of `ksh`, except that the following are disallowed:

BOURNE1.TXT

changing directory (see `cd(1)`),
setting the value of `SHELL` or `PATH`,
specifying path or command names containing `/`,
redirecting output (`>` and `>>`).

The restrictions above are enforced after `.profile` and the `ENV` files are interpreted.

When a command to be executed is found to be a shell procedure, `rksh` invokes `ksh` to execute it. Thus, it is possible to provide to the end-user shell procedures that have access to the full power of the standard shell, while imposing a limited menu of commands; this scheme assumes that the end-user does not have write and execute permissions in the same directory.

The net effect of these rules is that the writer of the `.profile` has complete control over user actions, by performing guaranteed setup actions and leaving the user in an appropriate directory (probably not the login directory).

The system administrator often sets up a directory of commands (i.e., `/usr/rbin`) that can be safely invoked by `rksh`. Some systems also provide a restricted editor `/bin/red`.

EXIT STATUS

Errors detected by the shell, such as syntax errors, cause the shell to return a non-zero exit status. If the shell is being used non-interactively then execution of the shell file is abandoned. Otherwise, the shell returns the exit status of the last command executed (see also the `exit` command above).

FILES

`/etc/passwd`
`/etc/profile`
`$HOME/.profile`
`$HOME/.kshrc`
`/tmp/sh*`
`/dev/null`

SEE ALSO

`cat(1)`, `cd(1)`, `echo(1)`, `emacs(1)`, `env(1)`, `gmacs(1)`,
`newgrp(1)`, `shl(1)`, `test(1)`, `umask(1)`, `vi(1)`.
`dup(2)`, `exec(2)`, `fork(2)`, `pipe(2)`, `signal(2)`, `umask(2)`,
`ulimit(2)`, `wait(2)`, `rand(3C)`, `a.out(4)`, `profile(4)` in the
`UMAX V Programmer's Reference Manual`.

